

# ReportServer

Configuration Guide 4.3.0





# ReportServer

## Configuration Guide 4.3.0

InfoFabrik GmbH, 2022

<http://www.infofabrik.de/>  
<http://www.reportserver.net/>



Copyright 2007 - 2022 InfoFabrik GmbH. All rights reserved.

This document is protected by copyright. It may not be distributed or reproduced in whole or in part for any purpose without written permission of InfoFabrik GmbH. The information included in this publication can be changed at any time without prior notice.

All rights reserved.

---

# Contents

<b>Contents</b>	<b>i</b>
<b>1 Preamble</b>	<b>3</b>
<b>2 Installation</b>	<b>5</b>
2.1 Automatic Installation . . . . .	5
2.2 Manual Installation . . . . .	5
2.3 Running ReportServer on JBoss Wildfly . . . . .	8
2.4 Installing the Demo Data . . . . .	9
<b>3 External Configuration Files</b>	<b>11</b>
3.1 persistence.properties . . . . .	11
3.2 reportserver.properties . . . . .	13
<b>4 Configuration</b>	<b>19</b>
4.1 Datasources . . . . .	20
4.2 Dynamic Lists . . . . .	23
4.3 Setting up the Scheduler . . . . .	24
4.4 Export settings . . . . .	31
4.5 UI Customization . . . . .	32
4.6 Extensions . . . . .	37
4.7 Executing Reports using URLs . . . . .	38
4.8 Misc Settings . . . . .	38
4.9 Scheduler Settings . . . . .	39
4.10 Localization Settings . . . . .	39
4.11 Security related properties . . . . .	41
4.12 SSO related properties . . . . .	46
4.13 LDAP . . . . .	46
<b>5 External Configdir</b>	<b>51</b>
<b>A Config File Reference</b>	<b>55</b>









# Preamble

## Business Intelligence

Business Intelligence (BI) describes the ability to jointly analyze all of a company's data, distilling relevant information to be used to foster better business decisions. The foundation of any BI solution is the careful preprocessing of existing data, for example, in a data warehouse.

ReportServer acts as the gateway between end-users and the collected data, allowing users to efficiently access and analyze the available data. From camera-ready evaluations to fine-grained ad-hoc reporting; ReportServer provides you with the tools to support your daily work.

## Target Audience

This document is designed for future administrators of ReportServer.

Separate manuals and instructions illustrate the various aspects of ReportServer.

**ReportServer Configuration Guide:** Describes the installation of ReportServer as well as the basic configuration options.

**ReportServer User Guide:** The user guide describes ReportServer from the point of view of the ultimate user. It includes an in-depth coverage of dynamic lists (ReportServer's adhoc reporting solution), execution of reports, scheduling of reports, and much more.

**ReportServer Administrator Guide:** The administrator guide describes ReportServer from the point of view of administrators that are tasked with maintaining the daily operation of the reporting platform including the development of reports, managing users and permissions, monitoring the system state, and much more.

**ReportServer Scripting Guide:** The ReportServer scripting guide covers the scripting capabilities of ReportServer which can be used for building complex reports as well as for extending the functionality of ReportServer or performing critical maintenance tasks. It extends the introduction to these topics given in the administrator guide.



---

# Installation

ReportServer is a web-application based on the Java Servlet technology and, thus, runs in an application server (such as Apache Tomcat). Being a Java application ReportServer supports any operating system that has a Java runtime environment and for which a supported application server is available. All application metadata is stored in a relational database.

ReportServer is available for download in .zip file format for deployment within an application server. Additional options, including native installers for various platforms, virtual machines and cloud images are provided by means of the Bitnami ReportServer Stack.

While the manual installation provides the most flexibility, it requires some prior knowledge about the deployment of web applications and the operating of an application server, so we recommend this for system administrators and advanced users. The Bitnami packages on the other hand are completely self contained and can be installed with only a couple of clicks.

You can download ReportServer from <http://reportserver.net/download>.

## 2.1 Automatic Installation

The Bitnami ReportServer Stack is available for Windows, Linux and Mac OS and provides a pre-configured installation of ReportServer with Apache Tomcat as application server and MariaDB as database backend. The installers are available from <http://reportserver.net/download> or directly from Bitnami. The installation wizard guides you through the installation providing you with the option to pre-configure parts of ReportServer and you can choose whether to install the demo package or not (we note that you can also manually install the demo data later; see Section 2.4). In case you already have an application server or MariaDB database running and the default ports are in use, you are asked to provide alternative ports. Documentation on the installation via the Bitnami installer is provided by Bitnami and can be accessed from <https://bitnami.com/stack/reportserver/README.txt>.

## 2.2 Manual Installation

The manual installation allows you to fine-tune the installation process to your environment and is generally recommended for any production environment.

### Installation of the Java Runtime Environment (JRE)

ReportServer requires an installed Java Runtime Environment (JRE) in version 11 or newer.

As of Java 11 or newer, you need some extra configuration which can be done in the `setenv.bat` / `setenv.sh` of your Tomcat environment. Specifically, the following configuration is needed:

- `-add-opens=java.base/java.net=ALL-UNNAMED`
- `-add-opens=java.base/jdk.internal.ref=ALL-UNNAMED`
- `-add-opens=java.base/jdk.internal.reflect=ALL-UNNAMED`
- `-Djavax.net.ssl.trustStoreType=JKS`

The following is an example configuration in our Bitnami packages where the configuration mentioned above is integrated:

```
set JAVA_OPTS=++JvmOptions="-Drs.configdir=C:/Bitnami/↵
↵ reportserverenterprise-3.3.0.6030-0/apps/reportserver/↵
↵ reportserver-conf" ++JvmOptions="-Dfile.encoding=UTF8" ++↵
↵ JvmOptions="--add-opens=java.base/java.net=ALL-UNNAMED" ++↵
↵ JvmOptions="--add-opens=java.base/jdk.internal.ref=ALL-UNNAMED" ↵
↵ ++JvmOptions="-Djavax.net.ssl.trustStoreType=JKS" --JvmMs 512 --↵
↵ JvmMx 1536
set JDK_JAVA_OPTIONS= %JDK_JAVA_OPTIONS%
```

**Tip.** If the host computer supports it, you should use the 64-bit edition.

### Installation and configuration of the application server

ReportServer can be configured to run in any application server that supports the Java Servlet Technology (e.g., Jetty, Tomcat or JBoss Wildfly). We recommend using Apache Tomcat (<http://tomcat.apache.org/>).

In order to smoothly run ReportServer it is necessary to provide the application server with sufficient memory which usually means that you have to increase the default values. If too little memory is available then ReportServer might not start at all or your users might experience performance problems. The following recommendations are to be understood as lower bounds. Depending on your environment (the types of reports that you want to run and the number of users the system is to handle) you might need to increase these (especially the available heap size).

We recommend to set the available permanent generation space (PermGenSpace) to at least 256mb (better 512mb). The maximal available heap size should be at least 1.5gb.

Furthermore, the encoding should be set to UTF8.

A sample configuration of the VM might look as follows:

```
-Xmx4096M
-XX:MaxPermSize=512M
-Dfile.encoding=UTF8
```

Further information can be found, for example, at <http://www.oracle.com/technetwork/java/javase/tech/vmoptions-jsp-140102.html>.

## Unpack the zip-archive

Stop the application server, if it was running, and unpack the ReportServer archive to a directory called reportserver below the webapps directory of your application server (on Windows this could be, for example, C:\Program Files\Apache Tomcat\webapps; on Linux /var/tomcat/webapps).

## Setup the database

Before we can start the application server we need to configure the database connection that ReportServer uses to store its metadata. ReportServer internally uses JPA with Hibernate (<http://www.hibernate.org/>) which allows us to support most popular database systems. A list of the database systems supported by Hibernate can be found at <https://developer.jboss.org/docs/DOC-13921>.

## Installation of the JDBC driver

ReportServer comes bundled with drivers for the open source databases MySQL (<http://www.mysql.com>) and PostgreSQL (<http://www.postgresql.org>). If you use either of these databases you do not need to manually copy the jdbc driver to the lib directory. If you use any other database you need to copy the corresponding JDBC driver to ReportServer's lib directory, that is, to directory:

```
path_to_webapps/reportserver/WEB-INF/lib.
```

## Creating the ReportServer schema

Next we need to setup the necessary database tables. For this, choose the create script corresponding to your database system from the directory "ddl" (directly beneath the reportserver directory) and execute it on your database. For a PostgreSQL database, for example, use the file:

```
reportserver-RS3.3.0-6030-schema-PostgreSQL_CREATE.sql.
```

## Adapt the persistence.properties config file

To complete the database setup we need to configure the connection properties. For this, go to WEB-INF/classes and edit the file persistence.properties. The file persistence.properties contains the configuration of the ReportServer database connection. You can find further information on this config file in Chapter 3. Following is a sample configuration for MySQL.

```
hibernate.dialect=net.datenwerke.rs.utils.hibernate.MySQL5Dialect
hibernate.connection.driver_class=com.mysql.cj.jdbc.Driver
hibernate.connection.url=jdbc:mysql://localhost:3306/reportserver
hibernate.connection.username=root
hibernate.connection.password=root
```

### The config file `reportserver.properties`

The final step in the installation is to check the (and possibly adapt) the main configuration settings. These are stored in the the config file `reportserver.properties` which is located in the `WEB-INF/classes` directory. It contains basic properties concerning the available authentication procedures used by ReportServer as well as configuration for cryptographic functionality used in ReportServer.

A detailed description of the available parameters are given in Chapter 3 [External Configuration Files](#).

### Application Server Start

You can now start the application server. Once the application server is started up ReportServer should be accessible, for example, under the URL <http://localhost:8080/reportserver>. ReportServer has generated the root user with which you can login:

```
username: root
password: root
```

## 2.3 Running ReportServer on JBoss Wildfly

To run ReportServer on JBoss Wildfly only a few configuration options need to be considered. First, you should ensure that JBoss is configured to use sufficient memory. The necessary changes can be made in file `wildfly/bin/standalone.conf` (or `standalone.conf.bat` for windows systems). To run ReportServer you should provide JBoss with at least 1.5 GB of heap space. Depending on the number of users, this value should be increased. Following is an example configuration:

```
JAVA_OPTS="-Xms64m -Xmx2g -XX:MaxPermSize=256m -Djava.net.preferIPv4Stack=true"
```

Besides increasing the memory as described above, you will need to add an application descriptor file called `jboss-deployment-structure.xml`. You will need to place this configuration file into the `WEB-INF` directory of ReportServer. Following is the content of the descriptor.

```
<?xml version="1.0" encoding="UTF-8"?>
<jboss-deployment-structure>
  <deployment>
    <exclusions>
      <module name="org.hibernate" />
      <module name="org.antlr" />
    </exclusions>
    <exclude-subsystems>
      <subsystem name="weld" />
      <subsystem name="org.hibernate" />
      <subsystem name="org.hibernate.validator" />
      <subsystem name="org.antlr" />
      <subsystem name="jpa" />
    </exclude-subsystems>
    <dependencies>
      <module name="org.bouncycastle" />
    </dependencies>
  </deployment>
</jboss-deployment-structure>
```

Having increased the memory and added the `jboss-deployment-structure.xml` to the ReportServer WEB-INF directory, you are now good to go.

## 2.4 Installing the Demo Data

ReportServer comes with a demo data package containing the example setup of the fictionally toy company “1-to-87”. In order to install the demodata package you should login with a root account (if you used the Bitnami installer, this would be the account you setup during installation). Also note that the **installation of the demodata will remove any existing data in the system**. To install the demo package login to ReportServer and open the terminal by pressing

```
CTRL+ALT+T
```

Then, to initiate the installation, run the command

```
pkg install -d demobuilder-VERSION_NR
```

Here, “VERSION\_NR” must be replaced by the correct version, which can be obtained by using the autocomplete feature of the terminal. Simply hit TAB to get a list of options:

```
pkg install -d [TAB]
```





---

# External Configuration Files

ReportServer has only two (external) config files which hold information on the database connection as well as information on available authentication methods. All other configuration is done from within ReportServer. The file `persistence.properties` (in directory `WEB-INF/classes`) holds information on the *database connection* that is used by ReportServer. The configuration file `reportserver.properties` (in the same directory) holds information about *available authentication schemes*, as well as, *cryptography related properties*.

By default the external configuration files are located in `WEB-INF/classes` and thus within the web-apps folder. It is advisable to move these files to an external location as this allows easier upgrades to future versions. For a detailed description of how to use an external configuration dir see Chapter 5.

## 3.1 persistence.properties

ReportServer uses the Java Persistence API (JPA) to abstract from the actual database system when storing application data. The necessary configuration is made in the `persistence.properties` config file.

Example

```
hibernate.dialect=net.datenwerke.rs.utils.hibernate.MySQL5Dialect
hibernate.connection.driver_class=com.mysql.cj.jdbc.Driver
hibernate.connection.url=jdbc:mysql://localhost:3306/reportserver
hibernate.connection.username=rs
hibernate.connection.password=rs
```

Note that to configure the JPA/Hibernate settings, we are not editing the standard JPA configuration file (usually called `persistence.xml`) but a ReportServer properties file.

### Connection properties

ReportServer supports all databases that are supported by Hibernate. A list of the database systems supported by Hibernate can be found on the hibernate webpages<sup>1</sup>. We recommend to run

---

<sup>1</sup><https://developer.jboss.org/docs/DOC-13921>

### 3. External Configuration Files

---

ReportServer on one of the following databases for which we now give example configurations:

#### Example config for *MySQL*

```
# MySQL
hibernate.dialect=net.datenwerke.rs.utils.hibernate.MySQL5Dialect
hibernate.connection.driver_class=com.mysql.cj.jdbc.Driver
hibernate.connection.url=jdbc:mysql://localhost:3306/reportserver
hibernate.connection.username=rs
hibernate.connection.password=rs
```

Note the custom dialect `net.datenwerke.rs.utils.hibernate.MySQL5Dialect`.

#### Example config for *MariaDB*

```
# MariaDB
hibernate.dialect=net.datenwerke.rs.utils.hibernate.MariaDbDialect
hibernate.connection.driver_class=org.mariadb.jdbc.Driver
hibernate.connection.url=jdbc:mariadb://localhost:3306/reportserver
hibernate.connection.username=rs
hibernate.connection.password=rs
```

#### Example config for *PostgreSQL*

```
# PostgreSQL
hibernate.dialect=net.datenwerke.rs.utils.hibernate.↵
↳ PostgreSQLDialect
hibernate.connection.driver_class=org.postgresql.Driver
hibernate.connection.url=jdbc:postgresql://localhost/postgres
hibernate.connection.username=rs
hibernate.connection.password=rs
hibernate.connection.autocommit=false
```

#### Example config for *Oracle*

```
# Oracle
#
# Select ONE of the following dialects depending on your Oracle ↵
↳ version
#
hibernate.dialect=net.datenwerke.rs.utils.hibernate.Oracle10gDialect
# hibernate.dialect=net.datenwerke.rs.utils.hibernate.↵
↳ Oracle12cDialect
#
hibernate.connection.driver_class=oracle.jdbc.driver.OracleDriver
hibernate.connection.url=jdbc:oracle:thin:@localhost:1521:MYDB
hibernate.connection.username=rs
hibernate.connection.password=rs
hibernate.connection.autocommit=false
```

#### Example config for *SQL Server*

```
# SQL Server
hibernate.dialect=net.datenwerke.rs.utils.hibernate.↵
↳ SQLServer2008Dialect
```

```
hibernate.connection.driver_class=com.microsoft.sqlserver.jdbc.↵
↳ SQLServerDriver
hibernate.connection.url=jdbc:sqlserver://localhost/sqlserver:1433;↵
↳ databaseName=mydb
hibernate.connection.username=rs
hibernate.connection.password=rs
hibernate.connection.autocommit=false
```

Note, that the JDBC driver corresponding to your database must be copied to the directory `path_to_webapps/reportserver/WEB-INF/lib` or to your external-configuration directory.

### Connection Pool (C3P0) Settings

Hibernate uses the C3P0 connection pool. The following properties allow to configure C3P0 as used by Hibernate. Note that this does not have any effect on the connection pool used by ReportServer for handling reporting.

```
hibernate.c3p0.acquire_increment=5
hibernate.c3p0.idle_test_period=60
hibernate.c3p0.timeout=3600
hibernate.c3p0.max_size=30
hibernate.c3p0.max_statements=0
hibernate.c3p0.min_size=5
```

See also <http://www.mchange.com/projects/c3p0/index.html#configuration>.

The most commonly used properties are:

Property	Description
<code>acquire_increment</code>	Defines how many connections are acquired simultaneously by c3p0, if all connections currently in the pool are busy.
<code>idle_test_period</code>	If not zero, C3P0 will test idle connections in this intervall.
<code>timeout</code>	Number of seconds a pooled connection can remain idle before it is discarded. Zero means that idle connections are never discarded.
<code>max_size</code>	Maximum number of connections in the pool.
<code>max_statements</code>	Maximal size of the statement cache. Zero means that statements should not be cached.
<code>min_size</code>	The minimum number of connections to be kept in the pool.

## 3.2 reportserver.properties

The config file `reportserver.properties` contains settings which are needed at ReportServer startup time as well as settings concerning cryptographic functionality. All properties are stored as attribute value pairs.

Excerpt from the `reportserver.properties` file

```
rs.crypto.pbe.passphrase = The Passphrase
rs.crypto.pbe.keylength = 128
```

#### Crypto settings

Passwords (such as, for example, datasource passwords<sup>2</sup>) that are stored in ReportServer will be encrypted. ReportServer uses AES and password based encryption. For this, you need to configure the following properties:

– `rs.crypto.pbe.salt`

the salt that is used on key generation by the password based encryption method. This value should be set to a long random string.

– `rs.crypto.pbe.keylength`

The key size used. Keep in mind that key sizes over 128 require the Java Cryptography Extension (JCE) Unlimited Strength Jurisdiction Policy Files. For more information, see <http://www.oracle.com/technetwork/java/javase/downloads/index.html>.

For secure storage of user passwords ReportServer uses the salted HMAC construction.

– `rs.crypto.passwordhasher.hmac.passphrase`

Defines the static part of the salt for the salted HMAC construction. This value should be set to a long random string.

#### Authentication settings

ReportServer supports several methods for user authentication. The different methods can also be combined.

– `rs.authenticator.pams`

This parameter defines which authentication methods are to be used. The individual values are separated by a colon.

Note that the default PAMs usually come in two variants, one being called **Authoritative**, e.g. `UserPasswordPAMAuthoritative`, or `LdapPAMAuthoritative`. The difference between the two variants (the non-authoritative and the authoritative variant) is how they handle the case where they cannot find the necessary information within the provided list of tokens. The authoritative version then denies access, while the non-authoritative version opts for letting someone else decide (can't tell, let another PAM in the list decide). More details on this can be found in the Script Guide.

The following authenticator modules are available

`net.datenwerke.rs.authenticator.service.pam.UserPasswordPAM`

This is the standard mechanism and allows users to authenticate using a username and password. Note: with this authentication method username and password are sent to the server in the clear.

---

<sup>2</sup>We note that for user passwords only a salted hash is stored. Passwords that need to be recoverable, such as database passwords, are stored encrypted.

Thus, this method should only be used over a secure channel (such as TLS/SSL). If you are not in a secured environment choose the *ChallengeResponsePAM* instead.

```
net.datenwerke.rs.authenticator.service.pam.IPRestrictionPAM
```

With this method you can restrict the set of IP addresses that can access ReportServer. The allowed address ranges are configured in `rs.authenticator.iprestriction.addresses`. The individual values are separated by a colon. Example: `rs.authenticator.iprestriction.addresses ↵ = 127.0.0.1/32:192.168.1.0/24`

```
net.datenwerke.rs.authenticator.service.pam.EveryoneIsRootPAM
```

This method will disable authentication and log in all users as root.

```
net.datenwerke.rs.authenticator.cr.service.pam.ChallengeResponsePAM
```

This method is similar to the *UserPasswordPAM* but the password is transmitted securely to the server. In cases where the connection is not secured via SSL this is the recommended authentication method. Note though, that this requires the client browser to perform cryptographic tasks which may be slow on non-up-to-date browsers.

```
net.datenwerke.rs.authenticator.service.pam.ClientCertificateMatchEmailPAM
```

If your organization uses *x509 certificates*, you can use this method to allow users to log in with their client certificates.

```
net.datenwerke.rs.ldap.service.ldap.pam.LdapPAM
```

If your organization uses LDAP and you want to allow LDAP authentication, you can use this method to allow users to log in with their LDAP credentials. Note that you previously have to import your LDAP users as described in the Admin Guide: <https://reportserver.net/en/guides/admin/chapters/Integrating-ReportServer-with-an-Active-Directory-using-LDAP/>

```
rs.authenticator.pam.ClientCertificateMatchEmailPAM.debug
```

This parameter allows to enable debug mode for client certificate authentication.

```
- rs.authenticator.blockroot
```

Setting this to true disables direct access using the root user. This is recommended for production environments. Note that you can switch to the root user using `sudo` if you need to perform administrative tasks (and you have the corresponding privileges). Further information on `sudo` can be found in the *administration guide*.

## General settings

```
rs.install.basedata
```

Setting this to true installs base data if the database is empty, i.e. during a first run. This includes

### 3. External Configuration Files

---

the audit log and other data.

`rs.scripting.disable`

If this property is set to `true`, scripting is completely disabled, so no scripts are run, including the `onlogin` and `onstartup` scripts. Thus, should you find yourself locked out of ReportServer, you can disable any scripts via this property. Since no scripts will be executed you can then login correctly to ReportServer.

`rs.scheduler.disable`

You can completely disable the scheduler by setting this property to `true`. If the property is set to `true` both in `reportserver.properties` and the analogous property is also set to `true` in `/fileserver/etc/scheduler/scheduler.cf`, the property set in `reportserver.properties` is taken into account, while the one set in `/fileserver/etc/scheduler/scheduler.cf` is ignored. This allows you to completely avoid running scheduled jobs if you don't have the possibility to log in and disable the scheduler quickly enough before any jobs are being executed.







---

# Configuration

ReportServer is now up and running. In the following section we describe configuration options affecting the operation of ReportServer. The present document should be considered as a reference containing a brief description of the various configuration options. Keep in mind that the settings described here affect all areas of ReportServer which to describe is beyond the scope of this *config guide*. See the *administrator's* and *user's guide* for further information to the various areas of ReportServer. Sample configurations can be found in Appendix A.

All configuration files described in this section can be found in ReportServer's internal filesystem. You can access the internal filesystem using the administration module (administration/ file system) or using the terminal: you can open the terminal by pressing `CTRL+ALT+T`.

**Tip.** Default configuration files are created on first run of ReportServer. Later, when upgrading ReportServer to a newer version, it is probable that newly added configuration files will be missing (i.e. all configuration files added between the version originally installed and the version upgraded to). You can use the "diffconfigfiles" command for getting help on this, check the Administration Guide for details. Note that default values are used for configuration files that are not found.

By using the command `editTextFile` you can edit files directly from the terminal. You can also create new files using the command `createTextFile`. For further information on the workings of the terminal see the *administrator's guide*. Using the graphical user interface, you can select files similar to selecting files when working in the Explorer in your operating system. To do this, go to administration/file system. To edit a file, choose the tab `Edit file`. Note that the edit file tab is only available for text files and if a proper mime-type is specified.

Please note, that after changing a config file you need to run the terminal command `config reload` for the change to take effect.

Configuration files in ReportServer are usually defined in an XML format.

### 4.1 Datasources

In this section we will cover:

- how to define the default datasource,
- how to define datasource bundles (only available in ReportServer Enterprise),
- how to configure the connection pool,
- how to configure the internal db

#### Defining the Default Datasource

ReportServer allows to configure a single default datasource. The default datasource can then be accessed with only a single mouse click when working with reports and parameters. The default datasource is set in the file `/fileserver/etc/datasources/datasources.cf`.

You can use the name of the datasource, or use the ID of the datasource, for the assignment. Use one of the two variants for the configuration:

```
<defaultDataSourceName>Myds</defaultDataSourceName>  
<defaultDataSourceId>12</defaultDataSourceId>
```

**Remark.** Keep in mind that the datasource name is case sensitive.

#### Configuring the Connection Pool

By default, ReportServer will pool connections to relational database systems. This increases the stability of the system, since you can define an upper limit of simultaneously open connections and, furthermore, it improves the performance at the same time since database connections are kept open and ready for use.

The connection pools can be configured both globally and per datasource. The configuration is done in the file `/fileserver/etc/datasources/pool.cf`.

To not use connection pools, change the attribute “disable” to “true”: `<pool disable="true">`.

ReportServer uses the library C3P0 (<http://www.mchange.com/projects/c3p0/>) to perform connection pooling. To globally set a property, set the property within the `<defaultconfig>` tags. For data-source-specific settings, use the tag `<pool16>`, where 16 is the ID of the data source.

```
<?xml version="1.0" encoding="UTF-8"?>  
<configuration>  
  <pool>  
    <defaultconfig>  
      <maxPoolSize>40</maxPoolSize>  
      <initialPoolSize>10</initialPoolSize>  
      <acquireRetryAttempts>10</acquireRetryAttempts>  
      <acquireRetryDelay>500</acquireRetryDelay>
```

```

    <checkoutTimeout>60000</checkoutTimeout>
    <maxConnectionAge>7200</maxConnectionAge>
    <maxIdleTime>3600</maxIdleTime>
  </defaultconfig>
  <pool16>
    <acquireRetryAttempts>20</acquireRetryAttempts>
  </pool16>
</pool>
</configuration>

```

The possible configuration settings of C3P0 can be found at [http://www.mchange.com/projects/c3p0/#configuration\\_properties](http://www.mchange.com/projects/c3p0/#configuration_properties). ReportServer simply passes on any set property to C3P0.

Note that as of ReportServer 4.0.0, the current state of the connections (including total max pool size, busy connections and number of connections) is visualized in the "Connection Pool" System Console.

## Internal database

ReportServer uses a database to buffer data coming from non-database datasources such as, for example, CSV datasources. This *buffer database* is called the *internal database*. Per default ReportServer uses its own database for this and creates tables with the prefix *rs\_tmptbl\_*. You can change the database to be used as well as configure certain aspects of the internal database via the configuration file *datasources/internaldb.cf*. The default configuration file is

```

<configuration>
  <internaldb>
    <droponstartup>true</droponstartup>
    <datasource>ReportServer Data Source</datasource>
  </internaldb>
</configuration>

```

The *droponstartup* tells ReportServer to remove any temporary tables on startup. This should only be turned off for debugging purposes as having old temporary tables still available after startup will cause errors when using the internal DB. Via the *datasource* tag you can define the datasource (via its name) to be used as the internal database.

## SQL limits and parameter options

The datasource parameter (a parameter that can be used to allow the user to select values from a predefined set) can return a single value or a list of values. If a user selects multiple values (or uses many filters in a dynamic list) this might lead to problems with certain database systems. This is due to the fact that the number of values that can be used in IN clauses is limited for most database systems.

You can specify the maximum number of values that are to be used in an IN clause in the file */fileservers/etc/datasources/sql.cf*. ReportServer will then distribute the selected values over multiple IN-clauses.

For this set the following parameter

## 4. Configuration

---

```
<incondition>
  <maxsize>1000</maxsize>
</incondition>
```

in accordance with the prerequisites of the used database system.

### The datasource parameter

Queries that run for a long time have an impact on the performance of ReportServer. You can specify how long ReportServer should wait for the results of a parameter query. A parameter query is executed when a report is opened.

You can specify a timeout for long running parameter queries in the configuration file `/fileserver/etc/datasources/parameter.cf`.

Set the parameter `<querytimeout>60</querytimeout>` to stop queries after 60 seconds.

If you want to use the “post-processing” feature of the datasource parameter enable it using the following lines:

```
<postprocessing>
  <enable>true</enable>
</postprocessing>
```

**Tip.** In general it is good practice to have parameter queries optimized such that they run very fast such as to provide a good user experience.

The post-processing feature, for example, allows to switch parameter values or perform complex string operations. Learn more about datasource parameter post-processing in the *parameter chapter* in the *administrator's guide*.

### Datasinks

Datasinks can be enabled/disabled in the `/fileserver/etc/datasinks/datasinks.cf` file. Here you have an entry similar as the following for each supported datasink type:

```
<configuration>
  <sftp disabled="false" supportsScheduling="true" />
  <ftp disabled="false" supportsScheduling="true" />
</configuration>
```

The `disabled` option controls if the datasink is overall enabled or disabled. Further, scheduling via datasinks can be enabled or disabled via the `supportsScheduling` setting. Note that you can not enable scheduling if the datasink is overall disabled.

### SFTP and FTP Datasinks

Datasinks are supported as of ReportServer 3.4.0. The legacy FTP configuration in `/fileserver/etc/exportfilemd/storage.cf` is ignored as of version 3.4.0.

For the SFTP datasink to work, you have to add your SFTP host to your `.ssh/known_hosts` file ([https://en.wikibooks.org/wiki/OpenSSH/Client\\_Configuration\\_Files#~/.ssh/known\\_hosts](https://en.wikibooks.org/wiki/OpenSSH/Client_Configuration_Files#~/.ssh/known_hosts)) in order to verify the identity of the remote host, thus protecting against impersonation or man-in-the-middle attacks. Its location be configured in the `/filesserver/etc/security/misc.cf` file as follows.

```
<?xml version="1.0" encoding="UTF-8"?>
<configuration>
  <knownHosts>/path/to/.ssh/known\_hosts</knownHosts>
</configuration>
```

For manually adding a public key to the `.ssh/known_hosts` file, check here: [https://en.wikibooks.org/wiki/OpenSSH/Client\\_Configuration\\_Files#Manually\\_Adding\\_Public\\_Keys\\_to\\_~/.ssh/known\\_hosts](https://en.wikibooks.org/wiki/OpenSSH/Client_Configuration_Files#Manually_Adding_Public_Keys_to_~/.ssh/known_hosts).

## Email SMTP Datasinks

As of ReportServer 3.7.0, the old `mail/mail.cf` configuration file is deprecated. Instead, Email SMTP datasinks should be used together with a default email datasink, which can be defined in the `/etc/datasinks/datasinks.cf` configuration file as follows.

```
<email disabled="false" supportsScheduling="true">
  <defaultDatasinkName>Default Email Datasink</defaultDatasinkName>
  <!-- or access via ID -->
  <!-- <defaultDatasinkId>14</defaultDatasinkId> -->
</email>
```

You can use the name of the datasink, or use the ID of the datasink, for the assignment. Use one of the two variants above for the configuration.

Note that you can configure a default datasink per datasink type, so this is not limited to email SMTP datasinks.

## 4.2 Dynamic Lists

In Dynamic Lists, users can use Computed Columns. Computed columns allow users to extend the list of columns by fields which do not exist in the source but which can be constructed from existing fields. Computed Columns are based on SQL.

In `/filesserver/etc/dynamiclists/computedcolumn.cf` you can specify which SQL functions can be used with Computed Columns.

Add those functions that may be used by your users.

Example:

```
<function>abs</function>
```

Note that SQL functions vary depending on the database system.

## 4. Configuration

---

We strongly recommend against allowing to use functions that can change data. Further, the database user used for report execution should not have write access.

### Theming

In ReportServer Enterprise Edition you can change how the PDF and HTML output of a dynamic list is outlined. Further information on this can be found in the Administration Guide.

## 4.3 Setting up the Scheduler

With ReportServer you can schedule reports and distribute the result either using mail, directly into a *TeamSpace*, or sent to a SFTP/FTP/FTPS server, among others (check datasink documentation for more details). The next section discusses important settings.

### Mail Server Configuration

Note that the old `/fileserver/etc/mail/mail.cf` configuration file is deprecated. Please use email SMTP datasinks instead together with the default email datasink configuration.

In order for ReportServer to be able to send mails you must specify the mail server settings. Make the following configurations in your Email SMTP datasink.

Setting up the SMTP server. Replace the values host, port, username, and password according to your SMTP server.

```
Host: mail.yourmailserver.com
Port: 25
Username: rs@yourmailserver.com
Password: passwordsecret
SSL: false
TLS enable: false
TLS require: false
```

If you are using SSL or TLS please also specify these values. Next, configure the sender name, email address and forceSender options. If the forceSender option is set to true, the emails will be sent using the given (generic) sender details. If set to false, the specific user sending the email will determine the sender details.

```
Sender: rs@yourmailserver.com
Sender name: ReportServer
Force sender: false
Encryption policy: allow_mixed
```

The encryption policy option controls whether or not mails have to be encrypted or whether it is ok to send mails unencrypted if a user's public key is not specified. Choose between `strict` and `allow_mixed`. Note that if you choose `strict` then mails to users that do not have public key registered with ReportServer will not receive any messages.

Details on setting the default email datasink can be found in Section [4.1](#).

## Scheduler settings

ReportServer comes with a powerful scheduler. ReportServer's scheduler allows you to schedule the execution of reports. The executed report can then either be emailed, stored in a folder in a *TeamSpace*, or sent to a FTP server.

The schedule and report recipients are user provided on scheduling. You can configure the messages that ReportServer will send out on certain events. Each message can be customized to your specifications.

ReportServer will send out the following emails:

- email with attached completed report (mailaction) (deprecated, use fileactionEmailDatasink instead),
- email if a report has been placed into a TeamSpace (fileaction),
- email if a report has been sent to an email SMTP server (fileactionEmailDatasink),
- email if a report has been sent to a table datasink (fileactionTableDatasink),
- email if a report has been sent to a SFTP server (fileactionSftp),
- email if a report has been sent to a FTPS server (fileactionSftp),
- email if a report has been sent to a FTP server (fileactionFtp),
- email if a report has been sent to a Samba - SMB/CIFS server (fileactionSamba),
- email if a report has been sent to a SCP (SSH) server (fileactionScp),
- email if a report has been sent to the local filesystem (fileactionLocalFilesystem),
- email if a report has been sent to a Dropbox datasink (fileactionDropbox),
- email if a report has been sent to a Google Drive datasink (fileactionGoogleDrive),
- email if a report has been sent to an Amazon S3 datasink (fileactionAmazonS3),
- email if a report has been sent to a Box datasink (fileactionBox),
- email if a report has been sent to a Printer datasink (fileactionPrinter),
- email if a report has been sent to a Script datasink (fileactionScriptDatasink),
- email on schedule (notification - scheduled),
- email if a schedule job is revoked (notification - unscheduled),
- email if a scheduled job failed (notification - failed)

## 4. Configuration

---

The following configurations are done in the file `/filesserver/etc/scheduler/scheduler.cf`. To include information such as “the user who created the schedule entry”, “the report’s name” etc. in your message you can use a variety of expressions. Substitutions are defined in the ReportServer formula language. You will find further information about the ReportServer formula language in the *Administrator’s*, as well as in the *User Guide*.

### Available Substitutions

Expression	Description
<code>\${job.getName()}</code>	job’s name
<code>\${job.getDescription()}</code>	job’s description
<code>\${job.getId()}</code>	job’s ID
<code>\${report.getName()}</code>	report’s name
<code>\${report.getDescription()}</code>	report’s description
<code>\${report.report.getKey()}</code>	report’s key
<code>\${report.getId()}</code>	report’s ID
<code>\${user.getUsername()}</code>	username
<code>\${user.getFirstname()}</code>	first name of user
<code>\${user.getLastname()}</code>	last name of user
<code>\${user.getEmail()}</code>	user’s email address
<code>\${user.getTitle()}</code>	user’s title
<code>\${user.getId()}</code>	id of user
<code>\${executor}</code>	job’s executor. You can use the same methods above as with user
<code>\${scheduledBy}</code>	job’s scheduler. You can use the same methods above as with user
<code>\${teamSpace.getName()}</code>	name of TeamSpace (only available in fileaction)
<code>\${folder.getName()}</code>	name of folder in TeamSpace (only available in fileaction)
<code>\${folder}</code>	name of folder in FTP server (only available in fileactionFtp)
<code>\${message}</code>	the message that was specified by the user on scheduling
<code>\${subject}</code>	the subject that was specified by the user on scheduling
<code>\${recipients}</code>	A list of the job recipients. Please check below for the exact configuration (list of users)
<code>\${owners}</code>	A list of the job owners. Please check below for the exact configuration (list of users)
<code>\${filename}</code>	filename as specified by the user (report is scheduled in teamspace)
<code>\${nextDates}</code>	date of next execution
<code>\${RS_CURRENT_DATE}</code>	current date
<code>\${errMsg}</code>	error message on erroneous execution
<code>\${stacktrace}</code>	detailed stacktrace on failed execution



**List of users** For substitution of a list of users (currently supported: list of job recipients and list of job owners), you can use a fluent API that allows you to configure the output exactly as you need. Available methods for this are:

<code>#{withSeparator()}</code>	use a given separator between users. Default is a new line.
<code>#{addString(",")}</code>	add a String, e.g. a comma
<code>#{addBlankspace()}</code>	add a blank space
<code>#{addNewline()}</code>	add a new line
<code>#{addUsernames()}</code>	add usernames
<code>#{addFirstnames()}</code>	add first names
<code>#{addLastnames()}</code>	add last names
<code>#{addEmails()}</code>	add emails
<code>#{addTitles()}</code>	add titles
<code>#{addIds()}</code>	user ids
<code>#{print()}</code>	create the result string. This method has to be called in the last place.

As mentioned, you can use a fluent API for configuring the output. E.g.,

```
#{recipients
    .addFirstnames()
    .addBlankspace()
    .addLastnames()
    .addBlankspace()
    .addString("(")
    .addUsernames()
    .addString(")")
    .print()
}
```

will print the following:

Barry Jones (bjones)

Diane Murphy (dmurphy)

Gerard Hernandez (ghernande)

Larry Bott (lbott)

If you want to separate the users by a comma instead of a new line, you can enter use the `withSeparator()` method as follows:

```
#{recipients
    .withSeparator(", ")
}
```

## 4. Configuration

---

```
.addFirstnames()
.addBlankspace()
.addLastnames()
.addBlankspace()
.addString("(")
.addUsernames()
.addString(")")
.print()
}
```

which will print the following data:

Barry Jones (bjones), Diane Murphy (dmurphy), Gerard Hernandez (ghernande), Larry Bott (lbott)

Below you can find some example configurations:

Configuration of email message with attached report (successful execution)

```
<mailaction html="false">
<subject>${subject}</subject>
<text>Text of message: ${message}</text>
<attachment>
  <name>rep-${report.getName()}-${RS_CURRENT_DATE}</name>
</attachment>
</mailaction>
```

Configuration on successful execution of report and storage in TeamSpace

```
<fileaction disabled="false" html="false">
  <subject></subject>
  <text></text>
</xmlcode>
```

Configuration on successful execution of report sent to email SMTP server

```
<fileactionEmailDatasink disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionEmailDatasink>
```

Configuration on successful execution of report sent to table datasink

```
<fileactionTableDatasink disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionTableDatasink>
```

Configuration on successful execution of report and storage in SFTP server

```
<fileactionSftp disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionSftp>
```

Configuration on successful execution of report and storage in FTPS server

```
<fileactionFtps disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionFtps>
```

Configuration on successful execution of report and storage in FTP server

```
<fileactionFtp disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionFtp>
```

Configuration on successful execution of report and storage in Samba server

```
<fileactionSamba disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionSamba>
```

Configuration on successful execution of report and storage in SCP (SSH) server

```
<fileactionScp disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionScp>
```

Configuration on successful execution of report and storage in the local filesystem

```
<fileactionLocalFilesystem disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionLocalFilesystem>
```

Configuration on successful execution of report and storage in Dropbox

```
<fileactionDropbox disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionDropbox>
```

Configuration on successful execution of report and storage in OneDrive - SharePoint (O365)

```
<fileactionOneDrive disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionOneDrive>
```

Configuration on successful execution of report and storage in Google Drive

```
<fileactionGoogleDrive disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionGoogleDrive>
```

Configuration on successful execution of report and storage in Amazon S3 bucket

```
<fileactionAmazonS3 disabled="false" html="false">
  <subject></subject>
```

## 4. Configuration

---

```
<text></text>
</fileactionAmazonS3>
```

Configuration on successful execution of report and storage in Box

```
<fileactionBox disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionBox>
```

Configuration on successful execution of report and storage in Printer datasinks

```
<fileactionPrinter disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionPrinter>
```

Configuration on successful execution of report and storage in Script datasinks

```
<fileactionScriptDatasink disabled="false" html="false">
  <subject></subject>
  <text></text>
</fileactionScriptDatasink>
```

Configuration of notifications on scheduling, unscheduling and execution errors

```
<notification disabled="false" html="false">
  <scheduled>
    <subject></subject>
    <text></text>
  </scheduled>
  <unscheduled>
    <subject></subject>
    <text></text>
  </unscheduled>
  <failed>
    <subject></subject>
    <text></text>
  </failed>
</notification>
```

If you would like to send emails in the HTML format please set the corresponding html attribute to "true".

In case you do not want to have one or more notifications, you can disable the individual notifications using the disabled attribute:

```
<fileaction disabled="true" html="false">
```

If you do not want to use the scheduler you can disable it using

```
<properties>
  <disabled>true</disabled>
</properties>
```

You can also disable the scheduler by setting the following property in your `reportserver.properties` file:

```
rs.scheduler.disable = true
```

If the property is set both in `reportserver.properties` and in `/filesserver/etc/scheduler/scheduler.cf`, the property set in `reportserver.properties` is taken into account, while the one set in `/filesserver/etc/scheduler/scheduler.cf` is ignored.

Keep in mind that this changes will only take effect after reboot. To enable or disable the scheduler while ReportServer is running, use the terminal command `scheduler daemon start/stop`. This command only works if the scheduler is not disabled in the file `reportserver.properties`. If it is, you first have to delete this property in order to be able to enable/disable the scheduler while ReportServer is running. Refer to the *Administration Guide* for more information on this command.

Further, refer to Section [4.9 Scheduler Settings](#) for more scheduler settings.

## 4.4 Export settings

Regarding the export to PDF and Microsoft Excel, there are several options that you can set. In `/filesserver/etc/exportfilecmd/excelexport.cf` you can specify in which format Excel documents are to be exported. You can choose between the old XLS and the current XLSX format. If you have selected the XLSX format, ReportServer allows to stream the data to the client. This means, that the chunks of resulting Excel file are sent to the user while it is still being created. Streaming result files can significantly reduce processing time.

To specify the Excel format and whether or not to use streaming, adjust the following parameters:

```
<format>xlsx</format>
<stream>>true</stream>
```

Further, you can specify the title of the data and configuration sheets in the resulting Excel file by the following parameters:

```
<datasheet>Dynamic list</datasheet>
<configsheet>Configuration</configsheet>
```

Refer to the “output\_parameters”, “output\_filters”, and “output\_complete\_configuration” report parameters in the Admin Guide for more information on this.

You can specify document properties (title, creator and author) of PDF files in the configuration file `/filesserver/etc/exportfilecmd/metadata.cf`. The texts specified here will be included in newly generated PDF files.

Modify the following parameters:

```
<title>title</title>
<creator>ReportServer</creator>
<author>ReportServer</author>
```

As with email notifications you can use substitutions to dynamically populate the fields. The following substitutions are available:

## 4. Configuration

---

### Available Substitutions

Expression	Description
<code>\${user.getUsername()}</code>	username
<code>\${user.getFirstname()}</code>	user's first name
<code>\${user.getLastname()}</code>	user's last name
<code>\${user.getEmail()}</code>	user's email address
<code>\${user.getTitle()}</code>	user's title
<code>\${user.getId()}</code>	user's id

You can further specify the default character set used by ReportServer. In the configuration file `/fileservers/etc/main/main.cf` you will find the option `charset`. By default, the charset UTF-8 is used.

## 4.5 UI Customization

In this section we cover the possibilities of customizing the user interface. ReportServer provides the following customization options:

- Specifying the default language,
- Customizing error messages,
- Customize the theme,
- customize PDF preview,
- customize the report documentation,
- add tabs based on context

Further customization options are available with the use of ReportServer scripts. More information on ReportServer scripts can be found in the *Administration Guide*.

### Specifying the available languages

Any visible text in ReportServer can, in principle, be displayed in any language. The languages available on log-in can be defined in the configuration file `/fileservers/etc/main/localization.cf`.

```
<default>de</default>
```

The “default” property specifies which language to use as default language.

```
<locales>en , fr , de</locales>
```

The “locales” property specifies a comma-separated list of available languages. If the property is not specified, all supported languages are available for selection.

**Remark.** The user's selection is stored in a cookie. Thus, the change of the default locale will not override any locale settings done by a user previously.

**Remark.** A large part of the translations have been generated in a semi-automatic way and are thus far from perfect. If you are a native speaker in one of the languages and would like to contribute please contact us at [info@infofabrik.de](mailto:info@infofabrik.de).

## Customization of error messages

Errors can occur due to various reasons.

Typical errors are:

- an error occurs on the database during report execution, because:
  - a table does not exist,
  - a column does not exist,
  - there is a syntax error in the underlying SQL,
  - the JDBC driver was not installed
  - etc.
- the connection pool does not have any free connections

An exception is thrown whenever an error occurs in ReportServer. The exception is composed of: a title, error message, and the stack trace.

In `/fileserver/etc/main/templates.cf` you can customize the error message that is displayed on errors that occur during the export of reports.

When customizing the error message you should give clear instructions as to what the affected employee should do in this case. Usually you would specify the contact address of an administrator or help desk. When customizing, the following substitutions are available: `${headline}`, `${msg}` and `${stacktrace}`.

## Customization of theming

In ReportServer Enterprise Edition it is possible to customize the theme via the `/fileserver/ui/theme.cf` config file. Further information on this can be found in the administration guide.

## Preview for PDF reports

In the configuration file `/fileserver/etc/ui/previews.cf` you can specify how to render PDF previews. The options are `${native}` (to use the native browser capabilities), `${jsviewer}` (to use a javascript library) or `${image}` to not render a PDF at all, but to only render the first page as an image. Also note that users can overwrite the settings within their profiles.

### Adding contextual tabs

Using the configuration file `/fileservers/etc/ui/urlview.cf` you can define context aware tabs to be displayed in the TeamSpace or in the administration module (e.g., report management, user management, etc.). This allows you to, for example, display the documentation report directly whenever a user selects a report in the TeamSpace.

The configuration of extra tabs is split into two parts:

```
<?xml version="1.0" encoding="UTF-8"?>
<configuration>
  <adminviews>

  </adminviews>
  <objectinfo>

  </objectinfo>
</configuration>
```

Tabs to be displayed in the administration module go into the **adminviews** tags and tabs for the TeamSpace are put within the **objectinfo** tags, respectively. The default configuration does not add any additional tabs for the admin interface, but adds several tabs to the TeamSpace:

```
<?xml version="1.0" encoding="UTF-8"?>
<configuration>
  <adminviews>
  </adminviews>
  <objectinfo>
    <view>
      <types>net.datenwerke.rs.tsreportarea.client.tsreportarea.dto.</types>
      ↳ TsDiskReportReferenceDto</types>
      <name>${msgs['net.datenwerke.rs.core.service.urlview.locale.UrlViewMessages']['</name>
      ↳ info']}</name>
      <url>rs:reportdoc://${reportId}/${id}</url>
    </view>
    <view>
      <types>net.datenwerke.rs.tsreportarea.client.tsreportarea.dto.</types>
      ↳ TsDiskReportReferenceDto</types>
      <name>${msgs['net.datenwerke.rs.core.service.urlview.locale.UrlViewMessages']['</name>
      ↳ history']}</name>
      <url>rs:revisions://${reportId}</url>
    </view>
    <view>
      <types>net.datenwerke.rs.tsreportarea.client.tsreportarea.dto.</types>
      ↳ TsDiskReportReferenceDto</types>
      <name>${msgs['net.datenwerke.rs.core.service.urlview.locale.UrlViewMessages']['</name>
      ↳ preview']}</name>
      <url>rs:reportpreview://${reportId}</url>
    </view>
  </objectinfo>
</configuration>
```

Each `<view>` tag adds a new tab. The `<types>` tag allows to define for which types of objects the tab is displayed and `<name>` provides a name (in the above example, the name is localized, but you could also simply write `<name>SomeName</name>`). Finally, the `<url>` tag takes a URL that is to be displayed. In the above example we have three custom ReportServer URLs that access custom functionality, the first accesses a documentation report, the second a revisions report and the last



one a preview of the report. Via the replacement `${reportId}` the id of the object is added to the URL.

In the following we go through the process of adding new tabs step by step.

### Adding a new Tab

To add a new tab, you define a `<view>` tag. For adding a tab to the TeamSpace whenever a report is selected add the following `<view>` tag within the `<objectinfo>` section.

```
<view>
  <types>
    net.datenwerke.rs.tsreportarea.client.tsreportarea.dto.↵
      ↳ TsDiskReportReferenceDto
  </types>
  <name>Some Additional Information</name>
  <url>
    reportserver/reportexport?key=someKey&amp;format=html&amp;↵
      ↳ p_reportId=${reportId}
  </url>
</view>
```

The above will execute the report with key "*someKey*" and pass the given report id as parameter. The following types are available in TeamSpaces.

All Objects in a TeamSpace:

```
net.datenwerke.rs.tsreportarea.client.tsreportarea.dto.AbstractTsDiskNodeDto
```

All folders in a TeamSpace:

```
net.datenwerke.rs.tsreportarea.client.tsreportarea.dto.TsDiskFolderDto
```

All reports and variants in a TeamSpace:

```
net.datenwerke.rs.tsreportarea.client.tsreportarea.dto.TsDiskReportReferenceDto
```

All *exported reports* which were, for example, created by the scheduler:

```
net.datenwerke.rs.scheduleasfile.client.scheduleasfile.dto.ExecutedReportFileReferenceDto↵
↳
```

The name field defines the tab's name. The url is the address that is displayed. This also allows you to access external addresses, that are then displayed within the tab.

For the report documentation you need to use the special ReportServer URL:

```
rs:reportdoc://${reportId}/${id}
```

As you can see there are two placeholders in the above url: `${reportId}` and `id`. The following replacements are available

## 4. Configuration

---

id            the object's id  
type         the object's type  
username    the current user's username

Note that TeamSpaces do not only contain report references. Thus, the replacement `${id}` will contain the id of the reference rather than the id of the referenced report. For this, there is the special replacement called `${reportId}` which is only available for report references.

Similarly, to the report documentation in the TeamSpace you can display additional information on any selected object in the *administration module*. In the administration module you can add tabs to objects in the report management, user management, dadget management, datasource management and fileserver modules. These are configured within the `<adminviews>` tag.

The following tables describe which types can be used. Note that the type must be used together with the corresponding prefix.

### Objects in Report Management

Prefix `net.datenwerke.rs.core.client.reportmanager.dto.reports`.

Type	Description
AbstractReportManagerNodeDto	All objects in the report management tree
ReportDto	reports
ReportFolderDto	folders

### Objects in User Management

Prefix `net.datenwerke.security.client.usermanager.dto`.

Type	Description
AbstractUserManagerNodeDto	All objects in the user management tree
UserDto	users
GroupDto	groups
OrganisationalUnitDto	organisational units (folders)

### Objects in the file server

Prefix `net.datenwerke.rs.fileserver.client.fileserver.dto`.

Type	Description
AbstractFileServerNodeDto	All objects in the file server
FileServerFolderDto	folders
FileServerFileDto	files

### Objects in Datasource Management

Prefix `net.datenwerke.rs.core.client.datasourcemanager.dto`.

Type	Description
AbstractDatasourceManagerNodeDto	all objects in datasource management
DatasourceFolderDto	folders
DatasourceDefinitionDto	datasources

## Objects in Dadget Management

Prefix `net.datenwerke.rs.dashboard.client.dashboard.dto`.

Type	Description
AbstractDashboardManagerNodeDto	All objects in the dashboard tree
DashboardNodeDto	dashboards
DashboardFolderDto	folders

The following example would display a tab **User Information** which displays the website at Url <http://www.mycompany.com/employee>.

```
<adminviews>
  <view>
    <types>net.datenwerke.security.client.usermanager.dto.UserDto</types>
    ↪ types>
    <name>User Information</name>
    <url>http://www.mycompany.com/employee=${id}</url>
  </view>
</adminviews>
```

## 4.6 Extensions

ReportServer has a modular design which is exposed in ReportServer Enterprise Edition to allow for customization. The extension points are called *hooks*. Extensions are written in groovy (<https://groovy-lang.org/>) and can *hook into* various places in ReportServer. In order to use scripts, you must configure certain properties in the configuration file `/fileserver/etc/scripting/scripting.cf`.

This file controls whether scripts are enabled to begin with. Furthermore, you have to specify a path (in the internal filesystem) beneath which scripts can be placed (this helps to allow users to create/edit files in the file system without giving them the rights to write scripts). Finally, you can name a script which is executed on ReportServer startup and one which is executed whenever a user logs in.

```
<scripting>
  <enable>>true</enable>
  <restrict>
    <location>bin</location>
  </restrict>
  <startup>
    <login>fileserver/bin/onlogin.groovy</login>
    <rs>fileserver/bin/onstartup.groovy</rs>
  </startup>
</scripting>
```

## 4. Configuration

---

In the above example we allow scripts only in the bin folder (and subfolders). We defined the script `fileserver/bin/onlogin.groovy` as the script that is executed whenever a user logs in (note that the script is executed with the current user, that is, the user that logged in and thus the user must have the rights to execute this script). The second, on startup script is executed without any user.

The *onstartup* and *onlogin* scripts shipped with the ReportServer demo data allow you to easily execute your own scripts. The *onstartup* script executes all scripts in the folder `/fileserver/bin/onstartup.d`. Likewise, the *onlogin.groovy* script executes all scripts within `/fileserver/bin/onlogin.d`.

Further information on ReportServer scripts can be found in the *administration guide* and the specialized *scripting guide*.

### 4.7 Executing Reports using URLs

You can configure ReportServer to allow other applications to call reports or to include reports into external websites. For this ReportServer allows to call and configure reports directly using a specific URL. You can find more information about how reports can be accessed using a URL in the *administrators guide*.

The old `httpauthexec` functionality was replaced in ReportServer 3.0. See the Administration Guide for further information on how to make reports available via the URL without login.

### 4.8 Misc Settings

ReportServer needs a directory to store temporary files. You can define the directory to use in `/fileserver/etc/main/main.cf`. Furthermore, you can specify a maximum lifetime (in seconds) of temporary files in the directory.

```
<tempdir>tempdir</tempdir>
<tempfile>
  <lifetime>3600</lifetime>
</tempfile>
```

#### Maintenance Tasks

ReportServer performs certain maintenance tasks from time to time. You can define the interval (in ms) with which ReportServer will execute these.

```
<maintenance>
  <tasks>
    <interval>600000</interval>
  </tasks>
</maintenance>
```

ReportServer allows to define a timeout (in ms) for search queries:

```
<search>
  <timeout>5000</timeout>
```

```
</search>
```

## 4.9 Scheduler Settings

While scheduling new jobs, you can select the option “Compress report” if you want the report to be compressed in the email sent. Normally, this option is not selected by default. Now you can set this setting to be selected by default (in `/fileserver/etc/main/main.cf`):

```
<scheduler>
  <email>
    <defaultcompression>true</defaultcompression>
  </email>
</scheduler>
```

If you set this to `true`, “Report compression” will be automatically selected when scheduling new jobs. Defaults to `false`.

Refer to Section [4.3 Scheduler settings](#) for more scheduler settings.

## 4.10 Localization Settings

ReportServer contains localization settings in the `/fileserver/etc/main/localization.cf` file.

You can configure the languages available to your ReportServer users with the following

```
<locales>en,fr,de</locales>
```

In the example above, english, french and german languages are enabled. The default language can be configured with the following setting:

```
<default>fr</default>
```

In the example above, only french will be auto-selected in the ReportServer language list. Note that for users that previously used ReportServer, the language they used is saved in a cookie for next time, so the default language setting will not have any effect on these users. You have to delete your browser’s cookies for this.

Formats can be configured in the following:

```
<format>
  <!--
    <shortDatePattern></shortDatePattern>
    <longDatePattern></longDatePattern>
    <shortTimePattern></shortTimePattern>
    <longTimePattern></longTimePattern>
    <shortDateTimePattern></shortDateTimePattern>
    <longDateTimePattern></longDateTimePattern>
    <numberPattern></numberPattern>
    <currencyPattern></currencyPattern>
    <integerPattern></integerPattern>
    <percentPattern></percentPattern>
  -->
```

## 4. Configuration

---

```
</format>
```

For example, the `shortDatePattern` and `numberPattern` may be configured as follows:

```
<format>
  <shortDatePattern>y-MM-dd</shortDatePattern>
  <numberPattern># ##0,00</numberPattern>
</format>
```

Details on the formats available may be found here:

**Number Formats** <http://www.gwtproject.org/javadoc/latest/com/google/gwt/i18n/client/NumberFormat.html>

**Date Formats** <http://www.gwtproject.org/javadoc/latest/com/google/gwt/i18n/client/DateTimeFormat.html>

The currency locales may be configured in the following section:

```
<currencyes>
  <currency language="de" region="DE">currencyEuro</currency>
  <currency language="en" region="US">currencyDollar</currency>
  <currency language="en" region="GB">currencyPound</currency>
  <currency language="ar" region="AE">AED</currency>
  <currency language="ps" region="AF">AFN</currency>
  ...
</currencyes>
```

In the example above, the Euro currency is localized to the `de_DE` locale. If you need to change this, e.g. to `fr_FR`, you may change this to:

```
<currencyes>
  <currency language="fr" region="FR">currencyEuro</currency>
  <currency language="en" region="US">currencyDollar</currency>
  <currency language="en" region="GB">currencyPound</currency>
  <currency language="ar" region="AE">AED</currency>
  <currency language="ps" region="AF">AFN</currency>
  ...
</currencyes>
```

As currency is locale-specific, the format may change depending on the locale configured here.

For example, 123456.79 dollars will be printed as follows in the default locale:

US\$123,456.79

In `en_US` locale, the same will be printed as:

\$123,456.79

Note that you have to restart ReportServer if you change your currency locale configuration.

More details on currency locales may be found here: <http://www.gwtproject.org/javadoc/latest/com/google/gwt/i18n/client/NumberFormat.html>.

## 4.11 Security related properties

In the following section we describe *certain security related* configuration options.

In `/fileserver/etc/security/misc.cf` you can define a blacklist for ReportServer expressions. If not running ReportServer with a SecurityManager, you should ensure that such expressions cannot use java reflection. At a minimum level you should deny the phrase `getClass`. Further information can be found in the *administration* and *user guides*.

```
<juel>
  <expression>
    <blacklist>getClass</blacklist>
  </expression>
</juel>
```

In the example the expression `getClass` is prohibited. Multiple expressions are comma separated.

### URL Whitelist

Certain operations, e.g. redirect, are not allowed for external URLs. If you need to allow a URL you can add it to the whitelist in the `/fileserver/etc/security/whitelist.cf` configuration file.

```
<urls>
  <url>http://www.host.com</url>
</urls>
```

### Configuring error message level of detail

Further, in this configuration file, you can select the level of detail of error messages shown to the user. Currently, the following is supported:

**hideViolatedSecurityExceptionDetails** When a security rule is violated, e.g. when a user tries to execute a report the user is not allowed to, specific details of the security violation are being printed to the user by default. This includes the specific security target, the rights/permissions being violated, the objects and the method where this happens, if available. This helps administrators to exactly understand which rights/permissions are needed for a specific object to be accessed by a user. If not desired, you can set this to false in order to hide these specific details from the user, which may be preferable in some cases. Defaults to false.

Below you can see an example configuration.

```
<errorMessages>
```

## 4. Configuration

---

```
<hideViolatedSecurityExceptionDetails>>false</hideViolatedSecurityExceptionDetails>
  ↳ hideViolatedSecurityExceptionDetails>
</errorMessages>
```

### Disabling forgot password

If you wish to disable the “forgot password” option in the login window, you can set the ‘disableLostPassword’ option to true.

Below you can see an example configuration for this.

```
<disableLostPassword>>true</disableLostPassword>
```

### Configuring cryptography

The file `/fileserver/etc/security/crypto.cf` defines various cryptography related options. The `<cryptocredentials>` section defines how cryptographic credentials, such as private keys and certificates are retrieved for various ReportServer modules.

To do so, a provider is specified for each module.

A provider is defined by specifying the name of the handler-class and some additional attributes.

```
<provider type="signature">
  <class>
    net.datenwerke.rs.incubator.service.crypto.
      ↳ FileServerKeyStoreKryptoCredentialProvider
  </class>
  <alias>rs</alias>
  <secret>secret</secret>
  <type>jks</type>
  <location>/fileserver/keystore.jks</location>
</provider>
```

This configures the default handler, which tries to load key-material from a file within the fileserver. Providers can be specified for these types:

**signature:** a keystore that holds the private key, ReportServer uses when sending signed emails

**user:** a keystore that holds public keys and certificates of ReportServer users. This is used, when sending encrypted emails. An alternate method to provide key material is by using a custom script, that retrieves the keys e.g. from a corporate directory.

### Specifying a Password Policy

ReportServer allows to configure the use of password policies to ensure that users choose secure passwords. The corresponding configuration goes into the configuration file `/fileserver/etc/security/passwordpolicy.cf`.

For example, you can define how long passwords should be and define character classes from which the password must be built. Furthermore, you can define how often passwords need to be changed and when a previously chosen password may be chosen again.



```

<pswd>
  <maxage>32</maxage>
  <minage>1</minage>
  <minlength>8</minlength>
</pswd>

```

The parameter `maxage` defines the number of days a password remains valid. The parameter `minage` denotes that a password may be changed at most every day. `minlength` defines the minimal length of passwords.

The property `<historysize>6</historysize>` denotes that the last 6 passwords may not be used when changing the password.

You can define a threshold on the number of failed login attempts after which a user account is blocked. This is done using `<lockoutthreshold>3</lockoutthreshold>`. `<lockoutresettimeout>60</lockoutresettimeout>` specifies the time after which automatically locked accounts can be used again.

The `<characterset>` definitions specify which characters for a password are approved and how many characters from a particular group must be used.

```

<characterset>0123456789</characterset>
<choosemin>2</choosemin>
<characterset>abcdefghijklmnopqrstuvwxyz</characterset>
<choosemin>1</choosemin>
<characterset>ABCDEFGHIJKLMNOPQRSTUVWXYZ</characterset>
<choosemin>1</choosemin>
<characterset>!$%+~#@</characterset>
<choosemin>2</choosemin>

```

In the above example, it is specified that from the first and last group (the digits and special characters) at least 2 characters must be used. From the two remaining groups at least a single character must be used.

Note that the specified number denotes a lower bound on the characters chosen from this group.

A complete configuration of the password policy might thus look as follows:

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration>
  <rs>
    <security>
      <passwordpolicy>
        <bsipasswordpolicy>
          <pswd>
            <maxage>32000</maxage>
            <minage>1</minage>
            <minlength>8</minlength>
          </pswd>
          <historysize>6</historysize>
          <lockoutthreshold>3</lockoutthreshold>
          <lockoutresettimeout>60</lockoutresettimeout>
          <characterset>0123456789</characterset>
          <choosemin>1</choosemin>
          <characterset>abcdefghijklmnopqrstuvwxyz</characterset>

```

## 4. Configuration

---

```
<choosemin>1</choosemin>
<characterset>ABCDEFGHIJKLMNOPQRSTUVWXYZ</characterset>
<choosemin>1</choosemin>
<characterset>!$%&amp;#;/=?*:.:;,-_+~\#@</characterset>
<choosemin>1</choosemin>
</bsipasswordpolicy>
</passwordpolicy>
</security>
</rs>
</configuration>
```

### Notifications

Users can be notified when their password has been created the first time or when their password was changed (by an administrator). The notification is done via email (note that for this the mail server must be correctly configured). For this purpose, the following configuration file is available: `security/notifications.cf`.

This configuration file allows to configure the texts sent by email and further allows to disable this functionality, if desired.

```
<createdpassword disabled="false">
  <email>
    <subject>Email Subject</subject>
    <text>Email Text
      Username: ${user.getUsername()}
    </text>
  </email>
</createdpassword>
<changedpassword disabled="false">
  <email>
    <subject>Email Subject</subject>
    <text>Email Text
      Username: ${user.getUsername()}
    </text>
  </email>
</changedpassword>
```

The following substitutions are available.

Expression	Description
<code>\${user.getUsername()}</code>	username
<code>\${user.getFirstname()}</code>	user's first name
<code>\${user.getLastname()}</code>	Last name of user
<code>\${user.getEmail()}</code>	user's email address
<code>\${user.getTitle()}</code>	user's title
<code>\${user.getId()}</code>	user's id

Further, this file allows to configure the texts of the email sent by the `listlogfiles` terminal command using the `-e` option.

```
<logfiles>
  <email>
```

```

    <subject>Email Subject</subject>
    <text>Email Text
      Filter: ${filter}
    </text>
  </email>
</logfiles>

```

In this section, the following substitutions are available. For more information, check the [listlogfiles](#) documentation.

Expression	Description
<code>\${filter}</code>	filter passed with -f parameter
<code>\${user.getUsername()}</code>	username
<code>\${user.getFirstname()}</code>	user's first name
<code>\${user.getLastname()}</code>	Last name of user
<code>\${user.getEmail()}</code>	user's email address
<code>\${user.getTitle()}</code>	user's title
<code>\${user.getId()}</code>	user's id

**Tip.** Note that from RS 3.3.0 the old `lostpassword.cf` configuration file is no longer available. This configuration is now done in the new `notifications.cf` file.

## User activation

Users can be activated by administrators using the user manager. On activation, the user will receive an email with an automatically generated (single use) password (note that for this the mail server must be correctly configured). After the first login, the user must change the password according to the password policy.

You can customize the email sent to the user in the configuration file `/fileserver/etc/security/activateuser.cf`.

```

<security>
  <activateaccount>
    <email>
      <subject>Your ReportServer account details</subject>
      <text>
        Username: ${user.getUsername()}
        Password: ${password}
      </text>
    </email>
  </activateaccount>
</security>

```

The following substitutions are available.

## 4. Configuration

---

Expression	Description
<code>\${user.getUsername()}</code>	username
<code>\${user.getFirstname()}</code>	user's first name
<code>\${user.getLastname()}</code>	Last name of user
<code>\${user.getEmail()}</code>	user's email address
<code>\${user.getTitle()}</code>	user's title
<code>\${user.getId()}</code>	user's id
<code>\${password}</code>	the generated password
<code>\${url}</code>	the URL under which ReportServer can be accessed

### Configuring the SFTP Server

ReportServer Enterprise Edition can be configured to expose its internal filesystem (and other management areas) using an SFTP server. The corresponding configuration goes into `/filesserver/etc/misc/misc.c`

```
<remoteaccess>
  <sftp disabled="false">
    <!-- Use $generated in order to generate a key on first start. -->
    <keylocation>/path/to/hostkey.pem</keylocation>
    <port>8022</port>
  </sftp>
</remoteaccess>
```

The SFTP server can be disabled if you don't need it via the `disabled` property. After a ReportServer restart, it will not be started if disabled previously.

The file `hostkey.pem` should contain the server's certificate. You can also use `$generated` in order to generate a key on first start. The path should be an absolute path (e.g., `file:///C:/path/to/hostkey.pem` in Windows or `/path/to/hostkey.pem` in Unix.) Note that the `file://` protocol is necessary in Windows in order to recognize `C` as the beginning of an absolute path.

Note that changes will only take effect after restarting ReportServer. If you do not want to start the SFTP server simply supply an invalid path or `$generated` and disable it with `disabled`.

## 4.12 SSO related properties

In the following section we describe *SSO* configuration options.

## 4.13 LDAP

*LDAP*-related properties, described below, are defined in the `/filesserver/etc/sso/ldap.cf` configuration file. These are relevant for the "ldapimport" terminal command and the `ldapimport.groovy` script available here: <https://github.com/infabrik/reportserver-samples/blob/main/src/net/datenwerke/rs/samples/admin/ldap/ldapimport.groovy>.

Note that you can (and should) test your LDAP configuration with the "ldaptest" commands described in the Administration Guide.

```
<provider>
  <host>directory.example.com</host>
  <port>389</port>
</provider>
```

Configures the host (or IP) and port where your LDAP server is installed. Note that if you use SSL (LDAPS) this port is different than the LDAP port. StartTLS uses the same LDAP port.

```
<security>
  <encryption>none</encryption>
  <principal>CN=ldaptest,CN=Users,DC=directory,DC=example,DC=com</principal>
  <credentials>password</credentials>
</security>
```

The “encryption” property defines the encryption protocol to use. Valid values are “none” (for no encryption), “starttls” (for StartTLS encryption (*recommended*)) and “ssl” (for SSL (LDAPS) encryption).

In order for encryption to work, you have to install the certificates needed for these to be trusted by ReportServer.

This means that you must add the LDAP server’s certificate (or a certificate higher up the trust chain) to a truststore that is known to ReportServer during startup.

This can be achieved in two different ways:

- Passing the truststore where the certificate is installed. If you use JKS keystores you can pass the keystore analogous to:

```
-Djavax.net.ssl.trustStore=/path/to/security/truststore.jks
-Djavax.net.ssl.trustStorePassword=myTrustStorePassword
-Djavax.net.ssl.trustStoreType=JKS
```

If you use PKCS12 you can pass the keystore analogous to:

```
-Djavax.net.ssl.trustStore=/path/to/security/truststore.p12
-Djavax.net.ssl.trustStorePassword=myTrustStorePassword
-Djavax.net.ssl.trustStoreType=PKCS12
```

Refer to the Java Documentation for details:

<https://docs.oracle.com/javase/8/docs/technotes/guides/security/jsse/JSSERefGuide.html>

Be aware that if you use this method, you may need to add other certificates as well in order for your Email, SFTP, OneDrive, etc to continue working, as these certificates are contained in the cacerts truststore, see below. You may of course create a copy of cacerts and add your certificates to this copy instead of using the java cacerts truststore directly.

- Or installing the certificate into your JVM trust store (usually located here `java-home/lib/security/cacerts`) Refer to the Java Documentation for details:

## 4. Configuration

---

<https://docs.oracle.com/javase/8/docs/technotes/guides/security/jsse/JSSERefGuide.html>.

You can test your SSL configuration, i.e. if your certificate was installed correctly, with the “ssltest” terminal command. Check the Administration Guide for details.

The “principal” and “credentials” properties allow you to authenticate to your LDAP server.

```
<base>OU=EXAMPLE,DC=directory,DC=example,DC=com</base>
<filter>(|(objectClass=organizationalUnit)(objectClass=user)(
  ↵ objectClass=group))</filter>
```

The “base” property defines the address of the root object in the LDAP directory. All objects are stored below the base.

The “filter” allows you to retrieve a subset of all the nodes found below the base DN.

```
<externalDir>/usermanager/external</externalDir>
<writeProtection>>true</writeProtection>
<includeNamespace>>false</includeNamespace>
<logResultingTree>>false</logResultingTree>
<flattenTree>>false</flattenTree>
```

The “externalDir” property defines the directory in ReportServer where your users/groups and OUs will be imported into. These objects will be write-protected if the “writeProtection” is set to “true”.

If “includeNamespace” is set to true, the full name of the bindings are used. Else, the relative names are used.

When the “logResultingTree” property is set to “true”, a summary and some statistics of the changes done in your ReportServer are logged into your logs.

If you need to import all nodes into the root directory (i.e. into the “externalDir” directory described above) instead of using the original LDAP tree, you can set “flattenTree” to “true”. Note that all OUs will be empty in this case. If you don’t want to include the empty OUs, you have to remove them via the filter attribute.

```
<attributes>
  <objectClass>objectClass</objectClass>
  <guid>entryUUID</guid>
  <organizationalUnit>
    <objectClass>organizationalUnit</objectClass>
    <name>name</name>
  </organizationalUnit>
  <group>
    <objectClass>group</objectClass>
    <name>name</name>
    <member>member</member>
  </group>
  <user>
    <objectClass>inetOrgPerson</objectClass>
    <firstname>givenName</firstname>
```

```

    <lastname>sn</lastname>
    <username>sAMAccountName</username>
    <mail>mail</mail>
  </user>
</attributes>

```

The properties above define the attributes used in your AD nodes.

General object class attributes are defined by the “attributes - objectClass” attribute, while object GUIDs are defined by the “guid” attribute. Note that GUIDs must be unique.

The “organizationalUnit - objectClass” defines a OU with name specified by “organizationalUnit - name”. The same applies to the “group” attributes.

The “user” attributes specify a given user. The node is determined as a user by the “user - objectClass” attribute, while the “firstname”, “lastname”, “username” and “mail” attributes allow Report-Server to fetch these attributes from a user node.

```

<attributes>
  <additional>
    <attribute>department</attribute>
    <attribute>office</attribute>
  </additional>
</attributes>

```

If you need additional attributes, i.e. attributes not included in the standard attribute list, you can fetch them from your LDAP by defining them in the “additional” list as shown above. The example would fetch the “department” and “office” attributes, which can be then used in a “LdapNodePost-ProcessHook” hooker as shown in this example: <https://github.com/infofabrik/reportserver-samples/blob/main/src/net/datenwerke/rs/samples/admin/ldap/ldapUserVariableProcessorHooker.groovy>. The example uses the “department” LDAP attribute in order to set the appropriate value into a given user-variable “myUserVar”.

```

<authentication>
  <allowLocalUsers>true</allowLocalUsers>
</authentication>

```

The “allowLocalUsers” setting allows you to control whether local, non-LDAP users are being allowed to authenticate or not alongside with the LDAP users. If this is set to “false”, only LDAP users are allowed to authenticate.





---

## External Configdir

ReportServer provides an alternative mechanism for providing configuration called the *configdir* mechanism. This allows to keep system settings separate from application files. You can use the config dir to

- store hibernate connection properties
- override reportserver.properties values
- move the config files from the internal fileserver to you local filesystem
- import contents into the internal fileserver
- hold additional jars (for example, additional JDBC drivers)
- override logging-rs.properties

To make ReportServer use the configdir you have to set the rs.configdir system property, for example by specifying the

```
-Drs.configdir=/var/lib/rsconfig
```

command line switch.

### hibernate connection properties

To use the configdir to specify hibernate connection properties, place a file with the name persistence.properties in the config dir. The file has the standard java properties file format. The properties defined here overwrite the properties configured in the persistence.xml file in the application directory.

For example you could create a persistence.properties file with these contents

```
hibernate.connection.url=jdbc:mysql://localhost:3306/reportserver
hibernate.connection.username=root
hibernate.connection.password=root
```

to provide the base connection parameters for ReportServer to use.

### **reportserver.properties values**

You can override the values defined in the reportserver.properties file in the application directory by creating a second reportserver.properties file in the configdir. Settings from this file will override settings made in the default reportserver.properties file.

### **additional jars**

The lib directory can hold additional jars (for example, additional JDBC drivers). This allows you, in particular, to maintain a set of libraries that will not be overwritten during your next reportserver upgrade.

### **logging-rs.properties values**

You can override the values defined in the logging-rs.properties file in the application directory by creating a second logging-rs.properties file in the configdir. Settings from this file will override settings made in the default logging-rs.properties file.

### **xml configfiles**

You can use the configdir to replace the internal files server storage for ReportServer xml configuration files. To use this feature create a config subdirectory in the configdir and place the config files there using the same directory layout as in the files server/etc directory. For example to store terminal aliases outside the internal files server create a file {rs.configdir}/config/terminal/alias.cf. You can use the baseconfig zip file in the pkg subdirectory of your ReportServer download to quickly create the correct directory structure. If a configfile is present in the internal files server, the same file on the local filesystem will be ignored, ReportServer will not try to merge the two files. However you can have some config files in the files server and others in the configdir.

### **files server import**

If you create a fsimport subdirectory in the configdir folder ReportServer will copy its contents to its internal files server on startup. This will update/override existing files, however missing files will not be removed.

### **Creating the configdir directory**

In the Linux <https://reportserver.net/en/tutorials/installation-best-practice/> and Windows <https://reportserver.net/en/tutorials/installation-windows/> Best-Practice Guides you can find examples of how to create the configdir and what files and directories to include in it.





## Config File Reference

In our github rs-samples repository you can find samples for each configuration file: <https://github.com/infofabrik/reportserver-samples/tree/main/config>