

ReportServer

Script Guide 3.0.6



ReportServer

Script Guide 3.0.6

InfoFabrik GmbH, 2019

<http://www.infofabrik.de/>
<http://www.reportserver.net/>



Copyright 2007 - 2019 InfoFabrik GmbH. All rights reserved.

This document is protected by copyright. It may not be distributed or reproduced in whole or in part for any purpose without written permission of InfoFabrik GmbH. The information included in this publication can be changed at any time without prior notice.

All rights reserved.

Contents

Contents	i
I Script Guide	3
1 Introduction	5
2 Getting Started	9
2.1 Terminology and Extension Points	10
3 Basics	13
3.1 Executing Scripts	13
3.2 Executing Scripts via URL	14
3.3 The GLOBALS Object	14
3.4 Working with Entities	17
3.5 Interpreting Script Error Messages	19
3.6 Reading and Writing to Files	22
3.7 Nesting Scripts: Calling Scripts from Scripts	23
4 Monitoring, Multithreading, Scheduling and other Advanced Techniques	27
4.1 Execution of Scripts	27
4.2 Storing Values Between Scripts	28
4.3 Multithreading in Scripts	30
4.4 Scheduling Scripts	32
5 Script Reporting	35
5.1 Basic Script Reports	36
5.2 Groovy's Markup Builder	38
5.3 Generating PDF and Word output	39
5.4 Running Script Reports from the Terminal	39
5.5 Testing via Browsers	41
5.6 Working with Parameters and Arguments	41
5.7 Working with Datasources	42

5.8	Interactive Reports	42
6	Script Datasources	47
7	Tapping into ReportServer	51
7.1	ReportServer Hooks Basics	51
7.2	Registering Hooks on Start-up and on Login	53
7.3	Which Hooks can I use?	54
8	Extending the Client	57
8.1	UrlView - Incorporating Websites and More	57
8.2	CommandResult - A Script's Result	60
8.3	ClientExtensionService	62
II	Examples	69
9	Adding Additional Data Sources	71
10	Integrating ReportServer with an Active Directory using LDAP	77
10.1	Synchronizing Users	77
10.2	Authenticating Users	78
10.3	Possible Improvements	80
11	Additional Report Executors	83
11.1	Background	83
11.2	Adding the Output Generator to the Client	88
12	Send To	91
A	AddFirebirdSupport.groovy	99
B	hookldappam.groovy	103
C	ldapimport.groovy	107

Part I

Script Guide

Introduction

The term Business Intelligence represents the capacity of a corporation to look at all business data as a whole in order to distinguish information which plays a key role in the strategic planning process and in decision making of the corporation. To achieve this all available data require consolidated preparation, for instance, in a Data Warehouse.

ReportServer serves as an interface to access these data, and the user can easily and efficiently make use of them. ReportServer offers tools to support you in your daily work establishing ready-to-print reports, or performing ad-hoc analyses.

Target Audience

In this manual we discuss ReportServer from the point of administrators that wish to extend ReportServers using scripts. This guide will also help report designers that use ReportServer script reports to create interactive reports or reports based on metadata kept by ReportServer.

Separate manuals and instructions illustrate the various aspects of ReportServer.

ReportServer Configuration Guide: Describes the installation of ReportServer as well as the basic configuration options.

ReportServer User Guide: The user guide describes ReportServer from the point of view of the ultimate user. It includes an in-depth coverage of dynamic lists (ReportServer's adhoc reporting solution), execution of reports, scheduling of reports, and much more.

ReportServer Administrator Guide: The administrator guide describes ReportServer from the point of view of administrators that are tasked with maintaining the daily operation of the reporting platform including the development of reports, managing users and permissions, monitoring the system state, and much more.

ReportServer Scripting Guide: The ReportServer scripting guide covers the scripting capabilities of ReportServer which can be used for building complex reports as well as for extending the functionality of ReportServer or performing critical maintenance tasks. It extends the introduction to these topics given in the administrator guide.

Content

This guide is based upon the ReportServer administrator's manual. We furthermore require basic programming experience in the Groovy programming language. An introduction to groovy can be found at <http://groovy.codehaus.org/>

This manual comprises the following chapters:

Part 1

Getting Started In this chapter we describe how to setup a work space to comfortably test and develop ReportServer scripts. Here we also cover the basic terminology.

Basic Script Services Introduces the GLOBALS object which provides access to services and entities for scripts.

Advanced Techniques Covers monitoring, multithreading, scheduling and other advanced techniques

Script Reporting This chapter covers the script reporting engine and script data sources.

Tapping into ReportServer Explains the ReportServer HookHandler concept that allows to extend and customize various aspects of ReportServer.

Extending the Client In this chapter we will look into various possibilities to extend the client side of ReportServer.

Part 2 - Examples

Adding additional Database Support In this chapter we explain how support for additional relational databases can be added to ReportServer.

Authentication against an Active Directory In this chapter we look into the authentication mechanisms of ReportServer and discuss how to authenticate against an Active Directory (LDAP)

Additional Report Exporters This chapter covers the basics of adding custom export formats to the various reporting engines available in ReportServer.

Please contact us in case you have questions or suggestions. We are looking forward to your requests. You can reach us via email (info@infofabrik.de) or our online forum which you can find at <https://forum.reportserver.net/>.

Getting Started

ReportServer scripts can be developed directly from within ReportServer using the Terminal and the commands `createTextFile` and `editTextFile`. In order to take full advantage of the services offered by ReportServer to script designers it is, however, necessary to get a basic understanding of the ReportServer source code. For this we provide a javadoc documentation of the sources together with the complete source code of ReportServer Community Edition on sourceforge.

To run and develop scripts in ReportServer, login to your ReportServer and open up the terminal (**CTRL+ALT+T**). All scripts must be stored in the fileserver somewhere beneath the `bin` directory. Thus, to give us a temporary working directory we go to the `bin` directory by typing `cd ↵`
↳ fileserver/bin create a new directory called `tmp` by typing `mkdir tmp` and go to our newly created directory (`cd tmp`). Next, we create our very first script by executing

```
createTextFile helloworld.groovy
```

A text editor opens in which we copy our first script:

```
return "Hello World"
```

which simply returns the string "Hello World" upon execution. Now, execute the script via

```
exec helloworld.groovy
```

You should see the following output:

```
reportserver$ exec helloworld.groovy
Hello World
reportserver$
```

That is, when executing a script on the terminal, then the final return statement is printed on the console. If you want to print something during the execution of the script (note that all print statements are buffered until the script is successfully executed) you can use the `tout` object (for terminal output).

```
tout.println('Hello World')
tout.println('Hello World2')
```

To edit the file in ReportServer directly call

```
editTextFile helloworld.groovy
```

2.1 Terminology and Extension Points

ReportServer scripts can be used for a variety of tasks. You can use them to create data sources or interactive reports, they can be used as administration tools and scheduled to perform maintenance tasks. They can, however, also be used to extend ReportServer both on the client side and on the server side. In this guide we will mainly focus on the last part of ReportServer scripts. This, however, directly also provides a large insight into other applications of scripts.

In order to write scripts that extend ReportServer we need to explain a bit about how GWT works and we need to learn about several important concepts within ReportServer. ReportServer is based on the GWT framework (you can find tons of information on GWT at <http://www.gwtproject.org/>). GWT is a web application framework that allows you to write the entire application including the client part in Java. Before deployment the client side is then translated to JavaScript such that it can be run natively in any modern web browser. This concept has several advantages: for example, you have most of the advantages of Java such as its sophisticated debugging tools or strong types available also for the client side. The main advantage, arguably, is that GWT is able to produce highly optimized JavaScript code which greatly benefits the user experience.

Script developers should keep in mind that the source code contains both server and client side code. Although code can be shared between the server and the client this is usually not the case. As scripts are written in Groovy and interpreted and executed on the server this means that scripts can only use server side code. If you look through the projects you will find that the package structure is the following:

```
net.datenwerke.(rs).(name).
```

where **rs** denotes a ReportServer project and name the main package of that project. Projects that are not ReportServer specific such as for example the DwHookHandler will not have the "rs" prefix. After the name part you will usually find the following packages:

client	Contains client side code.
server	Contains servlets.
service	Contains server side code

Hooks and Services

Now that we have seen the basic source structure there are two important concepts for script designers. One is the concept of Services. Most of the functionality offered by ReportServer, such as, executing reports, managing users, scheduling and many more are exposed by Service interfaces. An example is the ReportExecutorService which exposes the functionality to execute reports. When writing scripts you will usually use services to access ReportServer functionality. Services are by convention adhering to the naming scheme: nameService. If you search for `net.datenwerke.*.service.*Service` in the sources (or javadoc) of ReportServer you will find a large number of available server side services. We have also included a special services documentation file which lists all available services together with a short description and links to the Javadoc documentation of the service.

The second important concept is that of Hooks. Hooks are extension points in ReportServer which allow you to enhance functionality or be informed on certain events (such as report x is about to be executed). As with Services Hooks are used both on the server and client side and for script writers only the server side Hooks can be used. Hooks can be recognized by interfaces or abstract classes that implement the Hook interface

The hook interface is located in `net.datenwerke.hookhandler.shared.hookhandler.interfaces`

An example of a Hook is the `ReportExecutionNotificationHook` which is notified throughout the various stages of report execution. To use a Hook the corresponding interface must be implemented and the implementing Hook must be registered with the `HookHandlerService`. Classes that instantiate a Hook are usually suffixed by `Hooker` (i.e., the one doing the hooking).

Entities and DTOs

Entities are objects which are persisted in the database. Most objects, such as users, reports or TeamSpaces, that you will handle as a script designer are entities. You can recognize classes that represent entities by the `@Entity` annotation. When handling entities it is important to keep in mind that changes need to be persisted. To load and store entities the JPA `EntityManager` is used.

Entities can also be transported to the client. However, as they are inherently server based an entity is first transformed into a so called data transfer object (DTO) which is the representation on the client side. The conversion between entities and DTOs is handled by the `DtoService`.

Basics

In the previous chapter we saw that ReportServer functionality is exposed by services. In this chapter we discuss the basics of scripting within ReportServer. This includes passing parameters to scripts, accessing various services, interpreting error messages, working with entities, reading and writing text files and more.

3.1 Executing Scripts

As we have seen, scripts in ReportServer are executed via the Terminal using the `exec` command. The `exec` command takes as command a script and passes on any further arguments to the script. You can access command line arguments in your script via the variable `args`. Suppose we adapt our hello world script as follows:

```
package myscripts
```

```
tout.println('Hello ' + args )
```

If we now execute the script as

```
exec helloworld.groovy John
```

You will get the output

```
Hello [John]
```

The square brackets around the name, indicate that the `args` variable is in fact an array, or rather a groovy collection. If we again change our script to

```
package myscripts
```

```
tout.println('Hello ' + args.reverse() )
```

and call it with

```
exec helloworld.groovy John Doe
```

the output will be

```
Hello [Doe, John]
```

Return Values

Scripts have return values. The return value will be output in the terminal. You can either explicitly return from a script via the usual "return x" instruction or else the last line of your script will be interpreted as return value. Thus, we could change our above script to

```
package myscripts  
  
'Hello ' + args.reverse()
```

to get the same effect: an output in the terminal.

3.2 Executing Scripts via URL

Besides executing scripts from the terminal, you can execute scripts by calling a specific URL. To execute a script with ID 15 you need to call

```
http://SERVER:PORT/reportserverbasedir/reportserver/scriptAccess?id=15
```

The following parameters are available

id	The script's id.
path	Alternatively to specifying an id you can specify the path of a script.
args	The arguments to be passed to the script.
exception	In case of an exception the server will not respond with an error message. In order to make the server respond with the actual exception set this parameter to true.
commit	Whether or not the script should be executed in commit mode.

If executing a script via URL you have access to the predefined variable `HttpRequest` as well as `HttpResponse` which provide access to the HTTP request and response object.

3.3 The GLOBALS Object

Every ReportServer script is initialized with a scope that contains an object called GLOBALS. This object exposes ReportServer functionality to your script. This allows you to access ReportServer services but it also provides certain functionality to scripts such as easily accessing files in the fileserver. The most common case is access of ReportServer services and to access entities.

Tip: The GLOBALS object is of type `net.datenwerke.rs.scripting.service.scripting.scriptservices.GlobalsWrapper`. The javadoc documentation provides an overview the methods provided by GLOBALS.

Services can be retrieved via the method `getRsService()`. `getRsService` takes a class object as input and returns the corresponding service object. It is also possible to get access to a Provider object for a service. Providers can be regarded as containers which do not immediately access the service but which allow access to that particular service. This can for example be helpful when

writing complex scripts and you want to give access to services to functions or classes. Providers can be accessed via the `getRsServiceProvider` method which also takes a class object as input.

In the following we create a simple script that allows to search your ReportServer installation for users. For this we will use the `SearchService` located in package `net.datenwerke.rs.search.service.search`. The service exposes the search functionality provided by ReportServer.

Tip: In order to use auto completion and automatic import statements when editing scripts in Eclipse you must add all projects to the list of required projects. For this open the groovy project's properties (right-click on the project then choose properties) and Java Build Path. Choose the Projects tab and select all other projects.

Tip: Eclipse's auto-completion works better if you program Groovy using explicit types. That is, instead of writing

```
def var = 'string'

use

String var = 'string'
```

Create a new script in Eclipse called `searchuser.groovy`. We will require the `SearchService` from the GLOBALS object. We will then use the `locate` method to retrieve a list of results. As input we will simply pass on the argument array (converted to a string).

```
package myscripts

import net.datenwerke.rs.search.service.search.SearchService;
import net.datenwerke.security.service.usermanager.entities.User;

SearchService searchSvc = GLOBALS.getRsService(SearchService.class)
searchSvc.locate(User.class, args.join(" "))
```

If we add this script to our tmp folder in ReportServer and execute it via

```
exec searchuser.groovy root
```

you will get the output

```
[root root]
```

Let us create a second user via the user manager called "Tom Rootinger". If we run our script again with `root` as argument we will get the same output. This is because, by default the search service looks for exact matches. If we run the script as

```
exec searchuser.groovy root*
```

we get the expected result:

```
[root root, Tom Rootinger]
```

In a next step we want to use the `HistoryService` (located in `net.datenwerke.gf.service.history`) to generate links for the objects found by our script. The `HistoryService` has a sim-

3. Basics

gle method that takes an object and returns a list of links (objects of type `HistoryLink`). We will simply take the first link in this list (if it exists) and output it. The adapted script looks like

```
package myscripts

import net.datenwerke.gf.service.history.HistoryService;
import net.datenwerke.rs.search.service.search.SearchService;
import net.datenwerke.security.service.usermanager.entities.User;

SearchService searchSvc = GLOBALS.getRsService(SearchService.class)
HistoryService historySvc = GLOBALS.getRsService(HistoryService.class)

searchSvc.locate(User.class, args.join(" ")).collect{
    historySvc.buildLinksFor(it).get(0)?.getLink()
}.join("\n")
```

If we run this again using `exec searchuser.groovy root*` we get as output

```
usermgr/path:1.2.3&nonce:-1668828071
usermgr/path:1.4&nonce:475784900
```

On the one hand we are missing the server address and on the other, wouldn't it be nice to be able to actually click on the link? The server address can be accessed via the `ReportServerService`. Thus we could adapt our script as

```
package myscripts

import net.datenwerke.gf.service.history.HistoryService
import net.datenwerke.rs.core.service.reportserver.ReportServerService
import net.datenwerke.rs.search.service.search.SearchService
import net.datenwerke.rs.terminal.service.terminal.obj.CommandResult;
import net.datenwerke.security.service.usermanager.entities.User

SearchService searchSvc = GLOBALS.getRsService(SearchService.class)
HistoryService historySvc = GLOBALS.getRsService(HistoryService.class)
String urlBase = GLOBALS.getRsService(ReportServerService.class).getServerInfo(). ↗
    ↘ getBaseUrl();

searchSvc.locate(User.class, args.join(" ")).collect{
    urlBase + historySvc.buildLinksFor(it).get(0)?.getLink()
}
```

For the second part we need to return an object of type `CommandResult` (in package `net.datenwerke.rs.terminal.service.terminal.obj`). The `CommandResult` object allows us to better specify how the terminal treats the result returned by the script. It is able to display lists, tables, html and what we need for our task: links. The `CommandResult` object can create links either to external pages via `addResultHyperLink()` method or to internal locations via the `addResultAnchor()` method. Following is the final script.

```
package myscripts

import net.datenwerke.gf.service.history.HistoryService
import net.datenwerke.rs.core.service.reportserver.ReportServerService
```

```

import net.datenwerke.rs.search.service.search.SearchService
import net.datenwerke.rs.terminal.service.terminal.obj.CommandResult;
import net.datenwerke.security.service.usermanager.entities.User

SearchService searchSvc = GLOBALS.getRsService(SearchService.class)
HistoryService historySvc = GLOBALS.getRsService(HistoryService.class)
String urlBase = GLOBALS.getRsService(ReportServerService.class).getServerInfo().
    ↪ getBaseUrl();

CommandResult result = new CommandResult();
def links = searchSvc.locate(User.class, args.join(" ")).collect{
    result.addResultHyperLink(it.getName(), historySvc.buildLinksFor(it).get(0)?
    ↪ getLink() )
}

return result

```

Tip: Via the `terminal/alias.cf` configuration file you can make scripts directly accessible. For example the entry

```

<entry>
  <alias>search</alias>
  <command>exec /fileserver/bin/tmp/searchuser.groovy</command>
</entry>

```

would allow you to access your `searchuser` script from anywhere using the command `search`. If you change the config file don't forget to make ReportServer reload the configuration using the `config reload` terminal command.

3.4 Working with Entities

So far we have seen how we can access services via the GLOBALS object. In the following we will see how to work with entities. Entities are stored objects such as reports, users or TeamSpaces. You can find entities by searching for classes annotated with `@Entity`. You can also find a list of all entities in our ReportServer SourceForge project <https://sourceforge.net/projects/dw-rs/>. Download the latest apidocs file from the `src` directory for this.

Without directly spelling it out, we have in our above example already worked with user objects as the `SearchService` returns the actual entity objects. In the following we want to show how to access a particular entity by id. Almost all entities have a unique identifier which is usually called `id` and which normally can be accessed via the `getId()` method. Ids are in most cases of type `Long`. Go to the user manager in the administration module and select an arbitrary user (or use your `searchuser` script and click on a link). The user's id is displayed in the header line of the form that allows to set the user's properties. Let us assume that id is 4.

Usually, when you work with entities you will work with JPA's `EntityManager` (see <http://docs.oracle.com/javaee/6/api/javax/persistence/EntityManager.html>). The GLOBALS object provides access to an `EntityManager` by either the method `getEntityManager()` or as a `Provider` via `getEntityManagerProvider()`. For quick access to an entity it furthermore provides the methods `findEntity()` and `getEntitiesByType()`. In the following we want to create a simple script that

3. Basics

displays a list of all user objects. In a first step, we only access the user object with id 4 and display its name. We name our script `userlist.groovy`.

```
package myscripts

import net.datenwerke.security.service.usermanager.entities.User;

GLOBALS.findEntity(User.class, 4l)
```

Note the "l" behind the id. This is necessary to tell Groovy that the id is of type Long and not an integer. If you execute the script via

```
exec userlist.groovy
```

the user's name is printed. What the `findEntity` method returned however, was the user object. Let's have a closer look at that object. For this we can either have a look at the source of `User` (located in `net.datenwerke.security.service.usermanager.entities`), the javadoc of the `User` class or we use the terminal command `desc` which takes as argument an entity name and outputs a description of the entity class. Run

```
desc User
```

on the terminal. You see the various database fields that a `User` object stores. By convention, each field has a corresponding getter and setter. Thus the "username" property could be accessed via `getUsername()`. Let us change our script to output the username.

```
package myscripts

import net.datenwerke.security.service.usermanager.entities.User;

User user = GLOBALS.findEntity(User.class, 4l)

user.getUsername() + ' - ' + user.getName()
```

If we want to list the username of all users we can use the following adaption

```
package myscripts

import net.datenwerke.security.service.usermanager.entities.User;

GLOBALS.getEntitiesByType(User.class).collect{
    it.getUsername()
}.join("\n")
```

Writing to Entities

Suppose we want to do a bulk update, for example, synchronize our user objects with an external database. As you can imagine this is straightforward using ReportServer scripts. In the following we will add a simple comment to the description field of any group. For this, we can use a simple adaption of the above script

```
package myscripts

import net.datenwerke.security.service.usermanager.entities.Group
```

```

GLOBALS.getEntitiesByType(Group.class).each{
    it.setDescription("some description")
    tout.println("changed group: " + it.getName())
}

tout.println("done")

```

We call the file `editgroups.groovy`. To test our script, first go to the user management module in the admin module and create a few groups, let's say groups A and B. If you execute the script via `exec editgroups.groovy` you should see the following output:

```

changed group: A
changed group: B
done

```

However, if you look at your groups A and B nothing has changed, that is, the description was not added. This is because, by default the database transaction spanning a script execution is rolled back after the script is finished. In order to commit the transaction you need to supply the flag `"-c"` to the `exec` command. Call your script via

```
exec -c editgroups.groovy
```

If you now inspect the groups in the user management area you will find that, indeed, the description was added. Instead of inspecting the group in the user manager you can do this directly from the terminal via the `desc` command. As a third parameter the `desc` command takes an object which is then displayed. Thus, you could, for example, write

```
desc Group /usermanager/A
```

if your group is located directly in the root directory. Alternatively, you can specify the object via an hql (hibernate query language) query. Thus, we could also access the Group with name "A" via

```
desc Group "hql:from Group where name='A'"
```

In this way, you can also display multiple objects side by side

```
desc Group "hql:from Group"
```

To display the result in a new window, that is, the result is not directly added to the terminal window, add the `-w` flag to the `desc` command. To complete the picture you can also specify objects on the terminal via `type` and `id`. Thus, if your group has id 6, you could also write

```
desc Group id:Group:6
```

3.5 Interpreting Script Error Messages

When developing scripts ReportServer will support your debugging efforts by showing you full stack trace error messages. Let's go back to our simple `userlist` script but this time, I have included a typo:

```

package myscripts

import net.datenwerke.security.service.usermanager.entities.User;

```

3. Basics

```
GLOBALS.getEntitiesByType(User.class).collect{
    i.getUsername()
}.join("\n")
```

If we name this file "errorfile.groovy" and execute it, you will get the following error message:

```
net.datenwerke.rs.scripting.service.scripting.exceptions.ScriptEngineException: javax.script. ↗
    ↳ ScriptException: javax.script.ScriptException: groovy.lang.MissingPropertyException: No such ↗
    ↳ property: i for class: myscripts.Script5
at net.datenwerke.rs.scripting.service.scripting.engines.GroovyEngine.eval(GroovyEngine.java:62)
at net.datenwerke.rs.scripting.service.scripting.ScriptingServiceImpl.executeScript(ScriptingServiceImpl ↗
    ↳ .java:199)
at net.datenwerke.rs.scripting.service.scripting.ScriptingServiceImpl.executeScript(ScriptingServiceImpl ↗
    ↳ .java:242)
at net.datenwerke.rs.scripting.service.scripting.ScriptingServiceImpl.executeScript(ScriptingServiceImpl ↗
    ↳ .java:285)
at net.datenwerke.rs.scripting.service.scripting.ScriptingServiceImpl.executeScript(ScriptingServiceImpl ↗
    ↳ .java:256)
at net.datenwerke.rs.scripting.service.scripting.terminal.commands.ExecScriptCommand$1$1.doFilter( ↗
    ↳ ExecScriptCommand.java:228)
at com.google.inject.servlet.FilterChainInvocation.doFilter(FilterChainInvocation.java:66)
at com.google.inject.servlet.FilterDefinition.doFilter(FilterDefinition.java:168)
at com.google.inject.servlet.FilterChainInvocation.doFilter(FilterChainInvocation.java:58)
at com.google.inject.servlet.ManagedFilterPipeline.dispatch(ManagedFilterPipeline.java:118)
at com.google.inject.servlet.GuiceFilter.doFilter(GuiceFilter.java:113)
at net.datenwerke.rs.scripting.service.scripting.terminal.commands.ExecScriptCommand$1.call( ↗
    ↳ ExecScriptCommand.java:220)
at net.datenwerke.rs.scripting.service.scripting.terminal.commands.ExecScriptCommand$1.call( ↗
    ↳ ExecScriptCommand.java:1)
at java.util.concurrent.FutureTask$Sync.innerRun(FutureTask.java:334)
at java.util.concurrent.FutureTask.run(FutureTask.java:166)
at java.lang.Thread.run(Thread.java:722)
Caused by: javax.script.ScriptException: javax.script.ScriptException: groovy.lang. ↗
    ↳ MissingPropertyException: No such property: i for class: myscripts.Script5
at org.codehaus.groovy.jsr223.GroovyScriptEngineImpl.eval(GroovyScriptEngineImpl.java:138)
at net.datenwerke.rs.scripting.service.scripting.engines.GroovyEngine.eval(GroovyEngine.java:60)
... 15 more
Caused by: javax.script.ScriptException: groovy.lang.MissingPropertyException: No such property: i for ↗
    ↳ class: myscripts.Script5
at org.codehaus.groovy.jsr223.GroovyScriptEngineImpl.eval(GroovyScriptEngineImpl.java:335)
at org.codehaus.groovy.jsr223.GroovyScriptEngineImpl.eval(GroovyScriptEngineImpl.java:132)
... 16 more
Caused by: groovy.lang.MissingPropertyException: No such property: i for class: myscripts.Script5
at org.codehaus.groovy.runtime.ScriptBytecodeAdapter.unwrap(ScriptBytecodeAdapter.java:50)
at org.codehaus.groovy.runtime.callsite.PogoGetPropertySite.getProperty(PogoGetPropertySite.java:49)
at org.codehaus.groovy.runtime.callsite.AbstractCallSite.callGroovyObjectGetProperty(AbstractCallSite. ↗
    ↳ java:231)
at myscripts.Script5$_run_closure1.doCall(Script5.groovy:6)
at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:57)
at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
at java.lang.reflect.Method.invoke(Method.java:601)
at org.codehaus.groovy.reflection.CachedMethod.invoke(CachedMethod.java:90)
at groovy.lang.MetaMethod.doMethodInvoke(MetaMethod.java:233)
at org.codehaus.groovy.runtime.metaclass.ClosureMetaClass.invokeMethod(ClosureMetaClass.java:272)
at groovy.lang.MetaClassImpl.invokeMethod(MetaClassImpl.java:904)
at groovy.lang.Closure.call(Closure.java:415)
at groovy.lang.Closure.call(Closure.java:428)
at org.codehaus.groovy.runtime.DefaultGroovyMethods.collect(DefaultGroovyMethods.java:2203)
at org.codehaus.groovy.runtime.DefaultGroovyMethods.collect(DefaultGroovyMethods.java:2173)
at org.codehaus.groovy.runtime.dgm$60.invoke(Unknown Source)
at org.codehaus.groovy.runtime.callsite.PojoMetaMethodSite$PojoMetaMethodSiteNoUnwrapNoCoerce.invoke( ↗
    ↳ PojoMetaMethodSite.java:271)
```

```

at org.codehaus.groovy.runtime.callsite.PojoMetaMethodSite.call(PojoMetaMethodSite.java:53)
at org.codehaus.groovy.runtime.callsite.CallSiteArray.defaultCall(CallSiteArray.java:45)
at org.codehaus.groovy.runtime.callsite.AbstractCallSite.call(AbstractCallSite.java:108)
at org.codehaus.groovy.runtime.callsite.AbstractCallSite.call(AbstractCallSite.java:116)
at myscripts.Script5.run(Script5.groovy:5)
at org.codehaus.groovy.jsr223.GroovyScriptEngineImpl.eval(GroovyScriptEngineImpl.java:332)
... 17 more

```

The error stack trace typically consists of three parts: the error message, in this case

```

net.datenwerke.rs.scripting.service.scripting.exceptions.ScriptEngineException: javax.script. ↗
  ↳ ScriptException: javax.script.ScriptException: groovy.lang.MissingPropertyException: No such ↗
  ↳ property: i for class: myscripts.Script5

```

a stack trace of the failure propagation through ReportServer, here

```

at net.datenwerke.rs.scripting.service.scripting.engines.GroovyEngine.eval(GroovyEngine.java:62)
at net.datenwerke.rs.scripting.service.scripting.ScriptingServiceImpl.executeScript(ScriptingServiceImpl ↗
  ↳ .java:199)
at net.datenwerke.rs.scripting.service.scripting.ScriptingServiceImpl.executeScript(ScriptingServiceImpl ↗
  ↳ .java:242)
at net.datenwerke.rs.scripting.service.scripting.ScriptingServiceImpl.executeScript(ScriptingServiceImpl ↗
  ↳ .java:285)
at net.datenwerke.rs.scripting.service.scripting.ScriptingServiceImpl.executeScript(ScriptingServiceImpl ↗
  ↳ .java:256)
at net.datenwerke.rs.scripting.service.scripting.terminal.commands.ExecScriptCommand$1.doFilter( ↗
  ↳ ExecScriptCommand.java:228)
at com.google.inject.servlet.FilterChainInvocation.doFilter(FilterChainInvocation.java:66)
at com.google.inject.servlet.FilterDefinition.doFilter(FilterDefinition.java:168)
at com.google.inject.servlet.FilterChainInvocation.doFilter(FilterChainInvocation.java:58)
at com.google.inject.servlet.ManagedFilterPipeline.dispatch(ManagedFilterPipeline.java:118)
at com.google.inject.servlet.GuiceFilter.doFilter(GuiceFilter.java:113)
at net.datenwerke.rs.scripting.service.scripting.terminal.commands.ExecScriptCommand$1.call( ↗
  ↳ ExecScriptCommand.java:220)
at net.datenwerke.rs.scripting.service.scripting.terminal.commands.ExecScriptCommand$1.call( ↗
  ↳ ExecScriptCommand.java:1)
at java.util.concurrent.FutureTask$Sync.innerRun(FutureTask.java:334)
at java.util.concurrent.FutureTask.run(FutureTask.java:166)
at java.lang.Thread.run(Thread.java:722)

```

and the actual exception, which starts with a caused by clause:

```

Caused by: groovy.lang.MissingPropertyException: No such property: i for class: myscripts.Script5
at org.codehaus.groovy.runtime.ScriptBytecodeAdapter.unwrap(ScriptBytecodeAdapter.java:50)
at org.codehaus.groovy.runtime.callsite.PogoGetPropertySite.getProperty(PogoGetPropertySite.java:49)
at org.codehaus.groovy.runtime.callsite.AbstractCallSite.callGroovyObjectGetProperty(AbstractCallSite. ↗
  ↳ java:231)
at myscripts.Script5$_run_closure1.doCall(Script5.groovy:6)
at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:57)
at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
at java.lang.reflect.Method.invoke(Method.java:601)
at org.codehaus.groovy.reflection.CachedMethod.invoke(CachedMethod.java:90)
at groovy.lang.MetaMethod.doMethodInvoke(MetaMethod.java:233)
at org.codehaus.groovy.runtime.metaclass.ClosureMetaClass.invokeMethod(ClosureMetaClass.java:272)
at groovy.lang.MetaClassImpl.invokeMethod(MetaClassImpl.java:904)
at groovy.lang.Closure.call(Closure.java:415)
at groovy.lang.Closure.call(Closure.java:428)
at org.codehaus.groovy.runtime.DefaultGroovyMethods.collect(DefaultGroovyMethods.java:2203)
at org.codehaus.groovy.runtime.DefaultGroovyMethods.collect(DefaultGroovyMethods.java:2173)
at org.codehaus.groovy.runtime.dgm$60.invoke(Unknown Source)
at org.codehaus.groovy.runtime.callsite.PojoMetaMethodSite$PojoMetaMethodSiteNoUnwrapNoCoerce.invoke( ↗
  ↳ PojoMetaMethodSite.java:271)
at org.codehaus.groovy.runtime.callsite.PojoMetaMethodSite.call(PojoMetaMethodSite.java:53)

```

3. Basics

```
at org.codehaus.groovy.runtime.callsite.CallSiteArray.defaultCall(CallSiteArray.java:45)
at org.codehaus.groovy.runtime.callsite.AbstractCallSite.call(AbstractCallSite.java:108)
at org.codehaus.groovy.runtime.callsite.AbstractCallSite.call(AbstractCallSite.java:116)
at myscripts.Script5.run(Script5.groovy:5)
at org.codehaus.groovy.jsr223.GroovyScriptEngineImpl.eval(GroovyScriptEngineImpl.java:332)
```

Typically, what you need to look at to understand what went wrong is the caused by clause. In this case it tells us that the property "i" does not exist. It also tells us, how the script is known internally. It is called `myscripts.Scripts` where `myscripts` is the package name that we specified. If we examine the stack trace further we find in line 5 the following statement

```
at myscripts.Script5$_run_closure1.doCall(Script5.groovy:6)
```

This was the last call executed in our script. The number after the colon specifies the line that was executed. Thus, we should look for the missing property in line 6 of our script. As line 6 read

```
i.getUsername()
```

which should have been `it` instead of `i`, we have traced the error to its origin.

3.6 Reading and Writing to Files

Next we describe how to write to files (in the internal filesystem) from a script. Basically there are two ways to accomplish this. We have already seen how to work with persistent objects (or rather entities) such as users. A file is just such an entity:

```
net.datenwerke.rs.fileserver.service.fileserver.entities.FileServerFile
```

The corresponding service is the `FileServerService`. Thus, we could create a new file and store it. There is, however, a simpler way using the `GLOBALS` object. The `GLOBALS` object comes with a dedicated `fileService` object, that allows to easily read from and write to files.

As a first step we construct a new text file. We open the terminal and go to the `fileserver` and create a new temporary folder (e.g. `tmp` with `mkdir tmp`). To write some text into a new file we can simply use the following terminal command

```
echo foobar > file.txt
```

The `echo` command prints its arguments and the angular opening bracket forwards this output into the file `file.txt`. A single angular bracket will overwrite the contents of the file. To append text to the file use two angular brackets, for example:

```
echo more foobar >> file.txt
```

To inspect the created file you can either use the `editTextFile` command or use the `"cat"` command which simply dumps the text file to the terminal.

```
cat file.txt
```

Next, we are going to write a simple script that is going to emulate the `cat` command. We will call this script `myCat.rs`. For this create the script using

```
createTextFile myCat.rs
```

Remember that scripts need to be located beneath the bin folder. So if you created your script outside of the bin hierarchy move it there using the `mv` command. To emulate the `cat` command we only need a single line as the `GLOBALS` object offers some helper methods to read in files.

```
GLOBALS.read(args[0])
```

The `read` method takes a location of a file and returns the contents of the file as a string. Similarly the `write` method of the `GLOBALS` object allows to write to a text file. Note that this will overwrite the data within the file. Thus the following script emulates the terminal command `"echo TEXT > file"`

```
GLOBALS.write(args[0], args[1])
```

This could then be called, for example as

```
exec -c myWrite.rs file.txt 'This is some text'
```

Note the use of the `-c` flag to commit the changes and the use of single quotes to treat `'This ↵
↵ is some text'` as a single argument.

The `read` and `write` method of the `GLOBALS` object will always return (or expect) a string. If you want to work with binary files you can use the `fileService`. Via the `globals` object you have access to all Services provided by `ReportServer`. Additionally, there are a couple of services specifically for working with scripts. These are accessed via the `services` variable of the `GLOBALS` object. That is, we could have written our `myCat.rs` script also as

```
GLOBALS.services['fileService'].read(args[0])
```

In addition to the `read` and `write` methods the `fileService` has additionally the methods `readRaw` and `writeRaw` that allow to work directly with byte representations of the files.

Besides the `fileService` there are other services specifically available for script developers to help facilitate writing scripts. We will encounter them in the course of this manual. However, here is a short overview of the services available via `GLOBALS.services`

<code>fileService</code>	easy access to read and write files.
<code>scriptService</code>	provides methods to call scripts from within your script.
<code>registry</code>	A singleton registry that can be used to store and retrieve arbitrary values. The registry is held in memory and cleared on <code>ReportServer</code> restarts.
<code>clientExtensionService</code>	An interface to access client side extensions.

3.7 Nesting Scripts: Calling Scripts from Scripts

To properly structure larger scripts it can be helpful to spread functionality over several scripts. The above mentioned `scriptService` provides simple helper methods to call scripts from within scripts. For this, consider the following script which does nothing but provide two methods

```
def encrypt(plaintext, k){
  plaintext?.replaceAll("[^a-zA-Z ]", "").toUpperCase().collect{
    int c = ((it == ' ' ? 0 : (((int)it) - 64)) + k) % 27
    if(c == 0)
```

3. Basics

```
        return ' '
        return (c + 64) as char
    }.join()
}

def decrypt(ciphertext, k){
    return encrypt(ciphertext, (27 - k) % 27)
}
```

Assume this is stored in a file called `lib.rs`. For the interested reader, this is a simple implementation of the Caesar cipher (which should not be used for actual encryption). Now, to load these helper methods we can use the following, which we store in a file called `encryptionTest.rs`

```
GLOBALS.exec("lib.rs")

def plain = "The quick brown fox jumps over the lazy dog"
def key = 6
def cipher = encrypt(plain, key)

tout.println(plain)
tout.println(cipher)
tout.println(dec(cipher, key))
```

If you now run this script you should get the following output

```
reportserver$ exec encryptionTest.rs
The quick brown fox jumps over the lazy dog
ZNKFW OIQFHXBTF LUCFP SVYFUAKXFZ NKFRGEDFJUM
THE QUICK BROWN FOX JUMPS OVER THE LAZY DOG
```

Besides the simple `exec` method that we have used above the `GLOBALS` object provides a second `exec` method that takes as second parameter an argument string that is passed to the script.

Monitoring, Multithreading, Scheduling and other Advanced Techniques

In this chapter we are covering several advanced scripting techniques such as how to monitor script executions (and possibly stop the execution of a script), how to work with multiple threads, how to use the registry to temporarily or persistently store values and how to schedule scripts. Let us start by looking at how ReportServer executes scripts via the terminal.

4.1 Execution of Scripts

Whenever you execute a script via the terminal command `exec` the script execution is wrapped into a new thread. This allows to monitor the execution and if necessary stop the script. You can display a list of the currently running scripts via the terminal command `ps`.

The following script doesn't do much, but it needs almost one minute for it:

```
import java.lang.Thread

Thread.sleep(60000)

"awake again"
```

If you run this script, the Terminal window will remain inactive during the time of execution. You can either open a second terminal window (CTRL+ALT+T), or wait for the script to return and then run it using the silent flag:

```
exec -s sleep.groovy
```

The silent flag tells ReportServer to ignore the output of the script and run it in the background.

Now, by using the command `"ps"` you can view executions which are presently active.

```
reportserver$ ps
ID Date      User      Command      Thread Interrupted
1  03.05.13 16:23 3      exec -s sleep.groovy  false
```

By entering the `kill` command, you can cancel scripts. Here, first an interrupt will be sent to the script which in our case leads to sending the thread an interrupt. In our case we can interrupt the script as follows.

```
reportserver$ kill 1
```

When you call "ps" again you will see that the script was interrupted indeed. The following script, however, will not be terminated that easily. It catches any exception and thus also exceptions thrown on interrupt.

```
import java.lang.Thread

def slept = false;
while(! slept){
  try{
    Thread.sleep(60000)
    slept = true;
  } catch(all) {
  }
}
"done"
```

If you run this script and try to terminate it using "kill ID", you will see that the script is still listed by the "ps" command. Note that the flag "interrupted" is now set.

```
reportserver$ ps
ID Date      User      Command          Thread Interrupted
7 03.05.13 16:23    3      exec -s sleep.groovy true
```

To hard-terminate the execution you can enter `kill -f ID`. This will terminate the thread by `Thread.stop()`. Please keep in mind that this may have undesirable side effects. You will find a description of the `Thread.stop()` method and related issues under <http://docs.oracle.com/javase/7/docs/technotes/guides/concurrency/threadPrimitiveDeprecation.html>.

Note that scripts which are executed not via the terminal but, for example, during a script report execution or via the scheduler will not run in an extra thread. They will, thus, also not be listed by the ps command.

Starting scripts in the server thread

In some situations it might be helpful to avoid starting a script in an own thread, but to start it in the server thread. This means, however, that this script cannot be monitored and interrupted by "ps/kill". To start a script without an own thread use the `-n` flag.

4.2 Storing Values Between Scripts

When a script terminates its scope is cleared and any variables are lost. Sometimes it is helpful to store values which can then be retrieved at a later point, for example, by a different script. ReportServer provides script developers with two mechanisms to easily store and retrieve values at a later point. The script registry is kept in memory by ReportServer at all times and, thus, allows for very fast access. However, when ReportServer is restarted the registry is cleared. To

store values persistently, ReportServer offers the so called PropertiesService. Values stored via this service will be pushed to the database.

The registry is available via the GLOBALS object. Consider the following script `registryCnt.groovy`.

```
def registry = GLOBALS.services['registry']
def cnt = registry.containsKey("myCnt") ? registry.get("myCnt") : 0

cnt++;
registry.put("myCnt", cnt)

"The count is at: " + cnt
```

Executing this script multiple times will yield the following output

```
reportserver$ exec registryCnt.groovy
The count is at: 1
reportserver$ exec registryCnt.groovy
The count is at: 2
reportserver$ exec registryCnt.groovy
The count is at: 3
```

The registry implements `java.util.Map<String, Object>`. You can find detailed documentation on the various methods at <http://docs.oracle.com/javase/7/docs/api/java/util/Map.html>.

To store values persistently you need to use the PropertiesService (`net.datenwerke.gf.service.properties.PropertiesService`) which is a regular ReportServer service. Let us implement our same counter script as `persistentCnt.groovy`.

```
import net.datenwerke.gf.service.properties.PropertiesService

def registry = GLOBALS.getRsService(PropertiesService.class)
def cnt = registry.containsKey("myCnt") ? registry.get("myCnt") as int : 0

cnt++;
registry.setProperty("myCnt", cnt as String)

"The count is at: " + cnt
```

Note the `as int` and `as String`. The PropertiesService stores all its properties in form of character strings. If we execute the script, we get the following output.

```
reportserver$ exec persistentCnt.groovy
The count is at: 1
reportserver$ exec persistentCnt.groovy
The count is at: 1
reportserver$ exec persistentCnt.groovy
The count is at: 1
```

This is not quite as expected. If we have a look at the corresponding database table `RS_PROPERTY` you will see that the table is still empty. Alternatively, you can use the following terminal command

```
desc Property "hql:from Property"
```

which lists all entities of type Property. The reason is simple. We did not run the `exec` command in commit mode and, thus, the property change was not persisted. If we run the command again, this time with the `-c` flag, we get the following output.

```
reportserver$ exec -c persistentCnt.groovy
The count is at: 1
reportserver$ exec -c persistentCnt.groovy
The count is at: 2
reportserver$ exec -c persistentCnt.groovy
The count is at: 3
```

We can now also inspect the property using the `desc` command from before, which now yields:

```
d key version value
1 myCnt 2      3
```

4.3 Multithreading in Scripts

Sometimes it can be convenient to have work done in parallel. The common way to do this in Groovy or Java is to conjure up multiple threads that do the actual work and run them in parallel. Usually you would want to have the threads controlled by a thread pool. For this ReportServer provides an easy mechanism. The following script is a simple example of how to create thread pools using ReportServer's `DwAsyncService` ([net.datenwerke.async.DwAsyncService](#)):

```
import net.datenwerke.async.DwAsyncService
import net.datenwerke.async.configurations.*

def aService = GLOBALS.getRsService(DwAsyncService.class);
def poolName = "myPool"

// get pool
def pool = aService.initPool(poolName, new SingleThreadPoolConfig());

def runA = {
    (1..10).each{
        tout.println("A says: " + it)
        Thread.sleep(200)
    }
} as Runnable

def runB = {
    (1..10).each{
        tout.println("B says: " + it)
        Thread.sleep(200)
    }
} as Runnable

def futureA = pool.submit(runA)
def futureB = pool.submit(runB)

// wait for tasks
futureA.get()
```

```
futureB.get()
```

```
aService.shutdownPool(poolName)
```

The `initPool` method takes a name and a configuration and creates a new pool for the given configuration. If a pool with the same name already exists, it will first shutdown the old pool. If we run this script we get the following result:

```
reportserver$ exec threadExample.groovy
```

```
A says: 1
A says: 2
A says: 3
A says: 4
A says: 5
A says: 6
A says: 7
A says: 8
A says: 9
A says: 10
B says: 1
B says: 2
B says: 3
B says: 4
B says: 5
B says: 6
B says: 7
B says: 8
B says: 9
B says: 10
```

There are two things to note. First, the `println`s are not immediately pushed to the client. Currently `ReportServer` waits until the script terminates before it sends the result (which includes `println`s) to the client. Secondly, the script executed the two loops not in parallel, but consecutively. This is, because of our choice of thread pool. We used a `SingleThreadPoolConfig`, which constructs a thread pool consisting of a single thread. Besides the `SingleThreadPoolConfig` you can use a `FixedThreadPoolConfig` which generates a pool with a fixed size. Thus, if we exchange the `SingleThreadPoolConfig` by

```
new FixedThreadPoolConfig(2)
```

and rerun our program, we get the following (expected) output:

```
reportserver$ exec threadExample.groovy
```

```
A says: 1
B says: 1
B says: 2
A says: 2
A says: 3
B says: 3
B says: 4
A says: 4
B says: 5
A says: 5
```

```
B says: 6
A says: 6
A says: 7
B says: 7
B says: 8
A says: 8
B says: 9
A says: 9
B says: 10
A says: 10
```

4.4 Scheduling Scripts

The ReportServer scheduler is not only used to schedule reports, but it can also be used to schedule the execution of scripts. To schedule a script use the terminal command `scheduleScript`. It comes with two commands:

```
list      Lists all scheduled scripts
execute   Schedules a new script
```

To schedule a script you can use natural language expressions. Examples are

```
scheduleScript execute myScript.groovy " " today at 15:23
scheduleScript execute myScript.groovy " " every day at 15:23
scheduleScript execute myScript.groovy " " at 23.08.2012 15:23
scheduleScript execute myScript.groovy " " every workday at 15:23 starting on ↵
    ↵ 15.03.2011 for 10 times
scheduleScript execute myScript.groovy " " every hour at 23 for 10 times
scheduleScript execute myScript.groovy " " today between 16:00 and 23:00 every 10 ↵
    ↵ minutes
scheduleScript execute myScript.groovy " " every week on monday and wednesday at ↵
    ↵ 23:12 starting on 27.09.2011 until 28.11.2012
scheduleScript execute myScript.groovy " " every month on day 2 at 12:12 starting ↵
    ↵ on 27.09.2011 11:25 for 2 times
```

The " " (quotation marks) after the script name are the scripts arguments. If we schedule our previous `persistentCnt.groovy` script we get the following output

```
scheduleScript execute persistentCnt.groovy " " every hour at 23 for 10 times
Script persistentCnt.groovy scheduled. First execution: 13.12.2013 19:23:00
```

Via the `scheduleScript list` command you get an overview of all currently scheduled scripts:

```
reportserver$ scheduleScript list
id scriptId name          next firetime
1 573  persistentCnt.groovy 13.12.2013 19:23:00
```

To get an overview of the next fire times you can use the scheduler command.

```
reportserver$ scheduler listFireTimes 1
13.12.2013 19:23:00
13.12.2013 20:23:00
13.12.2013 21:23:00
```

```
13.12.2013 22:23:00
13.12.2013 23:23:00
14.12.2013 19:23:00
14.12.2013 20:23:00
14.12.2013 21:23:00
14.12.2013 22:23:00
14.12.2013 23:23:00
```

Here 1 denotes the schedule entry's id. The scheduler command can also be used for scheduled reports.

To remove an entry you can use the "scheduler remove" command, for example to remove the above entry you need to run

```
reportserver$ scheduler remove 1
```

Script Reporting

Besides for administrative tasks, ReportServer scripts can be used for generating reports or for providing data sources that can then be used together with any other reporting engine within ReportServer. If you are familiar with scripting and fluent in HTML and CSS you will find script reports a simple to use reporting alternative that is highly flexible. Script reports usually render to HTML which allows to create highly dynamic reports using AJAX and advanced web technologies. Naturally, you are not limited to HTML reporting but are free to produce any output format you choose, for example, PDF or even a zip archive containing multiple files. ReportServer supports you in that it provides renderers to turn HTML formatted reports into PDF and Microsoft Word (docx) files. Furthermore, ReportServer provides a simple to use exporter to generate Microsoft Excel documents. An example of a script report using the PDF renderer is the report documentation report that is shipped with ReportServer (see Administrators guide).

As for data sources, script data sources give you the flexibility to easily integrate any sort of data with ReportServer. A script data source can even accumulate data from various sources, that is, it can be used to implement a multi-platform join.

Generating Reports using Scripts. A script report consists of at least two objects: a script and a report. In addition a script report can be configured to use a data source. In the following we are going to, step by step, build several example reports:

- The first report we are going to create is a simple static report that allows us to show the basic concepts of script reports. This includes exporting into various output formats, working with Groovy's (X)HTML builder and working with parameters and arguments. If you have read the chapter on script reports in the administrator's manual most of this should be familiar.
- The second script will explain how to work with data sources.
- The third and final example will explain how to create a dynamic report, that allows for user interaction and which uses a dynamic list as data backend.

5.1 Basic Script Reports

By default script reports are supposed to generate HTML. Thus, all we really need is to return HTML code as in the following example (note that we are using Groovy's multiline string feature here).

```
return """\n<html>\n<head>\n  <title>Hello World</title>\n</head>\n<body>\n  <h1>Hello World</h1>\n</body>\n</html>\n"""
```

Let us store this script as `/bin/reports/report1.rs`. The next step is to define a script report. For this go to the report manager and create a new object of type script report. Provide a name and select the previously create script as script reference. After submitting the data you can execute the report as usual by simply double clicking on the item from the report manager. You should see that the report simply displays the content as defined by the HTML code. In contrast to other reports, there is no button for scheduling the report or exporting it. This is because we have not yet defined output formats for the report. For this go back to the script report in the report manager. Here you can define output Formats as a comma separated list. For example we can define

HTML, Plain

Submit the changes and reopen the report. You see that you now have two export options: HTML and Plain. However, both options produce the same, somewhat unexpected result. The browser displays the HTML code rather than the interpreted website. This is, because we have not specified the return type. For this, we need to return an object of type `net.datenwerke.rs.core.service.reportmanager.engine.CompiledReport` which besides the report's content contains information on, for example, the resulting mime type. Several predefined and simple to use objects are available:

`net.datenwerke.rs.core.service.reportmanager.engine.basereports.CompiledTextReportImpl`
For simple text documents.

`net.datenwerke.rs.core.service.reportmanager.engine.basereports.CompiledHtmlReportImpl`
For html documents.

`net.datenwerke.rs.core.service.reportmanager.engine.basereports.CompiledDocxReport`
For Microsoft Word documents.

`net.datenwerke.rs.core.service.reportmanager.engine.basereports.CompiledXlsxReport`
For Microsoft Excel documents.

`net.datenwerke.rs.core.service.reportmanager.engine.basereports.CompiledJsonReportImpl`
For JSON documents.

```
net.datenwerke.rs.core.service.reportmanager.engine.basereports.CompiledCsvReportImpl
```

For comma separated value documents.

```
net.datenwerke.rs.core.service.reportmanager.engine.basereports.CompiledPdfReportImpl
```

For PDF documents.

Thus, to make the browser render the output we could adapt our above script to

```
import net.datenwerke.rs.core.service.reportmanager.engine.basereports. ↵
    ↵ CompiledHtmlReportImpl

def report = """\
<html>
<head>
  <title>Hello World</title>
</head>
<body>
  <h1>Hello World</h1>
</body>
</html>
"""

return new CompiledHtmlReportImpl(report)
```

While the browser now renders the exported report properly, it also does so when using the export option **Plain**. To differentiate between the two output formats scripts have access to a predefined variable **outputFormat**. This variable contains the selected output format. Consider the following adaption

```
import net.datenwerke.rs.core.service.reportmanager.engine.basereports. ↵
    ↵ CompiledHtmlReportImpl

def report = """\
<html>
<head>
  <title>Hello World</title>
</head>
<body>
  <h1>Hello World</h1>
</body>
</html>
"""

if(outputFormat == 'plain')
  return 'Hello World'
return new CompiledHtmlReportImpl(report)
```

Note that, although the output format was defined as **Plain**, the script is given the output format in lower case and with leading and trailing whitespace removed. Now if you export the report to **Plain** you get the expected plain Hello World response, while an export to **HTML** will lead to a rendered Hello World response.

5.2 Groovy's Markup Builder

In the above example we wrote the HTML code as a plain text string. In the following example we use Groovy's Markup XML Builder.

```
import net.datenwerke.security.service.authenticator.AuthenticatorService
import net.datenwerke.rs.core.service.reportmanager.engine.basereports. ↗
    ↳ CompiledHtmlReportImpl
import groovy.xml.*

def user = GLOBALS.getRsService(AuthenticatorService.class).getCurrentUser()

def writer = new StringWriter()

new MarkupBuilder(writer).html {
    head {
        title ( 'Hello World' )
    }
    body {
        h1("Hello ${user.getFirstname()}")
    }
}

return new CompiledHtmlReportImpl(writer.toString())
```

Besides using the Markup Builder we have personalized the greeting a bit. Let us add some extra styling:

```
import net.datenwerke.security.service.authenticator.AuthenticatorService
import net.datenwerke.rs.core.service.reportmanager.engine.basereports. ↗
    ↳ CompiledHtmlReportImpl
import groovy.xml.*

def user = GLOBALS.getRsService(AuthenticatorService.class).getCurrentUser()

def writer = new StringWriter()

new MarkupBuilder(writer).html {
    head {
        title ( 'Hello World' )
    }
    body {
        h1(style: 'color: #f00', "Hello ${user.getFirstname()}")
        p("Isn't that an easy way to create a report?")
    }
}

return new CompiledHtmlReportImpl(writer.toString())
```

5.3 Generating PDF and Word output

Now that we have a simple styled report, let us export it not only to HTML but also to PDF and Microsoft Word. Basically, what we need to do is to output the byte code expected by a PDF reader (resp. a valid Word document). For this we can either use one of many java libraries such as Apache POI (<http://poi.apache.org/>). ReportServer, however, makes it easy for you to go from HTML directly to PDF and Word. For this you have access to two renderers via the predefined object renderer. First go back to the report manager and define the following output Formats

HTML, PDF, Word

Now, we need to adapt the report

```
import net.datenwerke.security.service.authenticator.AuthenticatorService
import groovy.xml.*

def user = GLOBALS.getRsService(AuthenticatorService.class).getCurrentUser()

def writer = new StringWriter()

new MarkupBuilder(writer).html {
  head {
    title ( 'Hello World' )
  }
  body {
    h1(style: 'color: #f00', "Hello ${user.getFirstname()}")
    p("Isn't that an easy way to create a report?")
  }
}

if(outputFormat == 'word')
  return renderer.get("docx").render(writer.toString())
if(outputFormat == 'pdf')
  return renderer.get("pdf").render(writer.toString())

return renderer.get("html").render(writer.toString())
```

You can now export the report to the various formats. Also note, that the HTML renderer that we used in the very last line is equivalent to using `CompiledHtmlReportImpl`.

5.4 Running Script Reports from the Terminal

For testing it might be helpful to run the script directly from the terminal. However, if you try to do this, with our above script you get the following exception:

```
reportserver$ exec report1.rs
net.datenwerke.rs.scripting.service.scripting.exceptions.ScriptEngineException: javax.script. ↵
  ↳ ScriptException: javax.script.ScriptException: groovy.lang.MissingPropertyException: No such ↵
  ↳ property: outputFormat for class: Script13
...
```

5. Script Reporting

The problem is that we used the variable `outputFormat` which is supplied by the script reporting engine but if we run the script as is, this variable does not exist.

```
import net.datenwerke.security.service.authenticator.AuthenticatorService
import groovy.xml.*

// define outputFormat if not already in binding
if(! binding.hasVariable('outputFormat'))
    outputFormat = null

def user = GLOBALS.getRsService(AuthenticatorService.class).getCurrentUser()

def writer = new StringWriter()

new MarkupBuilder(writer).html {
    head {
        title ( 'Hello World' )
    }
    body {
        h1(style: 'color: #f00', "Hello ${user.getFirstname()}")
        p("Isn't that an easy way to create a report?")
    }
}

if(outputFormat == 'word')
    return renderer.get("docx").render(writer.toString())
if(outputFormat == 'pdf')
    return renderer.get("pdf").render(writer.toString())
if(outputFormat == 'html')
    return renderer.get("html").render(writer.toString())

return writer.toString()
```

The variable binding is a special groovy variable that allows you to access the available variable bindings for the current script. It is an object of type `groovy.lang.Binding`. By not giving the `outputFormat` a type, that is by defining it as

```
outputFormat = null
```

instead of as

```
def outputFormat = null
```

or

```
String outputFormat = null
```

we add the variable to the binding instead of the current scope (which would be limited by the `if` clause. Thus, we can safely later on assume that the variable is defined. Note also that we slightly changed the final return value as also the `renderer` is a special object provided by the reporting engine.

5.5 Testing via Browsers

Simpler than testing via the terminal is to open the report in its own browser window by directly accessing it via the URL. For this use

http://SERVER:PORT/rsbasedir/reportserver/reportexport?id=REPORT_ID&format=HTML

More information on calling reports directly via the URL can be found in the administrator's guide.

5.6 Working with Parameters and Arguments

To conclude our first simple report example we want to show you how to access parameters and work with script arguments. The latter is easily established. If you return to the report management and select the script report you see a field for arguments. These arguments are passed to the script in the same way as command line arguments are passed to scripts. Thus, the following would simply output the arguments

```
new MarkupBuilder(writer).html {
    head {
        title ( 'Hello World' )
    }
    body {
        h1(style: 'color: #f00', "Hello ${user.getFirstname()}")
        p("Isn't that an easy way to create a report?")
        p('Arguments: ' + args.join(','))
    }
}
```

Parameters are handled similarly. Parameters can be accessed via the variables **parameterSet** and **parameterMap**. The first variable points to the ReportServer ParameterSet object. Other than the **parameterMap** this does not only store parameter keys and values but contains additional information on the parameter. See `net.datenwerke.rs.core.service.reportmanager.parameters.ParameterSet` for more details. Usually only the **parameterMap** variable is needed which stores the parameters in a `java.util.Map<String, Object>`. Let us add a simple text parameter to our report and we give it the name **param**.

```
new MarkupBuilder(writer).html {
    head {
        title ( 'Hello World' )
    }
    body {
        h1(style: 'color: #f00', "Hello ${user.getFirstname()}")
        p("Isn't that an easy way to create a report?")
        p('Arguments: ' + args.join(','))
        p('The single parameter is: ' + parameterMap['param'])
    }
}
```

That concludes the basic example. In the next section we see how to work with datasources.

5.7 Working with Datasources

In the following section we are going to create a second script report that directly accesses a datasource. Let us create a new script called `report2.rs` which we also put into `/bin/reports`. We will use Groovy's Sql functionality to directly access the database. Create a new script report in the report manager. As for any other report type you can select a datasource for the report. This datasource will then be given to your script via the predefined variable **connection**. In case the datasource is a relational database the **connection** variable would hold an actual database connection. Note that there is no need to close the connection as ReportServer will do that for you. The following script accesses the table `T_AGG_CUSTOMER` from the demo database.

```
import groovy.sql.Sql
import groovy.xml.*

def writer = new StringWriter()

new MarkupBuilder(writer).html {
  head {
    title ( 'Hello World' )
  }
  body {
    table {
      new Sql(connection).eachRow("SELECT CUS_CUSTOMERSNAME, CUS_CREDITLIMIT FROM ↵
      ↵ T_AGG_CUSTOMER") { row ->
      tr {
        td(row.CUS_CUSTOMERSNAME)
        if(row.CUS_CREDITLIMIT > 100000)
          td(style:'color:#F00', row.CUS_CREDITLIMIT)
        else
          td(row.CUS_CREDITLIMIT)
        }
      }
    }
  }
}

renderer.get('html').render(writer.toString())
```

5.8 Interactive Reports

As a final example we want to create a simple dynamic report which uses a dynamic list as its backend. For dynamic reports the logic will be written in JavaScript and the Groovy script will be mostly a container serving the JavaScript code. Create the following script as `report3.rs` in `/bin/reports` and create a fresh script report pointing to it.

```
import groovy.sql.Sql
import groovy.xml.*

def writer = new StringWriter()

new MarkupBuilder(writer).html {
```

```

head {
  title ( 'Dynamic World' )
  script(language: 'javascript', type: 'text/javascript', """\
    alert('Hello Dynamic World')
  """)
}
body {
}
}

```

```
renderer.get('html').render(writer.toString())
```

If you call the report you will be greeted with a JavaScript alert message. Let us now add some content to our report. For this we will access the dynamic list `T_AGG_CUSTOMER` (from the demo package). We assume that the list has key “customer”. We will use jquery to easily modify the DOM. We query the dynamic list to retrieve two attributes and build a table of the results.

```

import groovy.sql.Sql
import groovy.xml.*

def writer = new StringWriter()

new MarkupBuilder(writer).html {
  head {
    title ( "Dynamic World" )
    script(language: "javascript", type: "text/javascript", src: "http://www2.datenwerke.net/files/blog ↵
      ↵ /js/jqplot/jquery.min.js", " " )
  }
  body {
    h1("Dynamic World" )
    table (id: "content", " ")
    script(type: "text/javascript") { mkp.yieldUnescaped("""
    \$.getJSON( 'http://127.0.0.1:8888/reportserver/reportexport?key=customer&c_1=CUS_CUSTOMERNAME&c_2= ↵
      ↵ CUS_CREDITLIMIT&format=json', function(data) {
    \$.each( data, function( key, val ) {
      \$( "<tr><td>" + val['CUS_CUSTOMERNAME'] + "</td><td>" + val['CUS_CREDITLIMIT'] + "</td></tr>" ↵
      ↵ ).appendTo("#content");
    });
  });
  """) }
  }
}

renderer.get('html').render(writer.toString())

```

So, what have we done? First, note that self-closing script tags are likely to produce errors. Thus, we added a dummy space as content to the script tag that is loading jquery. A second change we introduced is to call `mkp.yieldUnescaped` to write our javascript code. This is to ensure that entities such as “&” are not escaped. Now, we get to the actual content retrieval. We used jquery’s `getJSON` function to load data from the following URI

http://127.0.0.1:8888/reportserver/reportexport?key=customer&c_1=CUS_CUSTOMERNAME&c_2=CUS_CREDITLIMIT&format=json

Here we specified to use the report with key **customer**, and selected two columns: `CUS_CUSTOMERNAME` ↵
↵ and `CUS_CREDITLIMIT`. Additionally, we told ReportServer to return data in the JSON format.

5. Script Reporting

Now all we did was to loop over the retrieved data and added an entry to our table.

So far, we have only created a static script, so let us add some dynamic elements to it. We will add an input field that allows to specify a minimum credit limit and on changes retrieve the filtered data from the server.

```
import groovy.sql.Sql
import groovy.xml.*

def writer = new StringWriter()

new MarkupBuilder(writer).html {
    head {
        title ( "Dynamic World" )
        script(language: "javascript", type: "text/javascript", src: "http://www2.datenwerke.net/files/blog ↵
        ↵ /js/jqplot/jquery.min.js", " " )
    }
    body {
        h1("Dynamic World" )
        input (id: "filter", type: "text", value: "10000")
        input (id: "btn", type: "button", value: "Retrieve Filtered Data" )
        table (id: "content", " ")
        script(type: "text/javascript") { mkp.yieldUnescaped("""
        \$("#btn").click(function(event){
            var val = \$("#filter").val();
            \$("#content").html("<tr><td>loading data</td></tr>");
            \$.getJSON( 'http://127.0.0.1:8888/reportserver/reportexport?key=customer&c_1=CUS_CUSTOMERNAME&c_2= ↵
            ↵ CUS_CREDITLIMIT&format=json&or_2=ASC&fri_2=' + val + ' -', function(data) {
                \$("#content").empty();
                \$.each( data, function( key, val ) {
                    \$( "<tr><td>" + val['CUS_CUSTOMERNAME'] + "</td><td>" + val['CUS_CREDITLIMIT'] + "</td></tr ↵
                ↵ >").appendTo("#content");
                });
            });
        });
        """) }
    }
}

renderer.get('html').render(writer.toString())
```

First, you should notice that we added a static textbox and a button. In our javascript code we added a callback to click events on the button. If the button is clicked, we first clear the content of our table (that we address by its id **content**) and read out the value of the textbox. We then perform an ajax call to URI

```
http://127.0.0.1:8888/reportserver/reportexport?key=customer&c_1=CUS_CUSTOMERNAME&c_2=CUS_CREDITLIMIT&format=json&or_2=ASC&fri_2='+val+' -'
```

As **val** contains the value of the textfield (say 10000) this would result in the following URL

```
http://127.0.0.1:8888/reportserver/reportexport?key=customer&c_1=CUS_CUSTOMERNAME&c_2=CUS_CREDITLIMIT&format=json&or_2=ASC&fri_2=10000 -'
```

With this URL we have introduced two changes. First, we order the resulting data by column 2, that is by CUS_CREDITLIMIT. Secondly, we added a range filter and use the result of the filter value as a lower bound.

Script Datasources

Script datasources are your swiss army knife when it comes to integrating data from various formats. Basically, what script datasources do is to produce any sort of data and output it in a table format, that ReportServer understands. This data will then be loaded (and potentially cached) in ReportServer's internal database (see Administrator's guide) which then allows you to build any sort of report (for example a dynamic list) on top of it.

Say you have an XML dataset such as the following dataset taken from **socrata** (a platform for open data):

<https://opendata.socrata.com/api/views/n4ex-cets/rows.xml?accessType=DOWNLOAD>

It lists the top 5000 from **INC.com** in the following XML format:

```
<response>
  <row>
    <row _id="1" _uuid="896E0607-A4B7-44C3-B496-212EA911A118" _position="1" _address="http://opendata. ↵
      ↵ socrata.com/resource/n4ex-cets/1">
      <rank>1.0</rank>
      <company url="http://www.inc.com/inc5000/2009/company-profile.html?id=200900010" description=" ↵
        ↵ Northern Capital Insurance"/>
      <city>Miami</city>
      <state>FL</state>
      <industry>Insurance</industry>
      <revenue>95000000.0</revenue>
      <growth>19812.2</growth>
    </row>
    <row _id="2" _uuid="E16EBF5E-3F16-4C5A-9C71-E958A7420122" _position="2" _address="http://opendata. ↵
      ↵ socrata.com/resource/n4ex-cets/2">
      <rank>2.0</rank>
      <company url="http://www.inc.com/inc5000/2009/company-profile.html?id=200900020" description=" ↵
        ↵ National Retirement Partners"/>
      <city>San Juan Capistrano</city>
      <state>CA</state>
      <industry>Financial Services</industry>
      <revenue>47400000.0</revenue>
      <growth>13416.4</growth>
    </row>
  </row>
</response>
```

In order to make this data available in ReportServer, we need to load this data using a simple script

6. Script Datasources

and transform it into an object of type `net.datenwerke.rs.base.service.reportengines.table.output.object.RSTableModel` which is a simple wrapper for a table. `RSTableModel` basically consists of a definition of a table (defining attributes) and a list of rows. So a simple table could be defined as

```
import net.datenwerke.rs.base.service.reportengines.table.output.object.*

def td = new TableDefinition(['colA', 'colB', 'colC'], [String.class, Integer. ↵
    ↵ class, String.class])

def table = new RSTableModel(td)
table.addDataRow('A', 10, 'C')
table.addDataRow('foo', 42, 'bar')

return table
```

If executed, this script would produce the following output.

```
reportserver$ exec ds1.rs
Table(definition:TableDefinition [columnNames=[colA, colB, colC], columnTypes=[ ↵
    ↵ class java.lang.String, class java.lang.Integer, class java.lang.String]], ↵
    ↵ rows: 2)
```

A script, as in the above example, is all we need to specify a script datasource. All that would be left to do is to create a new data source (in the data source management tree of the administrator's module) of type script data source and select the just created script. The only other configuration choice is to specify whether the data should be cached in the internal database (and if so, for how long) or whether the script should be executed whenever a request to the dataset is made. Henceforth, the datasource can be used similar to any other relational database.

In the following we will explain, step by step, how the above dataset can be transformed into a `RSTableModel`. The first step is to create the `TableDefinition`. The dataset consists of 7 attributes of various types:

```
def td = new TableDefinition(['rank', 'company', 'city', 'state', 'industry', ' ↵
    ↵ revenue', 'growth'], [Integer.class, String.class, String.class, String. ↵
    ↵ class, String.class, BigDecimal.class, BigDecimal.class])
```

In a next step we need to read in the XML. This task can be easily achieved using Groovy's `XmlSlurper`.

```
import groovy.util.XmlSlurper

def address = "https://opendata.socrata.com/api/views/n4ex-cets/rows.xml? ↵
    ↵ accessType=DOWNLOAD"

def connection = address.toURL().openConnection()
def feed = new XmlSlurper().parseText(connection.content.text)

return feed.size()
```

Executing the above script might take a few seconds, but you should see the following result

```
reportserver$ exec ds1.rs
```

1

There is exactly one root node, so the size is one. Now, all left to do is to loop over the records and add them to the table. Note above, that the rank is given in decimal notation, although it encodes an integer. We will, thus, before translating it into an integer remove the last two characters (the “.0”).

```
feed.row.row.each {
    table.addRow(
        Integer.parseInt(it.rank.text()[0..-3]),
        it.company.url.text(),
        it.city.text(),
        it.state.text(),
        it.industry.text(),
        it.revenue.toBigDecimal(),
        it.growth.toBigDecimal()
    )
}
```

Putting it all together, we get the following simple script:

```
import net.datenwerke.rs.base.service.reportengines.table.output.object.*
import groovy.util.XmlSlurper

def address = "https://opendata.socrata.com/api/views/n4ex-cets/rows.xml? ↵
    ↵  accessType=DOWNLOAD"

def connection = address.toURL().openConnection()
def feed = new XmlSlurper().parseText(connection.content.text)

def td = new TableDefinition(['rank', 'company', 'city', 'state', 'industry', ' ↵
    ↵ revenue', 'growth'], [Integer.class, String.class, String.class, String. ↵
    ↵ class, String.class, BigDecimal.class, BigDecimal.class])
def table = new RSTableModel(td)

feed.row.row.each {
    table.addRow(
        Integer.parseInt(it.rank.text()[0..-3]),
        it.company.url.text(),
        it.city.text(),
        it.state.text(),
        it.industry.text(),
        it.revenue.toBigDecimal(),
        it.growth.toBigDecimal()
    )
}

return table
```

Tapping into ReportServer

ReportServer makes heavy use of a subscriber-notifier pattern which we call hooking. That is, a central HookHandlerService plays the role of registry where so called Hooks can be registered. These registered code snippets are then notified, when certain code is executed (for example, when a report is about to be executed) or to provide functionality (for example, to handle the authentication process or export a report into a specified format). In this section we explain the basics of registering scripts as Hooks and discuss some of the more common Hook interfaces. Other examples of customization using Hooks are given in the appendix.

Besides extending ReportServer via hooks, ReportServer has an event mechanism that can be used to be notified upon certain events, such as changes to entities (for example, one can be notified whenever a report is changed) or on errors.

7.1 ReportServer Hooks Basics

A ReportServer hook is simply an interface that inherits the `net.datenwerke.hookhandler.shared.hookhandler.interfaces.hook` interface. Hooks are used throughout ReportServer to provide mechanisms to easily extend the ReportServer functionality. For example, hooks can be used to register additional database drivers, to add report output formats, to allow for customized authentication (for example, LDAP) and much more. To register a hook with ReportServer you will usually use the callbackRegistry which is available via the GLOBALS object. The callbackRegistry offers two methods to register a new hook:

`attachHook()` takes as input a class object, to specify the hook interface and an object from type hook (usually called hooker) which contains the actual code. The method returns a unique name for the hook which can be used to deregister it again.

`attachHook(name)` same as before, but one additionally specifies the name as first parameter. This makes it easy to remove or update the hooker by simply accessing it via the specified name. That is, if this method is called twice with the same name, then only one hook is registered.

To deregister hooks you can use the method `detachHook(name)` which takes the name of a previously

7. Tapping into ReportServer

registered hook as input. To get a list (or rather a map) of all the registered hooks use the method `getRegisteredHooks` which returns a map (name -> hook).

The easiest way to learn how to work with ReportServer hooks is to actually implement one. In the following we will create a simple hook that is notified before every report execution and denies the execution in case the request is not within the normal working hours. For this we will use the `ReportExecutionNotificationHook` or more precisely the ([net.datenwerke.rs.core.service.reportmanager.hooks.ReportExecutionNotificationHook](#)). Following is the basic outline of a script that registers a hook:

```
def HOOK_NAME = "THE NAME OF MY HOOK"

def callback = [
  /* implementation of hook */
] as TypeOfHook

GLOBALS.services.callbackRegistry.attachHook(HOOK_NAME, TypeOfHook.class, callback ↵
  ↵ )
```

In our case, this could look as follows

```
import net.datenwerke.rs.core.service.reportmanager.exceptions.*
import net.datenwerke.rs.core.service.reportmanager.hooks.*

def HOOK_NAME = "PROHIBIT_EXECUTION"

def callback = [
  notifyOfReportExecution : { report, parameterSet, user, outputFormat, configs ↵
    ↵ -> },
  notifyOfReportsSuccessfulExecution : { compiledReport, report, parameterSet, ↵
    ↵ user,
outputFormat, configs -> },
  notifyOfReportsUnsuccessfulExecution : { e, report, parameterSet, user, ↵
    ↵ outputFormat,
configs -> },
  doVetoReportExecution: { report, parameterSet, user, outputFormat, configs ->
    def cal = Calendar.instance
    def hour = cal.get(Calendar.HOUR_OF_DAY)
    if(hour > 17 || hour < 9)
      throw new ReportExecutorException("Please come back during working hours.");
    }
] as ReportExecutionNotificationHook

GLOBALS.services.callbackRegistry.attachHook(HOOK_NAME, ↵
  ↵ ReportExecutionNotificationHook.
class, callback)
```

We have implemented the interface `ReportExecutionNotificationHook` which has four methods. In our case we wanted to stop the execution of a report execution. For this, the interface specifies that we should throw a `ReportExecutorException`.

All that is left is to execute the above script.

```
reportserver$ exec denyexecutionhook.rs
PROHIBIT_EXECUTION
```

Tip: When implementing hooks you need to take care to properly implement the interface. Bugs that lead to an exception within your implementation could otherwise easily lead to unexpected behavior.

Getting a List of all Registered Hooks

It may be useful to list all the registered hooks, or all the registered hooks of a specific type. For this we can use the method "getRegisteredHooks" provided by the callbackRegistry. The following simple script simply outputs the name of all registered hooks together with the date, when the hook has been registered.

```
GLOBALS.services.callbackRegistry.getRegisteredHooks().each { key, value ->
  tout.println(key + ": " + value.getDate())
}

""
```

7.2 Registering Hooks on Start-up and on Login

On start-up and when a user logs in ReportServer executes a specially named script or all scripts in a named folder, respectively. This is the place to register your hooks in case you permanently want to adapt certain ReportServer functionality. The location of these scripts is configured in the config file `scripting/scripting.cf` (for further information see the freely available ReportServer Configuration Guide). The config could, for example, look like

```
<?xml version="1.0" encoding="UTF-8"?>
<configuration>
  <scripting>
    <enable>true</enable>
    <restrict>
      <location>bin</location>
    </restrict>
    <startup>
      <login>filesaver/bin/onlogin.d</login>
      <rs>filesaver/bin/onstartup.d</rs>
    </startup>
  </scripting>
</configuration>
```

Assuming that `onstartup.d` is a directory, ReportServer would execute all scripts within this directory on start-up. Note that ReportServer will not recursively traverse directories.

If something goes wrong during a start-up script ReportServer will record this event in its audit log. To access the audit log simply create a dynamic list pointing to the database that hosts ReportServer. The table is `RS_AUDIT_LOG`. The action is named `STARTUP_SCRIPT_FAILED`. More information on the audit log can be found in the administrator's manual.

7.3 Which Hooks can I use?

The interface `net.datenwerke.hookhandler.shared.hookhandler.interfaces.Hook` is implemented by all ReportServer Hooks. Thus, a good starting point is the Javadoc documentation of the source. In principle any such hook can be implemented. For hooks that were especially designed to be implemented by scripts we have added an adapter class that provides a dummy implementation for all methods required by the hook. You will find the corresponding adapter in the subpackage `adapter`. Other than the source directly the examples in the appendix of this manual should provide a good starting point.

Extending the Client

In this chapter we consider various ways to extend the client side of ReportServer. Some of these extensions will be configured via configuration files and which allow, for example, to add further information tabs to the TeamView or add further links to the module bar. Other extensions need scripting. These include adding additional report exporters, displaying messages on login, or adding custom information to the status bar.

8.1 UriView - Incorporating Websites and More

Via the configuration file `/etc/ui/urlview.xml` you can add links and tabs to various locations within ReportServer. For example, you can add a new link to the module bar and specify to which URL it should point. Additionally you can restrict what you want to add to certain users or groups. A typical configuration file could like

```
<?xml version="1.0" encoding="UTF-8"?>
<configuration>
  <adminviews>
    <view>
      <!-- View Configuration -->
    </view>
  </adminviews>
  <objectinfo>
    <view>
      <!-- View Configuration -->
    </view>
    <view>
      <!-- View Configuration -->
    </view>
  </objectinfo>
  <module>
    <!-- View Configuration -->
  </module>
</configuration>
```

The three scopes (`adminviews`, `objectinfo` and `module`) allow you to add additional information tabs to objects in the administration module (for example, add an additional tab to a user object

8. Extending the Client

displaying information on that particular user), additional tabs to objects in the teamspace and within module you can add additional links to the module bar. The documentation report within teamspace is by default, for example, integrated via the an objectinfo view configuration.

View configurations all share the following configuration

```
<view>
  <restrictTo><!-- can be used to restrict this to specific users/groups--></
    ↳ restrictTo>
  <name>The display name</name>
  <url>http://someUrl/</url>
</view>
```

Via restrictTo you can specify users by username or groups or OUs (organizational units, i.e., folders in the user tree) via IDs to include this view only for users that match one of the restrictions. The name is the name to be displayed on the tab or in the module bar. The URL denotes the URL to be loaded.

Restrictions are specified in the following form

```
<restrictTo>
  <users>username1,username2</users>
  <groups>123,234</groups>
  <ous>876</ous>
</restrictTo>
```

For adminviews and objectinfo views you can further restrict the view to specific object types. This is done by adding a "types" tag which takes a comma separated list of fully qualified names of objects for which this view applies. For example the following restriction would restrict the (objectinfo) view to report objects within the teamspace.

```
  <types>net.datenwerke.rs.tsreportarea.client.tsreportarea.dto.
    ↳ TsDiskReportReferenceDto</types>
```

The following types are available for **objectinfo** views

[net.datenwerke.rs.tsreportarea.client.tsreportarea.dto.AbstractTsDiskNodeDto](#)

All Objects in a Teamspace.

[net.datenwerke.rs.tsreportarea.client.tsreportarea.dto.TsDiskFolderDto](#)

All folders in a Teamspace.

[net.datenwerke.rs.tsreportarea.client.tsreportarea.dto.TsDiskReportReferenceDto](#)

All reports and variants in a Teamspace.

[net.datenwerke.rs.scheduleasfile.client.scheduleasfile.dto.ExecutedReportFileReferenceDto](#)

All "exported reports" which were, for example, created by the scheduler.

The following types are available for **adminviews**

Objects in Report Management.Prefix: `net.datenwerke.rs.core.client.reportmanager.dto.reports.`

Type	Description
AbstractReportManagerNodeDto	All objects in the report management tree.
ReportDto	reports
ReportFolderDto	folders

Objects in User Management.Prefix `net.datenwerke.security.client.usermanager.dto.`

Type	Description
AbstractUserManagerNodeDto	All objects in the user management tree.
UserDto	users
GroupDto	groups
OrganisationalUnitDto	organisational units (folders)

Objects in the file server.Prefix `net.datenwerke.rs.fileserver.client.fileserver.dto.`

Type	Description
AbstractFileServerNodeDto	All objects in the file server.
FileServerFolderDto	folders
FileServerFileDto	files

Objects in Data Source ManagementPrefix `net.datenwerke.rs.core.client.datasourcemanager.dto.`

Type	Description
AbstractDataSourceManagerNodeDto	All objects in data source management.
DatasourceFolderDto	folders
DatasourceDefinitionDto	data sources

Objects in Dadget ManagementPrefix `net.datenwerke.rs.dashboard.client.dashboard.dto.`

Type	Description
AbstractDashboardManagerNodeDto	All objects in the dashboard tree
DashboardNodeDto	dashboards
DashboardFolderDto	folders

You can use replacements within the URL to generate dynamic URLs. The following replacements are available

`${username}` Is replaced by the current user's username.

`${type}` Is replaced by the class name of the corresponding object. This replacement is only available for `objectinfo` and `adminviews`.

`${id}` Is replaced by the ID of the corresponding object. This replacement is only available for `objectinfo` and `adminviews`.

`${reportId}` Report objects within a team space are always references. Thus, the replacement `${id}` maps to the id of the reference rather than to the id of the actual report. In order to use the actual report's id you can use the replacement `${reportId}`

ReportServer Specific URLs

Besides specifying a view via a URL ReportServer you can tell ReportServer to display the preview view of a report. For this, you need to define the URL as

```
rs:reportpreview://ID
```

where ID should be replaced by the id of the corresponding report or, for example, by the replacement `${reportId}` when defining this view for report objects in the TeamSpace.

Note that, as with any configuration file you need to run `config reload` on the terminal for changes to take effect. Furthermore you need to reload your browser to see effects as the configuration is loaded onto the client on login.

8.2 CommandResult - A Script's Result

We will now get back to ReportServer scripts and have a closer look at the object returned by a script. In theory, you can return any object from a script. For example the script

```
"Hello World"
```

returns an object of type `String`. In order to transport the result onto the client the terminal process wraps such a result in an object of type `CommandResult` (located in package `net.datenwerke.rs.terminal.service.terminal.obj`) which the client knows how to handle. If executed in the terminal the terminal will extract the string and display

```
reportserver$ exec hello.rs  
Hello World
```

This is done dynamically behind the scenes. But, you can also make this explicit and directly return a `CommandResult`. For this, you need to change the script to

```
import net.datenwerke.rs.terminal.service.terminal.obj.CommandResult  
new CommandResult("Hello World")
```

When executing this script the result is identical to before. However, making the `CommandResult` explicit will give us more control over how the client treats the result. In Chapter 3 we have already seen how to add hyperlinks and anchors to `CommandResults`. You can furthermore add simple lists, tables and strings to structure the output on the terminal. Consider the following script

```
import net.datenwerke.rs.terminal.service.terminal.obj.CommandResult

def result = new CommandResult()
result.setResultList(['Hello', 'World'])
result.setResultLine('-----')
result.setResultList(['Hello', 'World'])

return result
```

Executing this script produces the following output

```
reportserver$ exec hello.rs
Hello
World
-----
Hello
World
```

Besides lists and tables, you can also directly return HTML.

```
import net.datenwerke.rs.terminal.service.terminal.obj.CommandResult

def result = new CommandResult()
result.setResultHtml('<b>Hello</b> World')

return result
```

These techniques, however, are limited to format the results of a script when displayed on a terminal. The `CommandResult` object, on the other hand, is not limited to terminal formatting. A `CommandResult` object can contain one or more objects of type `CommandResultExtensions` which trigger certain responses on the client. For example, this allows you to display popup messages or execute arbitrary JavaScript code.

Displaying Messages

In order to display popup messages your script needs to add a `CommandResultExtension` of type `CreMessage` to the `CommandResult` object. Following is a simple example.

```
import net.datenwerke.rs.terminal.service.terminal.obj.*

def result = new CommandResult()

def msg = new CreMessage("Hello World")
result.addExtension(msg)

return result
```

You can further control the size of the window and also directly add HTML.

```
import net.datenwerke.rs.terminal.service.terminal.obj.*

def result = new CommandResult()

def msg = new CreMessage()
msg.setTitle("Hello")
msg.setWindowTitle("Hello")
msg.setWidth(400)
msg.setHeight(300)
msg.setHtml("<b>Hello World</b>")
result.addExtension(msg)

return result
```

Executing Custom JavaScript

The `CreJavaScript CommandResultObject` allows to specify custom JavaScript which is executed on the client.

```
import net.datenwerke.rs.terminal.service.terminal.obj.*

def result = new CommandResult()

def script = """
alert("Hello World");
"""

result.addExtension(new CreJavaScript(script))

return result
```

8.3 ClientExtensionService

So far we have seen how to customize the output within the terminal, how to display messages in popups or execute custom JavaScript. In this section we will look at the so-called `ClientExtensionService`, that can be accessed via the `GLOBALS` object. The **ClientExetnasionService** offers methods to entries to various toolbars and context menus. Each entry comes with a callback, that is, a `ReportServer` script that is executed when the specified entry is activated. Depending on where you added the entry your script is provided with additional information. For example, when adding an entry to the context menu in the report management view in the admin module then your script will get the id of the object in question as an argument.

One thing to keep in mind when using the `ClientExtensionService` is that all effects are only valid as long as the current page is not refreshed. In order to have the changes permanently you should thus add the script into the `onlogin.d` folder.

The `ClientExtensionService` currently offers the following methods.

<code>addStatusBarLabel()</code>	Allows to display info texts in the status bar.
<code>addMenuEntry()</code>	Allows to add entries to certain context menus.
<code>addToolBarEntry()</code>	Allows to add buttons to certain toolbars.
<code>addReportExportOutputFormat()</code>	Allows to create custom exporters. We discuss this in detail in Chapter 11.

Adding Information to the Status Bar

The first method `addStatusBarLabel` allows you to add simple info texts to the status bar. The concept is best explained by a little example.

```
def service = GLOBALS.services['clientExtensionService']

service.addStatusBarLabel("All is fine")
```

As you might have guessed, the first line obtains the `ClientExtensionService` from the `GLOBALS` object. All that is left to do is to set a status update. Besides just adding text you can also call

```
addStatusBarLabel("All is fine", "path to some icon", true)
```

where the second parameter should point to an icon and the third parameter controls whether the object is added to the left or to the right (default).

Adding Context Menu Entries

The `ClientExtensionService` allows you to add menu entries to the following context menus

Module	Description	Menu Name
Datasource Manager	The datasource manager within the admin module	<code>datasource:admin:tree:menu</code>
Report Manager	The report manager within the admin module	<code>reportmanager:admin:tree:menu</code>
File Server	The file server within the admin module	<code>filesserver:admin:tree:menu</code>
Dadget Library	The dadgetlibrary within the admin module	<code>usermanager:admin:tree:menu</code>
User Manager	The user manager within the admin module	<code>dashboard:admin:tree:menu</code>

To add an entry to a specific menu you need to access the menu by name (we give the menu names in the above table, for example, `usermanager:admin:tree:menu` corresponds to the context menu within the user manager tree).

The simplest way to add a menu entry is to simply call the method `addMenuEntry()` from the `ClientExtensionService`:

```
public void addMenuEntry(String menuName, String entryName, String scriptLocation, ↵
    ↵ String configArgument)
```

8. Extending the Client

The method takes the menu name, a name for the entry, a location of the script that is to be called when the entry is activated, and an argument given to the script. In the following we want to add a menu to the user tree. We call our script that generates the entry `adddisplayinfoentry.rs`.

```
def service = GLOBALS.services['clientExtensionService']

service.addMenuEntry("usermanager:admin:tree:menu", "display info", "fileserver/ ↗
↳ bin/extensions/menu/displayuserinfo.rs", "an argument")
```

The script must be executed, before the user tree is loaded for the first time.

If you execute the above script and navigate to the user manager in the administration module and right click on any item in the tree you will see the new entry

display info

If you activate the entry you will see an error message, since we haven't yet created a script at location

fileserver/bin/extensions/menu/displayuserinfo.rs

We are now going to create this file and use the above and display a simple message outputting the object's id.

```
import net.datenwerke.rs.terminal.service.terminal.obj.*

def result = new CommandResult()

def msg = new CreMessage("ID: " + context['id'] + ", args" + args)
result.addExtension(msg)

return result
```

The important part here is the **context** object which contains a field **id** corresponding to the id of the object clicked upon. Besides key **id** the context also contains

id	The object's id.
classname	The object's classname.
path	The object's path.

Display Conditions

Sometimes it might be inconvenient to add the menu entry to every object in the tree. That is, maybe we want to add an entry only to user objects, but not to groups or organizational units. To have full control over how the menu item is created you can directly create an object of type `AddMenuEntryExtension` located in package `net.datenwerke.rs.scripting.service.scripting.extensions`. To better control when the entry is displayed use `DisplayConditions` located in the same package.

```
import net.datenwerke.rs.scripting.service.scripting.extensions.*
```

```

def service = GLOBALS.services['clientExtensionService']

def entry = new AddMenuEntryExtension()
entry.setMenuName("usermanager:admin:tree:menu")
entry.setLabel("display info")
entry.setScriptLocation("fileserver/bin/extensions/menu/displayuserinfo.rs")

def cond = new DisplayCondition("classname", "net.datenwerke.security.client. ↗
    ↪ usermanager.dto.UserDto")
entry.addDisplayCondition(cond)

service.addMenuEntry(entry)

```

Note that the for menus you can currently only compare classnames. Also note that always the base class of the DTO is used, that is, instead of `UserDtoDec` you need to use `UserDto`.

Adding Toolbar Entries

Besides adding entries to context menus, you can add buttons to various toolbars including all toolbars within the various admin modules. The mechanism is similar to before. The following toolbars support the addition of custom buttons.

Module	Description	Menu Name
Datasource Manager	The datasource manager within the admin module	datasource:admin:view:toolbar
Report Manager	The report manager within the admin module	reportmanager:admin:tree:menu
File Server	The file server within the admin module	fileserver:admin:view:toolbar
Dadget Library	The dadgetlibrary within the admin module	usermanager:admin:view:toolbar
User Manager	The user manager within the admin module	dashboard:admin:view:toolbar

Similar to before you can either use helper methods within the `ClientExtensionService` such as

```

public void addToolbarEntry(String toolbarName, String entryName, String entryIcon ↗
    ↪ , String scriptLocation, String arguments){

```

or alternatively create an object of type `AddToolbarEntryExtension`, also located in package `net.datenwerke.rs.scripting.service.scripting.extensions`.

```

import net.datenwerke.rs.scripting.service.scripting.extensions.*

def service = GLOBALS.services['clientExtensionService']

def entry = new AddToolbarEntryExtension()
entry.setToolbarName("usermanager:admin:view:toolbar")
entry.setLabel("display info")

```

8. Extending the Client

```
entry.setIcon("path/to/icon")
entry.setScriptLocation("fileserver/bin/extensions/menu/displayuserinfo.rs")

def cond = new DisplayCondition("classname", "net.datenwerke.security.client. ↗
    ↘ usermanager.dto.decorator.UserDtoDec")
entry.addDisplayCondition(cond)

service.addToolBarEntry(entry)
```

Note that with toolbar buttons you have more control over when buttons are to be displayed, as you can specify the exact type, that is, `UserDtoDec` instead of `UserDto`. This, for example, allows you to add a custom button only to dynamic lists, but not to jasper reports.

Future Additions

The possibilities offered by the `ClientExtensionService` are still rudimentary. We plan to extend these in future versions and are keen to hear your thoughts on what you would like to be able to do and what you are currently missing.

Part II

Examples

Adding Additional Data Sources

By default ReportServer is shipped with support only for the most common database systems, although it can interact with virtually every database that offers a JDBC compliant driver. In this chapter we will show how to develop a groovy script that adds support for the Firebird database (www.firebirdsql.org) to ReportServer.

Although SQL is well standardized and the JDBC specification defines a vendor independent interface to the actual database driver, simply adding the database driver to the classpath does not suffice. ReportServer tries to use mostly ANSI-SQL whenever possible, but in some situations not using a vendor-specific extension bears a high performance penalty. One of these situations is the limit/offset-mechanism, that allows the application to request only a certain chunk of the resultset. Most databases offer some solution to this problem, but there is no standard approach. To manage these differences in different SQL dialects ReportServer uses a DatabaseHelper class for each supported SQL dialect.

To add support for a new database, what we need to do, is to implement a **DatabaseHelper** for the database and register it with ReportServer.

Lets start by looking at the DatabaseHelper for the H2 database engine:

```
public class H2 extends DatabaseHelper {

    public static final String DB_NAME = "H2";
    public static final String DB_DRIVER = "org.h2.Driver";
    public static final String DB_DESCRIPTOR = "DBHelper_H2";

    @Override
    public String getDescriptor() {
        return DB_DESCRIPTOR;
    }

    @Override
    public String getDriver() {
        return DB_DRIVER;
    }
}
```

```
@Override
public String getName() {
    return DB_NAME;
}
}
```

The three methods `getDescriptor`, `getName` and `getDriver` are the minimum each `DatabaseHelper` has to implement.

<code>getName()</code>	The text the user is shown on the front-end when selecting the database type.
<code>getDriver()</code>	The name of the JDBC driver class.
<code>getDescriptor()</code>	The key used internally to map data sources to <code>DatabaseHelpers</code>

To adapt this to the Firebird database, we simply change the values of the three constants

```
class Firebird extends DatabaseHelper {

    public static final String DB_NAME = "Firebird";
    public static final String DB_DRIVER = "org.firebirdsql.jdbc.FBDriver";
    public static final String DB_DESCRIPTOR = "DBHelper_Firebird";

    @Override
    public String getDescriptor() {
        return DB_DESCRIPTOR;
    }

    @Override
    public String getDriver() {
        return DB_DRIVER;
    }

    @Override
    public String getName() {
        return DB_NAME;
    }
}
```

If we added this class to `ReportServer`, we would already be able to execute Birt and Jasper Reports where the query is simply passed through, but using a dynamic list with a Firebird data source would still fail.

There are basically three more changes to be made to fully support Firebird from within `ReportServer`.

To test a database connection `ReportServer` tries to execute a dummy query. Our default implementation of this is `SELECT * FROM DUAL`, but this does not work with Firebird. So we override the `createDummyQuery` method of our `DatabaseHelper` and provide an alternative implementation:

```
@Override
public String createDummyQuery() {
    return 'select 1 dummy from rdb$database';
}
```

```
}

```

The other two enhancements concern the earlier mentioned matter of limit and offset. ReportServers default implementation creates queries with `LIMIT` and `OFFSET` keywords at the end, so we need to provide a different implementation for Firebird.

```
@Override
public LimitQuery getNewLimitQuery(Query nestedQuery, QueryBuilder queryBuilder) ↵
    ↵ {
    return new LimitQuery(nestedQuery, queryBuilder){
        @Override
        public void appendToBuffer(StringBuffer buf) {
            buf.append("SELECT FIRST ");
            buf.append(queryBuilder.getLimit());
            buf.append(" * FROM (");
            nestedQuery.appendToBuffer(buf);
            buf.append(") limitQry");
        }
    }
}

```

```
@Override
public OffsetQuery getNewOffsetQuery(Query nestedQuery, QueryBuilder queryBuilder ↵
    ↵ , ColumnNamingService columnNamingService) {
    return new OffsetQuery(nestedQuery, queryBuilder, columnNamingService){
        @Override
        public void appendToBuffer(StringBuffer buf) {
            buf.append("SELECT FIRST ");
            buf.append(queryBuilder.getLimit());
            buf.append(" SKIP ");
            buf.append(queryBuilder.getOffset());
            buf.append(" * FROM (");
            nestedQuery.appendToBuffer(buf);
            buf.append(") limitQry");
        }
    }
}

```

The way ReportServer constructs dynamic queries is by basically wrapping multiple layers of SQL around each other. The `LimitQuery` follows the same approach. It has access to a `nestedQuery` and is asked to write itself into the supplied buffer, wrapping this nested query.

The final step is to register the newly created `DatabaseHelper` with `ReportServer`. This is done by implementing the `net.datenwerke.rs.base.service.dbhelper.hooks.DatabaseHelperProviderHook`. Following is the implementation needed to attach our custom Firebird database helper class

```
def HOOK_NAME = "DATASOURCE_HELPER_FIREBIRD"
def callback = [
    provideDatabaseHelpers : {
        return Collections.singletonList(new Firebird());
    }
}

```

9. Adding Additional Data Sources

```
] as DatabaseHelperProviderHook;
GLOBALS.services.callbackRegistry.attachHook(HOOK_NAME, DatabaseHelperProviderHook ↵
↳ .class, callback)
```

You will find the complete script (`AddFirebirdSupport.groovy`) in the appendix as well as in the support portal for download.

Note that, in order for this to work you of course need to place the Firebird JDBC driver into your classpath. Download Jaybird from <http://www.firebirdsql.org/en/jdbc-driver/> and put the files `jaybird-2.2.3.jar` and `lib/connector-api-1.5.jar` into the `WEB-INF/lib` subdirectory of your ReportServer installation. You might have to restart ReportServer afterwards.

Beware, that after restarting ReportServer hooks attached from the terminal will no longer be present. To automatically attach a hook on start-up put the script in the `bin/onstartup.d` directory in the fileserver.

Integrating ReportServer with an Active Directory using LDAP

In the following we will outline the necessary steps to connect ReportServer to an Active Directory using LDAP. As there are many valid ways to organize a company's directory (may it be AD or another vendors product) ReportServer does not come with a predefined LDAP connector. This on one hand means, that the configuration might seem rather complex, but on the other hand it provides you with a maximum of flexibility.

To connect ReportServer to the Active Directory Service we will use ReportServer's integrated groovy script engine. The whole process can be divided into two, mostly separate parts. One part is the synchronization of the user objects: we will automatically copy Users, Organizational Units and Groups from the directory to ReportServer and keep them updated. The second part is a mechanism that authenticates the previously imported users when they log into ReportServer.

10.1 Synchronizing Users

The complete example is available in the appendix (`ldapimport.groovy`) and also for download in the support portal.

As for the length of the script we will not go through it line by line, but rather outline the general process and highlight some important spots that are likely starting-points for customization.

We will start with a general overview of the synchronization process. Besides the account data used to log-in (bind) to the Active Directory Server the script requires two additional configuration values. The first is the `ldapBase` value, which specifies the common root node of all the directory entries that should be imported. This could simply be your organisation's User-root, as in the example or just a subtree, if you don't want to import all directory users into ReportServer. You can further tweak which user objects get imported by modifying the `ldapFilter` property. Keeping the default value will import all users, groups and organizational units as present in your directory. If you decide to modify this, keep in mind, that importing a user does not grant him any privileges. On the other hand a user not present in ReportServer will not even be available as a recipient for scheduled reports (that is, scheduled reports sent by email). So generally there is no reason to not just import all your users.

The second configuration is the target node in ReportServer's user tree. This is the node below which all imported objects will be placed. The script as published above will create an organizational unit "external" to which it will add all ldap objects. We suggest to keep imported objects separate from native ReportServer user tree objects, as this makes the synchronization much easier. The script also write protects all imported objects, to ensure that no objects are accidentally added to the automatically synchronized subtree.

After all configuration data is prepared the script starts by creating a map of all objects currently present below the targetNode. This map will later be used to make sure that objects that already existed are not recreated. This is important as creating the objects anew (and deleting the old one) will assign a new ID to the objects and we would have to update the id, wherever it was referenced. It's much more reliable to just reuse the existing object.

Afterwards the script connects to the directory and issues a search for all objects below the ldapBase node that match the ldapFilter. The search results are sorted by their path, so we don't have to take care of creating objects in the right order (parents before their children). If you change the filter expression you will have to add some code here that will find/create a suitable container for the node we are about to import.

In the next step the script iterates over the search results and creates the appropriate ReportServer object for each result. Execution is handed over to a create method for the specific object type. These methods all follow the same structure: they first either retrieve the node from the map created in the first step, or create a new node. Then the node is placed at the correct position in the target tree. Finally the search result's properties are copied over to the ReportServer object.

When the object is created its write-protection flag is set and the guid and origin properties are modified to indicate that the object was retrieved from the directory. The guid set here was used in the first step to uniquely identify and match existing nodes to the ones retrieved from the directory.

After all objects are created in the target structure post processing is performed that correctly sets the members of all groups. The process is to iterate over all objects found in the directory and for each group first clear the list of members and then retrieve the members from the map created in the previous step.

As a final step all users no longer present in the directory are removed from the target subtree.

10.2 Authenticating Users

There are many different ways to check a user's credentials, like using Client Certificates, authenticating with Kerberos or using some Single-Sign-On mechanism with e.g. spnego or CAS. We will present a very simple script that authenticates a user who provided a username/password-combination by trying to use this information to bind against the directory.

The complete script (`hook1dapppam.groovy`) is also in the appendix as well as available for download in the support portal.

The script consist of three separate parts: Two classes and a short script snippet, that registers an instance of these classes with ReportServer.

Let us first look at the LdapPAM class. PAM is short for pluggable authenticator module, authenticator modules in ReportServer are made up out of two parts: a client-side part, that handles the interaction with a user and a server-side part, that checks the credentials the client module retrieved from the user.

The implemented interface ReportServerPAM is shared by all of ReportServer authenticator mechanisms. It requires the implementation of two methods, the first is getClientModule, which provides the appropriate client component. Our LdapPAM reuses the UserPasswordClientPAM, that makes the user enter a combination of username and password and transfers the cleartext of both to the server. You should ensure SSL/TLS is enabled when using this module.

The second method authenticate performs the actual authentication. It is called with a set of tokens as collected by the specified client module and returns an object of type AuthenticationResult. The AuthenticationResult has three components, a boolean value indicating if authentication was successful, the resolved user, if any, and a second boolean value that indicates if the result is authoritative. This third value is only relevant with negative results - in this case it controls whether other modules (if any are activated) are queried or if the request is denied immediately.

The actual authentication is handed off to an instance of the LdapAuthenticator class. The code is basically the same as in the import script. A connection to the directory is established using the supplied password, and the information stored during import in the users origin field.

Depending on the outcome of this connection attempt an AuthenticationResult object is created and returned. In case of a negative authentication attempt the authoritative property is set based on the users origin property.

Lastly the script uses ReportServer's callback registry to hook into the authentication process.

Putting it all together

Now that you should have a basic understanding how the two scripts work, let's give it a try. Download the two files ldapimport.groovy and hookldappam.groovy to your computer.

Open the file with a text editor and change the following lines to match your configuration:

```
lul.setProviderUrl("ldap://directory.example.com:389");
lul.setSecurityPrincipal("CN=ldaptest,CN=Users,DC=directory,DC=example,DC=com");
lul.setSecurityCredentials("ldaptest");
```

```
lul.setLdapBase("OU=EXAMPLE,DC=directory,DC=example,DC=com");
```

The provider URL is the URL of your directory server, security principal and credentials are used to authenticate with the LDAP server. The ldapBase property specifies the parent nodes in your directory, where the import starts.

After you modified the script, open ReportServer in your browser and go to the fileservers section in the admin module.

Upload both files to a location below the bin directory. Open the terminal by pressing **CTRL+ALT+T**. Change your current directory to the location where you put the script files using the cd command

and execute the import script.

```
cd /fileserver/bin
exec -c ldapimport.groovy
```

The `-c` (commit) flag is important because otherwise changes to the data model made by the script would be reverted after execution.

If you now change over to the user manager section you can view the results of the import. Also some statistics were written to the server's logfile/console.

After you have verified that the import was successful, it's time to load the authenticator module. Again, open the terminal by pressing `Ctrl+Alt+T`, `cd` to the script's location and execute it.

```
cd /fileserver/bin
exec hookldappam.groovy
```

Now you are all set to give it a try: Log out, or better yet use a second browser in case something is wrong and try to log in again.

10.3 Possible Improvements

Autoload authenticator module on startup One important thing, to keep in mind is that hooks attached by a script will be lost when you restart ReportServer. To make sure the `ldap-PamHook` gets automatically reattached place the script in the `onstartup.d/` directory. Scripts in this directory automatically get executed on start-up, so your authenticator module is always available.

Using the scheduler to refresh users periodically To keep ReportServer's user database in sync with your company directory you would probably like to run the script automatically from time to time. To do this, you can use the `scheduleScript` terminal command.

Automatically fetch/refresh a user's corresponding user object on login Additionally to periodic updates you might want to refresh a user's object whenever s/he tries to log in. This can easily be achieved by modifying the `hookldappam` script and adding the required functionality.

Additional Report Executors

In this chapter we go through the necessary steps to add custom additional report exporters, for example to export dynamic lists into a custom text-based format. When talking about adding custom exporting options we need to distinguish between two things. On the one hand we need the server side code to actually implement the exporting logic. This already allows you to use the exporter, for example, when executing the report via URL. If you also want to add the option to the UI we need to take additional steps. In this chapter we will discuss which steps are necessary for both the server side integration and the client side integration.

11.1 Background

Reporting engines are structured similarly and each reporting engine comes with one or more so called OutputGenerators. As usual you can add additional generators via implementing the correct Hook interface. Following is a list of reporting engines and the corresponding Hook interface needed to be implemented in order to add a custom output generator for the particular engine.

Reporting Engine:	Dynamic Lists
Hook Interface:	<code>net.datenwerke.rs.base.service.reportengines.table.hooks.TableOutputGeneratorProviderHook</code>
Output Generator Interface:	<code>net.datenwerke.rs.base.service.reportengines.table.output.generator.TableOutputGenerator</code>
Reporting Engine:	JasperReports
Hook Interface:	<code>net.datenwerke.rs.base.service.reportengines.jasper.hooks.JasperOutputGeneratorProviderHook</code>
Output Generator Interface:	<code>net.datenwerke.rs.base.service.reportengines.jasper.output.generator.JasperOutputGenerator</code>

11. Additional Report Executors

Reporting Engine:	Birt
Hook Interface:	<code>net.datenwerke.rs.birt.service.reportengine.hooks.BirtOutputGeneratorProviderHook</code>
Output Generator Interface:	<code>net.datenwerke.rs.birt.service.reportengine.output.generator.BirtOutputGenerator</code>
Reporting Engine:	Crystal
Hook Interface:	<code>net.datenwerke.rs.crystal.service.crystal.reportengine.hooks.CrystalOutputGeneratorProviderHook</code>
Output Generator Interface:	<code>net.datenwerke.rs.crystal.service.crystal.reportengine.output.generator.CrystalOutputGenerator</code>
Reporting Engine:	Script Reports
Hook Interface:	<code>net.datenwerke.rs.scriptreport.service.scriptreport.hooks.ScriptReportOutputGeneratorProvider</code>
Output Generator Interface:	<code>net.datenwerke.rs.scriptreport.service.scriptreport.generator.ScriptReportOutputGenerator</code>
Reporting Engine:	Saiku
Hook Interface:	<code>net.datenwerke.rs.saiku.service.saiku.reportengine.hooks.SaikuOutputGeneratorProviderHook</code>
Output Generator Interface:	<code>net.datenwerke.rs.saiku.service.saiku.reportengine.output.generator.SaikuOutputGenerator</code>
Reporting Engine:	JXLS
Hook Interface:	<code>net.datenwerke.rs.jxlsreport.service.jxlsreport.reportengine.hooks.JxlsOutputGeneratorProviderHook</code>
Output Generator Interface:	<code>net.datenwerke.rs.jxlsreport.service.jxlsreport.reportengine.output.generator.JxlsOutputGenerator</code>
Reporting Engine:	GridEditor
Hook Interface:	<code>net.datenwerke.rs.grideditor.service.grideditor.reportengine.hooks.GridEditorOutputGeneratorProviderHook</code>
Output Generator Interface:	<code>net.datenwerke.rs.grideditor.service.grideditor.reportengine.output.generator.GridEditorOutputGenerator</code>

All output generators extend the interface `net.datenwerke.rs.core.service.reportmanager.output.ReportOutputGenerator` which specifies defines the following methods

```
String[] getFormats();
```

```
boolean isCatchAll();
```

```
CompiledReport getFormatInfo();
```

The first method (`getFormats`) returns an array of string constants that specify the formats this output generator recognizes. The `catchAll` method allows to implement a fall back mechanism, that is to implement an output generator that is called in case no other output generator recognizes the format specified by the user. The last method `getFormatInfo` should return an object of type `net.datenwerke.rs.core.service.reportmanager.engine.CompiledReport`. A compiled report is the result of an output generator, that is, it is for example a PDF document containing the finished report. The `CompiledReport` object contains, besides the actual report, information about the format such as the file's mime type, extension etc. The `getFormatInfo()` method should return an empty `CompiledReport` object, that is, the object does not contain any data but should specify the format. Let us look at the `CompiledReport` object in more detail. It is an interface specifying the following methods:

```
Object getReport();
```

```
String getMimeType();
```

```
String getFileExtension();
```

```
boolean hasData();
```

```
boolean isStringReport();
```

A `CompiledReport` is thus a simple bean containing information. `GetReport` should return the actual report (e.g., PDF document), `getMimeType` should return a mime type specifying the mime type of the report. `getFileExtension` returns a proper file extension (e.g., pdf in case the report is of the PDF format). `HasData` should return true if the report contains any data, that is, if the underlying datasource provided data for the report. Finally, `isStringReport` specifies whether the report is of a string format (such as HTML) or of a binary format (such as PDF).

For convenience we have a default implementation of `CompiledReport` called `CompiledReportImpl` (in the same package) which takes all the data as a constructor argument. Additionally, we have `CompiledReport` objects for many standard file formats. These can be found in the package

[net.datenwerke.rs.core.service.reportmanager.engine.basereports](#)

The following objects are available

- `CompiledCsvReport`
- `CompiledDocReport`
- `CompiledDocxReport`
- `CompiledXHtmlReport`
- `CompiledJsonReport`
- `CompiledPdfReport`

11. Additional Report Executors

- CompiledTxtReport
- CompiledXlsReport
- CompiledXlsxReport
- CompiledXmlReport

With this in mind, we can now add a simple output generator for a dynamic list (note that the corresponding object in ReportServer is called TableReport). The output generator will create a simple HTML page that displays the number of data rows in the result. For this purpose let us look at the TableOutputGenerator interface.

```
void initialize(OutputStream os, TableDefinition td, boolean withSubtotals, ↵
    ↳ TableReport report, TableReport originalReport, CellFormatter[] ↵
    ↳ cellFormatters, ParameterSet parameters, User user, ReportExecutionConfig ↵
    ↳ ... configs) throws IOException;

void nextRow() throws IOException;

void addField(Object field, CellFormatter cellFormatter) throws IOException;

void close() throws IOException;

CompiledReport getTableObject();

void addGroupRow(int[] subtotalIndices, Object[] subtotals, int[] ↵
    ↳ subtotalGroupFieldIndices, Object[] subtotalGroupFieldValues, int rowSize, ↵
    ↳ CellFormatter[] cellFormatters) throws IOException;
```

The initialize method is called before the first data entry is processed. NextRow informs the generator that the current row is complete and that a new row is about to begin. AddField adds a new data cell and close is called upon completion. One thing to keep in mind is that the initialize method can be called in two modes. Either with an OutputStream or without one. In the first case the actual data is to be streamed directly into the output stream. Otherwise the report is to be generated in memory. Usually data is directly streamed and you do not need to worry about in memory generation. GetTableObject returns a CompiledReport object (without any actual data, in case of streaming) and addGroupRow is used for reports that have subtotals enabled. We will ignore this possibility here.

In order to implement our simple row counter, all we need to do is to keep track of the calls to nextRow().

```
import net.datenwerke.rs.base.service.reportengines.table.output.generator.TableOutputGenerator
import net.datenwerke.rs.base.service.reportengines.table.hooks.TableOutputGeneratorProviderHook
import net.datenwerke.rs.base.service.reportengines.table.hooks.adapter. ↵
    ↳ TableOutputGeneratorProviderHookAdapter
import net.datenwerke.rs.core.service.reportmanager.engine.basereports.CompiledXHtmlReport

import java.io.OutputStream

import net.datenwerke.rs.base.service.reportengines.table.entities.Column.CellFormatter
import net.datenwerke.rs.base.service.reportengines.table.entities.TableReport
```

```

import net.datenwerke.rs.base.service.reportengines.table.output.object.TableDefinition
import net.datenwerke.rs.core.service.reportmanager.engine.CompiledReport
import net.datenwerke.rs.core.service.reportmanager.engine.config.ReportExecutionConfig
import net.datenwerke.rs.core.service.reportmanager.output.ReportOutputGenerator
import net.datenwerke.security.service.usermanager.entities.User
import net.datenwerke.rs.core.service.reportmanager.parameters.ParameterSet

def HOOK_NAME = "MY_ADDITIONAL_GENERATOR"

/* specify the generator */
class MyGenerator implements TableOutputGenerator {
    def writer = null
    int rows = 0

    void initialize(OutputStream os, TableDefinition td, boolean withSubtotals, TableReport report, ↵
        ↵ TableReport originalReport, CellFormatter[] cellFormatters, ParameterSet parameters, User ↵
        ↵ user, ReportExecutionConfig... configs ){
        writer = new PrintWriter(new BufferedWriter(new OutputStreamWriter(os)));
        writer.append("<?xml version=\"1.0\" encoding=\"ISO-8859-1\" ?>" +
            "<html xmlns=\"http://www.w3.org/1999/xhtml\">" +
            "<head></head>" +
            "<body><b>Number of rows:</b>");
    }

    void nextRow(){
        rows++;
    }

    void close() {
        writer.append(" ").append((rows+1) as String).append("</body></html>");
        writer.close();
    }

    boolean supportsStreaming(){
        return true;
    }

    void addField( Object field, CellFormatter cellFormatter ){

    CompiledXHtmlReport getTableObject() {
        return new CompiledXHtmlReport(null);
    }

    void addGroupRow (int[] subtotalIndices, Object[] subtotals, int[] subtotalGroupFieldIndices, Object ↵
        ↵ [] subtotalGroupFieldValues, int rowSize, CellFormatter[] cellFormatters ){ }

    String[] getFormats() {
        String[] formats = ['MY_CUSTOM_FORMAT']
        return formats
    }

    boolean isCatchAll() { return false; }

    CompiledXHtmlReport getFormatInfo() {
        return new CompiledXHtmlReport(null);
    }
}

/* specify provider */
def provider = [
    provideGenerators : { ->
        return [new MyGenerator()]
    }
}

```

11. Additional Report Executors

```
] as TableOutputGeneratorProviderHookAdapter
```

```
/* plugin hook */
GLOBALS.services.callbackRegistry.attachHook(HOOK_NAME, TableOutputGeneratorProviderHook.
class, provider)
```

There are few things to explain. In order to make the new output generator available, we need to install our new generator object in the `TableOutputGeneratorProviderHook` which returns a list of generator objects. Note that we should return a new instance upon every call to method "provideGenerators". Otherwise one would need to ensure that the output generator is implemented in a thread safe manner.

If we execute our script (assume it is called `customDynamicListExporter.groovy`) then you should see the following terminal response.

```
reportserver$ exec generator.groovy
MY_ADDITIONAL_GENERATOR
```

You can now use your custom exporter when exporting dynamic lists, for example, if you export the dynamic list via URL:

```
http://.../reportserver/reportexport?key=customer&format=MY\_CUSTOM\_FORMAT
```

Note that the output generator will only be available as long as `ReportServer` is running. If you want this output generator added permanently you should add the script to the list of startup scripts (the `startup.d` folder, see Section 7.2).

11.2 Adding the Output Generator to the Client

So far we have added the new output generator, but you can only use it when exporting reports via the URL, that is, normal users would not know that the output generator exists since it doesn't show in the user interface. To change this we will use the `ClientExtensionService` (see Section 8.3). Following is the script needed to add the exporter as an option to the client. The `ClientExtensionService` offers a method "addReportExportOutputFormat" which we need to supply with an instance of a report object, a string to be displayed, the actual format, and an optional path to an icon. The object instance in our case is `TableReportDtoDec`. Remember that each server object has a corresponding client object called `ServerObjectDto`. The code of most of these objects is generated automatically during the compile process and thus, in order to manually add code most objects come with a corresponding decorator. You will always find the corresponding decorator in the sub-package decorator and by convention it is called `ServerObjectDtoDec`, thus, in our case we deal with `TableReportDtoDec`.

```
import net.datenwerke.rs.base.client.reportengines.table.dto.decorator. ↵
    ↵ TableReportDtoDec

/* obtain ClientExtensionService */
def ces = GLOBALS.services['clientExtensionService']

/* register format */
ces.addReportExportOutputFormat new TableReportDtoDec(), "My Format", " ↵
    ↵ MY_CUSTOM_FORMAT", ""
```

""

Again, remember that this script needs to be run after a user has logged in and should thus be placed in the `onlogin.d` directory.

Send To

In this chapter we explain how to add custom “send to targets” to the *Send to...* menu within the report executor. These can be used to, for example, upload a report to a web service. To add a custom target we need to implement `net.datenwerke.rs.core.service.sendto.hooks.SendToTargetProviderHook` which consists of three methods: `consumes`, `getId`, and `sendTo`. The `getId` method is used to define a unique identifier to identify the send to target. The `consumes` method takes as input a report object and allows to specify a target configuration. Finally, the `sendTo` method is called to execute the action. The basic outline to define a target is thus the following code snippet

```
import net.datenwerke.rs.core.service.sendto.hooks.SendToTargetProviderHook
import net.datenwerke.rs.core.service.sendto.hooks.adapter. ↵
    ↳ SendToTargetProviderHookAdapter
import net.datenwerke.rs.core.client.sendto.SendToClientConfig

def HOOK_NAME = "MY_SEND_TO"

def callback = [
  consumes : { report ->
    def config = new SendToClientConfig();
    config.setTitle("Custom Send To");
    config.setIcon("wrench");
    return config;
  },
  getId : { ->
    return "aUniqueId"
  },
  sendTo : { report, values, execConfig ->
    // perform send to action
  }
] as SendToTargetProviderHookAdapter

GLOBALS.services.callbackRegistry.attachHook(HOOK_NAME, SendToTargetProviderHook. ↵
    ↳ class, callback)
```

The `consumes` method takes as input the current report object and returns an object of type

12. Send To

`SendToClientConfig` (or null, if for this report the target should not be active). In its simplest form the `SendToClientConfig` only takes a title and possibly an icon (any font-awesome icon identifier) which is used to populate the send-to menu on the client. If the user selects the menu item the `sendTo` method of the above hook is called. The `sendTo` method takes as input

<code>report</code>	The report object with its current configuration.
<code>values</code>	In case a form configuration is specified (we'll cover forms shortly) the values object is a map containing the selected values.
<code>execConfig</code>	Contains the execution config which should be passed on in case the report is executed.

An important point to make is that the report object is not necessarily as the stored object in the database but is configured as it was currently configured on the client side. This in particular means that the ID field of the report object is not set. In order to obtain the id you can use the `getOldTransientId()` method. Note that this is not the case for the report provided to the `consumes` method.

Output Format

By default the send to target does directly call the script when the user selects the option. You can specify that the user needs to configure an output format. For this call `config. ↵ ↵ setSelectFormat(true)` when specifying the `SendToClientConfig` object. Then, when the user selects the send-to target he or she will first be asked to specify an output format. In this case you can make your life easier when implementing the hook and override the method

```
public String sendTo(CompiledReport compiledReport, Report report,
    String format, HashMap<String, String> values,
    ReportExecutionConfig... executionConfig);
```

Here, as first parameter you are given the executed report (`compiledReport`). In this case we do not need to implement the other `sendTo` method, and an implementation could look like the following:

```
import net.datenwerke.rs.core.service.sendto.hooks.SendToTargetProviderHook
import net.datenwerke.rs.core.service.sendto.hooks.adapter. ↵ ↵
    SendToTargetProviderHookAdapter
import net.datenwerke.rs.core.client.sendto.SendToClientConfig

def HOOK_NAME = "MY_SEND_TO"

def callback = [
    consumes : { report ->
        def config = new SendToClientConfig();
        config.setTitle("Custom Send To");
        config.config.setSelectFormat(true);
        return config;
    },
    getId : { ->
        return "aUniqueId"
    },
    sendTo : { compiledReport, report, format, values, execConfig ->
        // perform send to action
```

```

}

] as SendToTargetProviderHookAdapter

GLOBALS.services.callbackRegistry.attachHook(HOOK_NAME, SendToTargetProviderHook. ↵
↳ class, callback)

```

Form Configuration

In addition to (or in place of) having the user select an output format for the report you can specify additional form fields. That is, you can display a simple form when the send-to menu item is selected and then have the data from the form available when executing the action. This is what the parameter `values` is for. It contains a map of the form-data specified by the user. In order to configure a form you can set the "form" property of the `SendToClientConfig`:

```

def callback = [
  consumes : { report ->
    def config = new SendToClientConfig();
    config.setTitle("Custom Send To");
    config.setForm(""); // the form configuration via json
    return config;
  },
  getId : { ->
    return "aUniqueId"
  },
  sendTo : { report, values, execConfig ->
    // perform send to action
  }
]

```

```

] as SendToTargetProviderHookAdapter

```

The form is defined via JSON (<http://www.json.org/>). The basic outline is as follows, where "form" would take the actual form configuration. The properties `width` and `height` define the width and height of the popup window that contains the form.

```

{
  "width": 400,
  "height": 200,
  "form" : {
    // form configuration
  }
}

```

The form configuration itself consists of a definition of fields.

```

"form" : {
  "fields": [{
    // first field
  }, {
    // second field
  }]
}

```

Scheduling

By default any send-to target is also available as a scheduler target. You can prevent this by implementing the method `supportsScheduling`:

```
def callback = [
  consumes : { report ->
    def config = new SendToClientConfig();
    config.setTitle("Custom Send To");
    return config;
  },
  getId : { ->
    return "aUniqueId"
  },
  sendTo : { report, values, execConfig ->
    // perform send to action
  },
  supportsScheduling: { -> return false }
] as SendToTargetProviderHookAdapter
```

If you have scheduling enabled, then by default a scheduling execution is forwarded to the `sendTo` method of your hook. You can however further control the scheduling execution by additionally overriding the method `scheduledSendTo`.

```
def callback = [
  consumes : { report ->
    def config = new SendToClientConfig();
    config.setTitle("Custom Send To");
    return config;
  },
  getId : { ->
    return "aUniqueId"
  },
  sendTo : { report, values, execConfig ->
    // perform send to action
  },
  scheduledSendTo : {compiledReport, report, reportJob, format, values ->
    // perform action
  },
  supportsScheduling: { -> return true }
] as SendToTargetProviderHookAdapter
```

Similarly, to the `sendTo` method you have access to the report object and the configured values. However, in addition you can access the `compiledReport` (the scheduler executed the report according to the instructions and the first parameter contains the result) as well as to the scheduler job definition.

Complete Example

The following is a complete example that reimplements sending a report via email.

12. Send To

```
import net.datenwerke.rs.core.service.sendto.hooks.SendToTargetProviderHook
import net.datenwerke.rs.core.service.sendto.hooks.adapter.SendToTargetProviderHookAdapter
import net.datenwerke.rs.core.client.sendto.SendToClientConfig

import net.datenwerke.rs.core.service.mail.MailService
import net.datenwerke.rs.core.service.reportmanager.ReportService
import net.datenwerke.rs.core.service.reportmanager.ReportExecutorService
import net.datenwerke.rs.core.service.mail.SimpleAttachement

def HOOK_NAME = "MY_SEND_TO"

reportService = GLOBALS.getInstance(ReportService.class)
reportExec = GLOBALS.getInstance(ReportExecutorService.class)
mailService = GLOBALS.getInstance(MailService.class)

def callback = [
  consumes : { report ->
    def config = new SendToClientConfig();
    config.setTitle("Send via Custom Mail");
    config.setForm("""
{
  "width": 400,
  "height": 150,
  "form" : {
    "labelAlign": "top",
    "fields": [{
      "id": "email",
      "type": "string",
      "label": "Email Address",
      "value": "name@example.com"
    }]
  }
}
""")
    return config;
  },
  getId : { ->
    return "someUniqueId"
  },
  sendTo : { report, values, execConfig ->
    def pdf = reportExec.execute(report, "PDF", execConfig)

    // prepare for sending mail
    def mail = mailService.newSimpleMail()
    mail.setSubject("The Report")
    mail.setToRecipients(values.get("email"))
    mail.setFrom("from@reportserver.net")

    def attachement = new SimpleAttachement(pdf.getReport(), pdf.getMimeType(), "filename.pdf")
    mail.setContent("Some Message", attachement)

    // send mail
    mailService.sendMail(mail)

    return "Send the report via mail. Config " + values
  }
] as SendToTargetProviderHookAdapter

GLOBALS.services.callbackRegistry.attachHook(HOOK_NAME, SendToTargetProviderHook.class, callback)
```

AddFirebirdSupport.groovy

```
1 package databasehelper;
2
3 import net.datenwerke.rs.scripting.service.scripting.scriptservices.GlobalsWrapper;
4 import net.datenwerke.rs.base.service.dbhelper.DatabaseHelper
5 import net.datenwerke.rs.base.service.dbhelper.hooks.DatabaseHelperProviderHook
6 import net.datenwerke.rs.base.service.dbhelper.queries.LimitQuery
7 import net.datenwerke.rs.base.service.dbhelper.queries.OffsetQuery
8 import net.datenwerke.rs.base.service.dbhelper.queries.Query
9 import net.datenwerke.rs.base.service.dbhelper.querybuilder.ColumnNamingService
10 import net.datenwerke.rs.base.service.dbhelper.querybuilder.QueryBuilder
11
12
13
14 class Firebird extends DatabaseHelper {
15
16     public static final String DB_NAME = "Firebird";
17     public static final String DB_DRIVER = "org.firebirdsql.jdbc.FBDriver";
18     public static final String DB_DESCRIPTOR = "DBHelper_Firebird";
19
20     @Override
21     public String getDescriptor() {
22         return DB_DESCRIPTOR;
23     }
24
25     @Override
26     public String getDriver() {
27         return DB_DRIVER;
28     }
29
30     @Override
31     public String getName() {
32         return DB_NAME;
33     }
34
35     @Override
36     public String createDummyQuery() {
37         return 'select 1 dummy from rdb$database';
38     }
39
40     @Override
41     public LimitQuery getNewLimitQuery(Query nestedQuery, QueryBuilder queryBuilder) {
42         return new LimitQuery(nestedQuery, queryBuilder){
43             @Override
44             public void appendToBuffer(StringBuffer buf) {
45                 buf.append("SELECT FIRST ");
```

A. AddFirebirdSupport.groovy

```
46     buf.append(queryBuilder.getLimit());
47     buf.append(" * FROM (");
48     nestedQuery.appendToBuffer(buf);
49     buf.append(") limitQry");
50 }
51 }
52 }
53
54 @Override
55 public OffsetQuery getNewOffsetQuery(Query nestedQuery, QueryBuilder queryBuilder, ColumnNamingService ↵
    ↵ columnNamingService) {
56     return new OffsetQuery(nestedQuery, queryBuilder, columnNamingService){
57         @Override
58         public void appendToBuffer(StringBuffer buf) {
59             buf.append("SELECT FIRST ");
60             buf.append(queryBuilder.getLimit());
61             buf.append(" SKIP ");
62             buf.append(queryBuilder.getOffset());
63             buf.append(" * FROM (");
64             nestedQuery.appendToBuffer(buf);
65             buf.append(") limitQry");
66         }
67     }
68 }
69 }
70
71
72 def HOOK_NAME = "DATASOURCE_HELPER_FIREBIRD"
73
74 def callback = [
75     provideDatabaseHelpers : {
76         return Collections.singletonList(new Firebird());
77     }
78 ] as DatabaseHelperProviderHook;
79
80 GLOBALS.services.callbackRegistry.attachHook(HOOK_NAME, DatabaseHelperProviderHook.class, callback)
```

hookldappam.groovy

```
1 import javax.naming.AuthenticationException
2 import javax.naming.Context
3 import javax.naming.InvalidNameException
4 import javax.naming.NamingException
5 import javax.naming.directory.InitialDirContext
6 import javax.persistence.NoResultException
7
8 import net.datenwerke.rs.authenticator.client.login.dto.UserPasswordAuthToken
9 import net.datenwerke.rs.authenticator.client.login.pam.UserPasswordClientPAM
10 import net.datenwerke.rs.utils.crypto.PasswordHasher;
11 import net.datenwerke.security.client.login.AuthToken
12 import net.datenwerke.security.service.authenticator.AuthenticationResult
13 import net.datenwerke.security.service.authenticator.ReportServerPAM
14 import net.datenwerke.security.service.authenticator.hooks.PAMHook
15 import net.datenwerke.security.service.usermanager.UserManagerService
16 import net.datenwerke.security.service.usermanager.entities.User
17
18 import com.google.inject.Inject
19
20 final LdapPAM ldapPam = GLOBALS.injector.getInstance(LdapPAM.class);
21 GLOBALS.services.callbackRegistry.attachHook("LDAP_PAM", PAMHook.class, new PAMHook() {
22
23     public void beforeStaticPamConfig(LinkedHashSet < ReportServerPAM > pams) {}
24     public void afterStaticPamConfig(LinkedHashSet < ReportServerPAM > pams) {
25         /* The only PAM we allow is the current LDAP PAM.
26          * The PAM in reportserver.properties is ignored. */
27         pams.clear()
28         pams.add(ldapPam);
29     }
30
31 });
32
33
34 public class LdapPAM implements ReportServerPAM {
35
36     /* If true, RS users are allowed alongside LDAP users. If false, only LDAP users are allowed. */
37     private static final ALLOW_LOCAL_USERS = true;
38
39     private static final String CLIENT_MODULE_NAME = UserPasswordClientPAM.class.getName();
40     private UserManagerService userManagerService;
41     private PasswordHasher passwordHasher;
42
43     @Inject
44     public LdapPAM(UserManagerService userManagerService, PasswordHasher passwordHasher) {
45         this.userManagerService = userManagerService;
```

B. hookldappam.groovy

```
46     this.passwordHasher = passwordHasher;
47 }
48
49
50 public AuthenticationResult authenticate(AuthToken[] tokens) {
51     for (Object token: tokens) {
52         if (token instanceof UserPasswordAuthToken) {
53             UserPasswordAuthToken credentials = (UserPasswordAuthToken) token;
54             User u = authenticate(credentials.getUsername(), credentials.getPassword());
55             if (null != u) {
56                 //System.out.println("##### LdapPAM: authenticate success (usr=" + u.getUsername() ↵
57                 ↵ + ")")
58                 return new AuthenticationResult(true, u);
59             } else {
60                 //System.out.println("##### LdapPAM: authenticate failed (result= ↵
61                 ↵ AuthenticationResult(false, null)")
62                 return new AuthenticationResult(false, null);
63             }
64         }
65     }
66     //System.out.println("##### LdapPAM: authenticate notoken (result=AuthenticationResult(false, ↵
67     ↵ null)")
68     return new AuthenticationResult(false, null);
69 }
70
71 protected User getUserOrNull(String username) {
72     try {
73         return userManagerService.getUserByName(username);
74     } catch (NoResultException ex) {
75         return null;
76     }
77 }
78
79 public User authenticate(String username, String cleartextPassword) {
80     User user = getUserOrNull(username);
81     if (null == user)
82         return null;
83
84     if (ALLOW_LOCAL_USERS) {
85         if (null != user.getPassword() && !user.getPassword().isEmpty() && passwordHasher. ↵
86         ↵ validatePassword(user.getPassword(), cleartextPassword)) {
87             //System.out.println("##### LdapPAM: authenticate with local password: success")
88             return user;
89         } else {
90             //System.out.println("##### LdapPAM: authenticate with local password: fail")
91         }
92     }
93
94     LdapAuthenticator authenticator = new LdapAuthenticator();
95     if (authenticator.authenticate(user, cleartextPassword)) {
96         //System.out.println("##### LdapPAM: authenticate against directory server: success")
97         return user;
98     } else {
99         //System.out.println("##### LdapPAM: authenticate against directory server: failed")
100        return null;
101    }
102 }
103
104 public String getClientModuleName() {
105     return CLIENT_MODULE_NAME;
106 }
```

```

106 }
107
108
109 public class LdapAuthenticator {
110
111     public boolean authenticate(User user, String password) {
112         if (null == user.getOrigin() || null == user.getGuid())
113             return false;
114
115         Properties props = new Properties();
116
117         props.setProperty(Context.INITIAL_CONTEXT_FACTORY, "com.sun.jndi.ldap.LdapCtxFactory");
118         props.setProperty(Context.PROVIDER_URL, getProvider(user));
119         props.setProperty(Context.URL_PKG_PREFIXES, "com.sun.jndi.url");
120         props.setProperty(Context.SECURITY_AUTHENTICATION, "simple");
121
122         props.setProperty(Context.SECURITY_PRINCIPAL, getPrincipal(user));
123         props.setProperty(Context.SECURITY_CREDENTIALS, password);
124
125         try {
126             InitialDirContext ctx = new InitialDirContext(props);
127             ctx.getAttributes(getPrincipal(user));
128             return true;
129         } catch (AuthenticationException e) {
130             return false;
131         } catch (InvalidNameException e) {
132             throw new RuntimeException(e);
133         } catch (NamingException e) {
134             if (e.getMessage().contains("LdapErr: DSID-0C0906E8")) {
135                 return false;
136             }
137
138         }
139     }
140
141     private String getProvider(User user) {
142         String origin = user.getOrigin();
143         int i = origin.lastIndexOf("/");
144
145         return origin.substring(0, i);
146     }
147
148     private String getPrincipal(User user) {
149         String origin = user.getOrigin();
150
151         int i = user.getOrigin().lastIndexOf("/");
152         return origin.substring(i + 1);
153     }
154 }
155
156 }

```

ldapimport.groovy

```
1 package ldap
2
3 import java.util.Map.Entry
4 import java.util.logging.Level
5 import java.util.logging.Logger
6
7 import javax.naming.Context
8 import javax.naming.NamingEnumeration
9 import javax.naming.NamingException
10 import javax.naming.directory.Attribute
11 import javax.naming.directory.DirContext
12 import javax.naming.directory.InitialDirContext
13 import javax.naming.directory.SearchControls
14 import javax.naming.directory.SearchResult
15 import javax.naming.ldap.LdapName
16
17 import net.datenwerke.security.service.usermanager.UserManagerService
18 import net.datenwerke.security.service.usermanager.entities.AbstractUserManagerNode
19 import net.datenwerke.security.service.usermanager.entities.Group
20 import net.datenwerke.security.service.usermanager.entities.OrganisationalUnit
21 import net.datenwerke.security.service.usermanager.entities.User
22
23
24
25
26 UserManagerService userManagerService = GLOBALS.getRsService(UserManagerService.class);
27
28 LdapUserLoader lul = new LdapUserLoader();
29
30 lul.setProviderUrl("ldap://directory.example.com:389");
31 lul.setSecurityPrincipal("CN=ldaptest,CN=Users,DC=directory,DC=example,DC=com");
32 lul.setSecurityCredentials("ldaptest");
33
34 lul.setLdapBase("OU=EXAMPLE,DC=directory,DC=example,DC=com");
35 OrganisationalUnit targetNode = (GLOBALS.findObject("/usermanager/external"));
36
37 if(null == targetNode){
38     AbstractUserManagerNode umRoot = userManagerService.getRoots().get(0);
39     targetNode = new OrganisationalUnit("external");
40     umRoot.addChild(targetNode);
41     userManagerService.persist(targetNode);
42 }
43
44 lul.setTargetNode(targetNode);
45 lul.run();
```

C. Ldapimport.groovy

```
46
47
48 public class LdapUserLoader {
49
50     private final Logger logger = Logger.getLogger(getClass().getName());
51
52
53     private String ldapBase;
54     private String ldapFilter = "(|(objectClass=organizationalUnit)(objectClass=user)(objectClass=group))" ↵
55         ↵ ;
56
57     private String providerUrl;
58     private String securityCredentials;
59
60     private String securityPrincipal;
61     private OrganisationalUnit targetNode;
62
63     private boolean includeNamespace = false;
64
65     private Map<String, AbstractUserManagerNode> guidMap;
66     private Map<LdapName, AbstractUserManagerNode> nodesInDirectoryByName;
67     private Map<String, AbstractUserManagerNode> nodesInDirectoryByGuid;
68     private TreeMap<LdapName, SearchResult> searchResults;
69
70     private List<AbstractUserManagerNode> removedNodes;
71     private List<AbstractUserManagerNode> addedNodes;
72
73
74     private class AdGUID {
75         byte[] bytes;
76
77         public AdGUID(byte[] bytes) {
78             this.bytes = bytes;
79         }
80
81         private void addByte(StringBuffer sb, int k) {
82             if(k<=0xF)
83                 sb.append("0");
84             sb.append(Integer.toHexString(k));
85         }
86
87         @Override
88         public String toString() {
89             StringBuffer sb = new StringBuffer();
90             addByte(sb, (int)bytes[3] & 0xFF);
91             addByte(sb, (int)bytes[2] & 0xFF);
92             addByte(sb, (int)bytes[1] & 0xFF);
93             addByte(sb, (int)bytes[0] & 0xFF);
94             sb.append("-");
95             addByte(sb, (int)bytes[5] & 0xFF);
96             addByte(sb, (int)bytes[4] & 0xFF);
97             sb.append("-");
98             addByte(sb, (int)bytes[7] & 0xFF);
99             addByte(sb, (int)bytes[6] & 0xFF);
100            sb.append("-");
101            addByte(sb, (int)bytes[8] & 0xFF);
102            addByte(sb, (int)bytes[9] & 0xFF);
103            sb.append("-");
104            addByte(sb, (int)bytes[10] & 0xFF);
105            addByte(sb, (int)bytes[11] & 0xFF);
106            addByte(sb, (int)bytes[12] & 0xFF);
107            addByte(sb, (int)bytes[13] & 0xFF);
108            addByte(sb, (int)bytes[14] & 0xFF);
```

```
109     addByte(sb, (int)bytes[15] & 0xFF);
110
111     return sb.toString();
112 }
113
114 }
115
116 public LdapUserLoader() {
117
118 }
119
120
121 public String getLdapBase() {
122     return ldapBase;
123 }
124
125 public String getProviderUrl() {
126     return providerUrl;
127 }
128
129 public String getSecurityCredentials() {
130     return securityCredentials;
131 }
132
133 public String getSecurityPrincipal() {
134     return securityPrincipal;
135 }
136
137 public void setLdapBase(String ldapBase) {
138     this.ldapBase = ldapBase;
139 }
140
141 public void setProviderUrl(String providerUrl) {
142     this.providerUrl = providerUrl;
143 }
144
145 public void setSecurityCredentials(String securityCredentials) {
146     this.securityCredentials = securityCredentials;
147 }
148
149 public void setSecurityPrincipal(String securityPrincipal) {
150     this.securityPrincipal = securityPrincipal;
151 }
152
153 public void setTargetNode(OrganisationalUnit targetNode) {
154     this.targetNode = targetNode;
155 }
156
157 public boolean isIncludeNamespace() {
158     return includeNamespace;
159 }
160
161 public void setIncludeNamespace(boolean includeNamespace) {
162     this.includeNamespace = includeNamespace;
163 }
164
165 public String getLdapFilter() {
166     return ldapFilter;
167 }
168
169 public void setLdapFilter(String ldapFilter) {
170     this.ldapFilter = ldapFilter;
171 }
172
```

C. Ldapimport.groovy

```
173
174
175 private Properties compileProperties(){
176     Properties props = new Properties();
177
178     props.setProperty(Context.INITIAL_CONTEXT_FACTORY, "com.sun.jndi.ldap.LdapCtxFactory");
179     props.setProperty(Context.PROVIDER_URL, providerUrl);
180     props.setProperty(Context.URL_PKG_PREFIXES, "com.sun.jndi.url");
181     props.setProperty(Context.REFERRAL, "throw");
182     props.setProperty(Context.SECURITY_AUTHENTICATION, "simple");
183
184     props.setProperty(Context.SECURITY_PRINCIPAL, securityPrincipal);
185     props.setProperty(Context.SECURITY_CREDENTIALS, securityCredentials);
186
187     /* return these as binary */
188     props.put("java.naming.ldap.attributes.binary", "objectGUID");
189     return props;
190 }
191
192 private void createGuidMap(AbstractUserManagerNode current) {
193     Map<String, AbstractUserManagerNode> map = new HashMap<>();
194     createGuidMap(current, map );
195
196     guidMap = map;
197 }
198
199 private void createGuidMap(AbstractUserManagerNode current, Map<String, AbstractUserManagerNode> map){
200     map.put(current.getGuid(), current);
201
202     for(AbstractUserManagerNode cn : current.getChildren()){
203         createGuidMap(cn, map);
204     }
205 }
206
207 private String getStringAttribute(SearchResult sr, String attributeName) throws NamingException{
208     try{
209         return sr.getAttributes().get(attributeName).get().toString();
210     }catch(Exception e){
211         logger.log(Level.WARNING, "failed to retrieve attribute '" + attributeName + "' from " + sr. ↵
212             ↵ getNameInNamespace(), e);
213     }
214 }
215
216 private String getGuid(SearchResult sr) throws NamingException{
217     try{
218         AdGUID guid = new AdGUID((byte[]) sr.getAttributes().get("objectGUID").get());
219         return guid.toString();
220     }catch(Exception e){
221         throw new RuntimeException("failed to retrieve objectGUID from " + sr.getNameInNamespace(), e);
222     }
223 }
224
225 private void loadFromDirectory() throws NamingException {
226     Properties props = compileProperties();
227     String originBase = this.providerUrl.endsWith("/")?providerUrl:providerUrl + "/";
228
229     this.nodesInDirectoryByName = new HashMap<>();
230     this.nodesInDirectoryByGuid = new HashMap<>();
231     this.addedNodes = new ArrayList<>();
232     this.removedNodes = new ArrayList<>();
233
234     DirContext ctx = null ;
235
```

```

236     try {
237         ctx = new InitialDirContext(props);
238
239         SearchControls searchControls = new SearchControls();
240         searchControls.setSearchScope(SearchControls.SUBTREE_SCOPE);
241
242         LdapName ldapBaseName = new LdapName(getLdapBase());
243         NamingEnumeration<SearchResult> results = ctx.search(ldapBaseName, this.ldapFilter, searchControls) ↵
                ↵ ;
244
245         /* order search results by name to make sure children never get processed before their parent */
246         searchResults = new TreeMap<>();
247         while (results.hasMoreElements()) {
248             SearchResult sr = (SearchResult) results.next();
249             searchResults.put(new LdapName(sr.getNameInNamespace()), sr);
250         }
251
252         for(SearchResult sr : searchResults.values()){
253             try {
254                 LdapName nodeName = new LdapName(isIncludeNamespace() ? sr.getNameInNamespace() : sr.getName()) ↵
                        ↵ ;
255                 LdapName nodeNameInNamespace = new LdapName(sr.getNameInNamespace());
256
257                 /* skip empty nodes */
258                 if(nodeName.size() == 0)
259                     continue;
260
261
262                 /* get parent node */
263                 LdapName parentName = (LdapName) nodeNameInNamespace.getPrefix(Math.max(0, nodeNameInNamespace. ↵
                        ↵ size() - 1));
264                 AbstractUserManagerNode parent = this.nodesInDirectoryByName.get(parentName);
265                 if(null == parent){
266                     if(parentName.equals(new LdapName(ldapBase))){
267                         /* root node */
268                         parent = targetNode;
269                     }else{
270                         throw new IllegalStateException("Missing parent for " + sr.getNameInNamespace());
271                     }
272                 }
273
274                 /* create node */
275                 Attribute objectClass = sr.getAttributes().get("objectClass");
276                 AbstractUserManagerNode umNode = null;
277                 if(objectClass.contains("organizationalUnit")) {
278                     umNode = createOUNode(sr, parent);
279
280                 } else if(objectClass.contains("user")) {
281                     umNode = createUserNode(sr, parent);
282
283                 } else if(objectClass.contains("group")){
284                     umNode = createGroupNode(sr, parent);
285                 }
286
287                 /* set common attributes */
288                 umNode.setWriteProtection(true);
289                 umNode.setGuid(getGuid(sr));
290                 umNode.setOrigin(originBase + sr.getNameInNamespace());
291
292                 nodesInDirectoryByName.put(new LdapName(sr.getNameInNamespace()), umNode);
293                 nodesInDirectoryByGuid.put(getGuid(sr), umNode);
294             }catch(Exception e){
295                 throw new RuntimeException("Error processing search result: " + sr.getNameInNamespace() , e);
296             }

```

C. ldapimport.groovy

```
297     }
298
299
300   }finally{
301     try {
302       if(null != ctx)
303         ctx.close();
304     } catch (NamingException e) {
305       logger.log(Level.WARNING, e.getMessage(), e);
306     }
307   }
308 }
309
310
311 private AbstractUserManagerNode createGroupNode(SearchResult sr, AbstractUserManagerNode parent) throws NamingException {
312     Group node = (Group) guidMap.get(getGuid(sr));
313     if(null == node){
314         node = new Group();
315         addedNodes.add(node);
316     }
317     parent.addChild(node);
318
319     /* copy Group attributes */
320     node.setName(getStringAttribute(sr, "name"));
321
322     return node;
323 }
324
325
326 private AbstractUserManagerNode createUserNode(SearchResult sr, AbstractUserManagerNode parent) throws NamingException {
327     User node = (User) guidMap.get(getGuid(sr));
328     if(null == node){
329         node = new User();
330         addedNodes.add(node);
331     }
332     parent.addChild(node);
333
334     /* copy User attributes */
335     node.setFirstname(getStringAttribute(sr, "givenName"));
336     node.setLastname(getStringAttribute(sr, "sn"));
337     node.setUsername(getStringAttribute(sr, "sAMAccountName"));
338
339     return node;
340 }
341
342 private AbstractUserManagerNode createOUNode(SearchResult sr, AbstractUserManagerNode parent) throws NamingException {
343     OrganisationalUnit node = (OrganisationalUnit) guidMap.get(getGuid(sr));
344     if(null == node){
345         node = new OrganisationalUnit();
346         addedNodes.add(node);
347     }
348     parent.addChild(node);
349
350     /* copy OU attributes */
351     node.setName(getStringAttribute(sr, "name"));
352
353     return node;
354 }
355
356
357 private void postprocessGroups() throws NamingException {
```

```

358
359  /* clear */
360  for(Entry<LdapName, AbstractUserManagerNode> entry : nodesInDirectoryByName.entrySet()){
361      if(entry.getValue() instanceof Group){
362          Group group = (Group) entry.getValue();
363          group.getUsers().clear();
364          group.getOus().clear();
365          group.getReferencedGroups().clear();
366      }
367  }
368
369  /* add appropriate users */
370  for(Entry<LdapName, AbstractUserManagerNode> entry : nodesInDirectoryByName.entrySet()){
371      if(entry.getValue() instanceof Group){
372          Group group = (Group) entry.getValue();
373          SearchResult sr = searchResults.get(entry.getKey());
374          if(null != sr.getAttributes().get("member")){
375              NamingEnumeration<?> members = sr.getAttributes().get("member").getAll();
376              while(members.hasMore()){
377                  LdapName memberName = new LdapName(members.next().toString());
378                  AbstractUserManagerNode member = nodesInDirectoryByName.get(memberName);
379                  if(null != member){
380                      if(member instanceof User)
381                          group.addUser((User) member);
382                      if(member instanceof OrganisationalUnit)
383                          group.addOu((OrganisationalUnit) member);
384                      if(member instanceof Group)
385                          group.addReferencedGroup((Group) member);
386                  }
387              }
388          }
389      }
390  }
391 }
392
393 private void printTree(AbstractUserManagerNode current){
394     StringBuilder sb = new StringBuilder();
395     List<AbstractUserManagerNode> rl = current.getRootLine();
396     Collections.reverse(rl);
397     for(AbstractUserManagerNode node : rl){
398         sb.append(node.getName()).append(".");
399     }
400     sb.append(current.getName() + " [" + current.getClass().getSimpleName() + "]" );
401
402     if(current instanceof Group){
403         Group group = (Group) current;
404         sb.append(" (").append(group.getUsers().size() + group.getOus().size() + group.getReferencedGroups
405             ↵ ().size()).append(" members)");
406     }
407     System.out.println(sb.toString());
408
409     for(AbstractUserManagerNode cn : current.getChildren()){
410         printTree(cn);
411     }
412 }
413
414
415 private void deleteRemovedUsers(AbstractUserManagerNode current) {
416     for(AbstractUserManagerNode c : current.getChildren()){
417         deleteRemovedUsers(c);
418     }
419
420     if(null != current.getOrigin() && current.getOrigin().startsWith(providerUrl) && ! ↵

```

C. ldapimport.groovy

```

    ↪ nodesInDirectoryByGuid.containsKey(current.getGuid())){
421     current.getParent().removeChild(current);
422     removedNodes.add(current);
423 }
424 }
425
426 public void run() throws NamingException{
427     createGuidMap(targetNode);
428
429     loadFromDirectory();
430     postprocessGroups();
431
432     deleteRemovedUsers(targetNode);
433
434     System.out.println("Retrieved nodes from directory: " + nodesInDirectoryByGuid.size() );
435     System.out.println("Nodes added: " + addedNodes.size() );
436     System.out.println("Nodes removed: " + removedNodes.size() );
437     int overallCount = countNodes(targetNode) - 1;
438     System.out.println("Overall nodes in rs: " + overallCount);
439
440     if(overallCount != nodesInDirectoryByGuid.size())
441         throw new RuntimeException("Failed to import user data from directory");
442     else
443         System.out.println("done.");
444
445     // printTree(targetNode);
446 }
447
448
449 private int countNodes(AbstractUserManagerNode current) {
450     int i = 1;
451     for(AbstractUserManagerNode n : current.getChildren()){
452         i += countNodes(n);
453     }
454     return i;
455 }
456
457 }
```